



THIS IS A SINGLE FACED DROP-IN DISPLAY TO BE MOUNTED IN A RECTANGULAR OPENING IN A LARGER SIGN.

DIMENSIONS ARE IN INCHES [MILLIMETERS].

USE HOLES IN THE FRONT FLANGES OF THE CABINET TO ATTACH THE DISPLAY TO THE SIGN FACE USING APPROPRIATE HARDWARE.

DAKTRONICS IS NOT RESPONSIBLE FOR THE MOUNTING STRUCTURE OR FOR THE ADEQUACY OF ATTACHMENT TO THE STRUCTURE. STRUCTURE AND ATTACHMENT MUST CONFORM TO ALL APPLICABLE BUILDING CODES.

THE OVERALL SIGN STRUCTURE MUST BE DESIGNED WITH SUFFICIENT VENTILATION SO THAT AIR AROUND THE DISPLAY DOES NOT EXCEED 120°F [49°C].

THE DISPLAY IS FRONT VENTILATED. NO PORTION OF THE FACE MAY BE COVERED.

SIGNAL INTERCONNECT CABLES ARE PROVIDED AND MUST BE ROUTED AND CONNECTED WHEN MULTIPLE DISPLAYS ARE INSTALLED WITHIN A SINGLE SIGN.

THIS DISPLAY IS A UL RECOGNIZED COMPONENT.

REFER TO THE DISPLAY MANUAL FOR COMMUNICATION OPTIONS AND INSTALLATION INSTRUCTIONS.



FEATURE	
DIGIT HEIGHT	8" [203 MM]
DIGIT LED COLOR	RED, AMBER, OR GREEN
CABINET COLOR	SEMI-GLOSS BLACK
SERVICE ACCESS	FRONT ONLY
CABINET MATERIAL	0.050 [1.3] ALUMINUM SHEET
EST. WEIGHT	10 LB [5 KG]
MAX. OPER. TEMP.	120°F [49°C]
PRIMARY VOLTS	100V - 240V AC
MAX. POWER	30 W

 DAKTRONICS, INC. BROOKINGS, SD 57006 DO NOT SCALE DRAWING		THE CONCEPTS EXPRESSED AND DETAILS SHOWN ON THIS DRAWING ARE CONFIDENTIAL AND PROPRIETARY. DO NOT REPRODUCE BY ANY MEANS WITHOUT THE EXPRESSED WRITTEN CONSENT OF DAKTRONICS, INC. COPYRIGHT 2011 DAKTRONICS, INC.	
PROJ: FUELIGHT DISPLAYS			
TITLE: SHOP DRAWING, FL-3000-8-DI			
DESIGN: A VANBEMMEL		DRAWN: A VANBEMMEL	
SCALE: 8/100		DATE: 07-MAY-13	
SHEET: 1 OF 1	REV: 02	JOB NO: P 1611	FUNC-TYPE-SIZE: R - 08 - A
			1086408

02	07 MAY 13	REVISED TEMPERATURE RATINGS.	AVB
01	05 JUN 12	UPDATED WEIGHT.	AVB
REV	DATE:		BY: