

1 1ST FLOOR ELECTRICAL PLAN E-101 1/4" = 1'-0"

ELECTRICAL NOTES:

- 1) ALL DIMMERS, SWITCHES, WALL PLATES & ENVIRONMENTAL CONTROLS TO BE LUTRON
- 2) ALL HVAC GRILLES TO BE TITUS 3) ALL ELECTRICAL WORK SHALL BE PERFORMED BY A LICENSED ELECTRICIAN WHO SHALL ARRANGE FOR AND OBTAIN INSPECTIONS AND REQUIRED SIGN-OFFS.
- 4) ALL DIMMABLE FIXTURES TO BE COORDINATED W/ DIMMERS BY ELECTRICIAN
- 5) ALL WIRING TO BE CONCEALED IN WALLS
- 6) LOCATION OF FIXTURES TO BE COORDINATED PRIOR TO INSTALLATION 7) SEE LIGHTING SCHEDULE FOR FIXTURE TYPE. 8) ELECTRICIAN SHALL SUPPLY AND INSTALL ALL
- (TELEPHONE AND COMPUTER) CAT OR EQUAL. 9) CONTRACTOR TO REVIEW ALL OUTLETS WITH

WIRING & TERMINATIONS FOR LOW VOLTAGE

- DESIGNER PRIOR TO INSTALLATION. 10) ALL OUTLETS IN KITCHEN AND BATHROOM TO BE
- GROUND FAULT INTERRUPTED. 11) ALL ELECTRICAL FIXTURES TO BE REVIEWED W/
- DESIGNER PRIOR TO ORDER & INSTALLATION
- 12) All BATHROOM EXHAUST FANS TO BE NUTONE 13) ALL CEILING FINISHES TO BE PAINTED GWB
- UNLESS OTHERWISE NOTED.

ELECTRICAL SYMBOLS WALL SWITCH SPECIAL SWITCH TYPES: 3 - THREE WAY 4 - FOUR WAY D — DIMMER E - EXISTING LOCATION K – KEY OPERATED OC- OCCUPANT SENSOR P - PILOT LIGHTED JS JAMB SWITCH/DOOR SWITCH EXIT LIGHT

WALL MOUNTED DOUBLE DUPLEX RECEPTACLE GFI — GROUND FAULT INTERUPTER D — DEDICATED DUPLEX RECEPTACLE E - EXISTING RECEPTACLE C - CLOCK RECEPTACLE SP - SURGE PROTECTION RECEPTACLE IG — ISOLATED GROUND RECEPTACLE

- WALL MOUNTED DOUBLE DUPLEX RECEPTACLE WALL MOUNTED SPECIAL PURPOSE WALL MOUNTED SPECIAL FOR OSE RECEPTACLE SIZE AND TYPE AS INDICATED ON PLANS
- WALL MOUNTED 208V, 1 PHASE RECEPTACLE 9 30A NUMBER INDICATES RATED AMPERAGE CEILING MOUNTED DUPLEX CONVENIENCE
- RECEPTACLE CEILING MOUNTED JUNCTION BOX J FLOOR MOUNTED JUNCTION BOX
- WALL MOUNTED JUNCTION BOX 4" SQUARE BACKBOX FOR WALL MOUNTED DATA OUTLET
- 4" SQUARE BACKBOX FOR WALL MOUNTED TELE/DATA OUTLET
- 4" SQUARE BACKBOX FOR WALL MOUNTED TELEPHONE OUTLET 4" SQUARE BACKBOX FOR WALL MOUNTED CABLE TELEVISION
- INTERCOM STATION
- FIRE ALARM PULL BOX SMOKE/CO DETECTOR WITH SOUNDER BASE,
- 120V CONNECTION AND DRY CONTACT HEAT DETECTOR WITH SOUNDER BASE, 120V CONNECTION AND DRY CONTACT
- VA VISUAL ALARM CONNECTED TO SP SP STROBE PANEL EMERGENCY LIGHT

B-SCAN:

DWG. CONTENTS: **FIRST FLOOR ELECTRICAL PLAN**

September 5, 2014 SCALE: 1/4" = 1'-0"

DWG. BY: PROJECT NO.: 008 DWG. NO.: E-101

SHEET NO.:

660-662 CONGRESS STREET

PORTLAND, MAINE

PRESENT ARCHITECTURE PLLC

66 WEST BROADWAY, SUITE 306 NEW YORK, NY, 10007 T: (207) 449-8513

CONTRACTOR: BAYHILL BUILDING & DESIGN

P.O. BOX 179 SOUTH FREEPORT, ME 04078 T: (207) 865-9351

STRUCTURAL ENGINEER: ENGINEERING DESIGN PROFESSIONALS

P.O. BOX 575 FREEPORT, ME 04032 T: (207) 865-9505

A.K. LONGFELLOW LLC

660 CONGRESS STREET PORTLAND, ME 04101





