

Pinnacle Series

CLAD DOUBLE HUNG

DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

Operating							
Glass Size	16	20	24	28	32	36	40
	Width						
16	35	35	35	35	35	35	35
20	35	35	35	35	35	35	35
22	35	35	35	35	35	35	35
24	35	35	35	35	35	35	35
26	35	35	35	35	35	35	35
28	35	35	35	35	35	30	30
30	35	35	35	35	35	30	30
32	35	35	35	35	35	30	30
34	35	35	35	30	30	30	30
36	35	35	35	30	30	30	30
Oriel / Cottage DH							
24/36	35	35	30	30	30	30	30
Oriel / Cottage SH							
46/28	30	30	25	20	20	NA	NA
52/28	30	30	20	20	20	NA	NA
58/28	30	25	20	20	20	NA	NA

Picture										
Glass Size	8	10	12	20	24	28	32	44	56	68
	Width									
42	30	30	30	30	30	30	30	30	30	30
46	30	30	30	30	30	30	30	30	30	30
50	30	30	30	30	30	30	30	30	30	30
54	30	30	30	30	30	30	30	30	30	30
58	30	30	30	30	30	30	30	30	30	30
62	30	30	30	30	30	30	30	30	30	30
66	30	30	30	30	30	30	30	30	30	30
70	30	30	30	30	30	30	30	30	30	30

Transom										
Glass Size	16	20	24	28	32	36	40	44	56	68
	Width									
8	40	40	40	40	40	40	40	40	40	35
10	40	40	40	40	40	40	40	40	40	35
12	40	40	40	40	40	40	40	40	40	35
20	40	40	40	40	40	40	40	40	40	30
26	40	40	40	40	40	40	40	40	40	30
32	40	40	40	40	40	40	40	40	40	30

Note: Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

Minimum and Maximum Measurements			
Minimum Frame Width	Minimum Frame Height	Maximum Frame Width	Maximum Frame Height
Operating			
1-9 3/8	2-8 3/4	3-9 3/8	6-8 3/4
Picture			
1-1 3/8	2-10 3/4	6-1 3/8	6-4 3/4
Transom			
1-9 3/8	1-0	6-1 3/8	3-0