



Black

LG265S1K-A3

60 cell


MonoX[™] series are LG Electronics' high-quality monocrystalline module brands. The quality is the result of our strong commitment to developing a module to improve benefits for customers. Features of MonoX™ series include higher efficiency and durability, convenient installation, and aesthetic exterior.











With LG,



LIGHT AND ROBUST

With a weight of just 16.8 kg (36.96 lb), LG modules are proven to demonstrate outstanding durability against external pressure up to 5400 Pa.



100% EL TEST COMPLETED

All LG modules pass Electroluminescence inspection. This EL inspection detects cracks and other imperfections unseen by the naked eye.



RELIABLE WARRANTIES

LG stands by its products with the strength of a global corporation and sterling warranty policies. LG offers a 10 year product limited warranty and a 25 year limited linear output warranty.



CONVENIENT INSTALLATION

LG modules are carefully designed to benefit installers by allowing quick and easy installations throughout the carrying, grounding, and connecting stages of modules.



THE EXTRA 2% POWER

POSITIVE POWER TOLERANCE

To minimize losses due to mismatch, LG produces 3 groups of solar modules which are sorted by its current class. This enables MonoX[™] to maximize the system's output by around 2% based off the theoretical calculation.



LG provides rigorous quality testing to solar modules

to assure customers of the stated power outputs of all modules, with a positive nominal tolerance starting at 0%.

About LG Electronics



MECHANICAL PROPERTIES

Cells	6 x 10
Cell vendor	LG
Cell type	Monocrystalline
Cell dimensions	156 x 156 mm / 6 x 6 in
# of busbar	3
Dimensions (L x W x H)	1640 x 1000 x 35 mm
	64.57 x 39.37 x 1.38 in
Static snow load	5400 Pa / 113 psf
Static wind load	2400 Pa / 50 psf
Weight	16.8 ± 0.5 kg / 36.96 ± 1.1 lb
Connector type	MC4 connector IP 67
Junction box	IP 67 with 3 bypass diodes
Length of cables	2 x 1000 mm / 2 x 39.37 in
Glass	High transmission tempered glass
Frame	Anodized aluminum

CERTIFICATIONS AND WARRANTY


Certifications (In Progress)	IEC 61215, IEC 61730-1/-2,
	UL 1703, ISO 9001
Product warranty	10 years
Output warranty of Pmax (measurement Tolerance ± 3%)	Linear warranty*


 $^{^{\}star}$ 1) 1st year: 97%, 2) After 2nd year: 0.7%p annual degradation, 3) 80.2% for 25 years

TEMPERATURE COEFFICIENTS

NOCT	47.0 ± 2 °C
Pmpp	-0.44 %/°C
Voc	-0.31 %/°C
lsc	0.05 %/℃

CHARACTERISTIC CURVES





ELECTRICAL PROPERTIES (STC*)

	LG265S1K-A3	
Maximum power at STC (Pmpp)	265	
MPP voltage (Vmpp)	31.5	
MPP current (Impp)	8.42	
Open circuit voltage (Voc)	38.4	
Short circuit current (Isc)	9.03	
Module efficiency (%)	16.2	
Operating temperature (°C)	-40 ~ +90	
Maximum system voltage (V)	1000 (IEC), 600 (UL)	
Maximum series fuse rating (A)	15	
Power tolerance (%)	0 ~ +3	


^{*} STC (Standard Test Condition): Irradiance 1000 W/m², module temperature 25 °C, AM 1.5 $\,$

ELECTRICAL PROPERTIES (STC*)

	LG265S1K-A3
Maximum power at STC (Pmpp)	192
MPP voltage (Vmpp)	28.6
MPP current (Impp)	6.72
Open circuit voltage (Voc)	35.3
Short circuit current (Isc)	7.30
Efficiency reduction (from 1000 W/m² to 200 W/m²)	< 4.5 %

^{*} NOCT (Nominal Operating Cell Temperature): Irradiance 800 W/m², ambient temperature 20 °C, wind speed 1 m/s

DIMENSIONS (MM/IN)





North America Solar Business Team LG Electronics U.S.A. Inc 1000 Sylvan Ave, Englewood Cliffs, NJ 07632

Contact: lg.solar@lge.com www.lgsolarusa.com

Product specifications are subject to change without notice. "LG Life's Good" is a registrated trademark of LG Corp. All other trademarks are the property of their respective owners. DS-A3-60-K-US-F-EN-31002





^{*} The nameplate power output is measured and determined by LG Electronics at its sole and absolute discretion.