



HIGH ROOF FRAMING PLAN

NOTES:
 1. SEE SHEET S-1.0 FOR GENERAL STRUCTURAL NOTES AND ADDITIONAL INFORMATION.
 2. COORDINATE ALL MECHANICAL & CHASES ETC. W/ ARCH AND MECHANICAL DRAWINGS -TYP.
 3. VERIFY ROOFTOP MECHANICAL EQUIPMENT WEIGHTS PRIOR TO CONSTRUCTION.
 4. VERIFY ROOF PITCH AND DRAINAGE W/ ARCH -TYP.
 5. ALL SMALL FRAME BEAMS @ OPENINGS ETC. SHALL BE W8x28 -TYP UNO
 6. ALL ROOF DECKING SHALL BE 1.5" B 22 STEEL DECK (22GA) W/ 5/8"Ø PUDDLE WELDS @ 12", (36/4 PATTERN) AND (3) #10 TEK SCREW SIDE LAP FASTENERS PER SPAN.
 7. T.O. STL BEAM ELEV = [XX-XXX'] -TYP UNO.

SCALE: 1/8"=1'-0"

FRAMING KEY

	INDICATES DROPPED BEAM -TYP UNO
	INDICATES FLUSH TOP BEAM -TYP UNO
	INDICATES X-BRACED BAY BELOW
	INDICATES W8x28 DRAG STRUT W/ (10) 3/4"Ø x 3 1/2" H.L.S. -TYP UNO
	INDICATES BEAM END W/ MOMENT CONN.
	INDICATES COL CONT. (SPICES, SEE COL. SCHD.)
	INDICATES COL ABOVE, SEE COL. SCHD.
	INDICATES COL BELOW
	INDICATES DECKING SPAN -TYP