2.) G.C. TO CONFRIM AND COORDINATE ALL ROUGH FRAMING DIMENSIONS FOR TUBS, SHOWERS, BUILT-IN FIXTURES ETC. G.C. TO CONFRIM AND COORDINATE ALL CABINETRY AND APPLIANCES DIMENSIONS		
3.) PROVIDE APPROPRIATE FIRE TREATED BLOCKING IN WALLS BEHIND ALL FIXTURES, PARTITIONS AND ACCESSORIES. BLOCKING FOR GRAB BARS TO BE PROVIDED IN WALLS OF BATHROOMS IN ALL UNITS		
4.) PROVIDE MOISTURE RESISTANT GWB AT ALL WALLS AND CEILINGS IN BATHROOMS TYPICAL		
5.) SET A	LL CLO	OTHES WASHERS IN PANS WITH WATER SENSOR
6.) REFER TO ELECTRICAL AND MECHANICAL DRAWINGS FOR ADDITIONAL INFORMATION REGARDING, LIGHTING, DIFFUSERS, ETC.		
		RE EXTINGUISHER ON BRACKET IN BASE CABINET CHEN SINK - TYPICAL
		WATER HEATER FROM DECK ABOVE. (SEE DETAIL . UNIT DETAILS SHEET)
ARE I	N ADD	DPPED SOFFITS AND CEILINGS ARE SHOWN, THESE ITION TO THE FIRE RATED GWB CEILING ABOVE ART OF THE RATED ASSEMBLY
10.) WHERE PLUMBING VALVES (TUB, SHOWER, ETC) ARE LOCATED IN FIRE RATED WALLS, PROVIDE FIRE RATED BOX IN WALL FOR VALVE TO BE INSTALLED WITHIN		
CABINE	TRY /	AND APPLIANCE ABBREVIATIONS
DB = DRAWER BASE		
DRB = DOOR BASE		
SB = SINK BASE WC = WALL CABINET		
WC = WALL CABINET WC(24) = WALL CABINET 24" DEEP		
PU = PANTRY UNIT 24" DEEP		
OS = OPEN SHELVES		
RA = RANGE DW = DISHWASHER		
		EFRIGERATOR
REFLEC	TED	CEILING PLAN AND LIGHTING LEGEND
SYMBOL	TAG	DESCRIPTION
\bigcirc	А	SURFACE MOUNT - TBD
\bigcirc	В	SURFACE MOUNTED - TBD
\bigcirc	С	SURFACE MOUNT - IN CLOSETS
	D	SURFACE MOUNTED ON WALL ABOVE DOOR
\square	Е	WALL SCONCE IN BATHROOM OVER VANITY
\bigcirc	F	SURFACE MOUNT - WET LOCATION
$\overline{\bigcirc}$	н	SURFACE MOUNT CENTER IN BEDROOMS
\bigcirc	J	SURFACE MOUNT - WET LOCATION
\Box	К	EXTERIOR CUT OFF DOWN LIGHT
		CEILING GRILLE
	L	1

MATCH THE CEILING THEY ARE INSTALLED WITHIN UNIT NOTES 1.) CEILING HEIGHTS, WINDOW HEAD AND SILL HEIGHTS VARY

2.) G.C. TO CONFRIM AND COORDINATE ALL ROUGH FRAMING

TO BUILDING SECTIONS AND WALL SECTIONS

FROM FLOOR TO FLOOR, INTERIOR ELEVATIONS GRAPHICALLY DEPICT ONE FLOOR ONLY, FOR HEIGHT INFORMATION REFER

AND CONTROL JOINTS 4.) ALL ACCESS PANELS TO BE FIRE RATED TO

3.) G.C. TO PROVIDE METAL FRAMING AND BLOCKING REQUIRED FOR ALL ACCESS PANELS

2.) G.C. TO PROVIDE ACCESS PANELS AS REQUIRED FOR ALL ELEMENTS (SPRINKLER, VALVES, ETC) NOT SHOWN ON THIS REFLECTED CEILING PLAN)

1.) G.C. TO COORDINATE LOCATIONS OF PLUMBING CLEAN OUTS WITH ACCESS PANELS AS SHOWN ON REFLECTED CEILING PLANS

REFLECTED CEILING PLAN NOTES



