1.) G.C. TO COORDINATE LOCATIONS OF PLUMBING

CLEAN OUTS WITH ACCESS PANELS AS SHOWN ON

REFLECTED CEILING PLAN NOTES

UNIT NOTES

ETC.

REFLECTED CEILING PLANS

2.) G.C. TO PROVIDE ACCESS PANELS AS REQUIRED

FOR ALL ELEMENTS (SPRINKLER, VALVES, ETC) NOT

SHOWN ON THIS REFLECTED CEILING PLAN)

3.) G.C. TO PROVIDE METAL FRAMING AND

BLOCKING REQUIRED FOR ALL ACCESS PANELS AND CONTROL JOINTS

4.) ALL ACCESS PANELS TO BE FIRE RATED TO

MATCH THE CEILING THEY ARE INSTALLED WITHIN

.) CEILING HEIGHTS, WINDOW HEAD AND SILL HEIGHTS VARY

2.) G.C. TO CONFRIM AND COORDINATE ALL ROUGH FRAMING

TO BUILDING SECTIONS AND WALL SECTIONS

APPLIANCES DIMENSIONS

BATHROOMS IN ALL UNITS

CEILINGS IN BATHROOMS TYPICAL

BELOW KITCHEN SINK - TYPICAL

ON TYPICAL UNIT DETAILS SHEET)

WHICH IS PART OF THE RATED ASSEMBLY

WALL FOR VALVE TO BE INSTALLED WITHIN

CABINETRY AND APPLIANCE ABBREVIATIONS

REFLECTED CEILING PLAN AND LIGHTING LEGEND

SURFACE MOUNT - IN CLOSETS

D SURFACE MOUNTED ON WALL ABOVE DOOR

E WALL SCONCE IN BATHROOM OVER VANITY

EXTERIOR CUT OFF DOWN LIGHT

H SURFACE MOUNT CENTER IN BEDROOMS SURFACE MOUNT - WET LOCATION

 F
 SURFACE MOUNT - WET LOCATION

WC(24) = WALL CABINET 24" DEEP

A SURFACE MOUNT - TBD

B SURFACE MOUNTED - TBD

CEILING GRILLE

PU = PANTRY UNIT 24" DEEP

DB = DRAWER BASE

WC = WALL CABINET

OS = OPEN SHELVES

DW = DISHWASHER REF = REFRIGERATOR

DRB = DOOR BASE

SB = SINK BASE

RA = RANGE

SYMBOL TAG DESCRIPTION

FROM FLOOR TO FLOOR, INTERIOR ELEVATIONS GRAPHICALLY

DEPICT ONE FLOOR ONLY, FOR HEIGHT INFORMATION REFER

DIMENSIONS FOR TUBS, SHOWERS, BUILT-IN FIXTURES ETC.

G.C. TO CONFRIM AND COORDINATE ALL CABINETRY AND

3.) PROVIDE APPROPRIATE FIRE TREATED BLOCKING IN WALLS BEHIND ALL FIXTURES, PARTITIONS AND ACCESSORIES.

BLOCKING FOR GRAB BARS TO BE PROVIDED IN WALLS OF

4.) PROVIDE MOISTURE RESISTANT GWB AT ALL WALLS AND

5.) SET ALL CLOTHES WASHERS IN PANS WITH WATER SENSOR

6.) REFER TO ELECTRICAL AND MECHANICAL DRAWINGS FOR

ADDITIONAL INFORMATION REGARDING, LIGHTING, DIFFUSERS,

7.) PROVIDE FIRE EXTINGUISHER ON BRACKET IN BASE CABINET

8.) HANG HOT WATER HEATER FROM DECK ABOVE. (SEE DETAIL

9.) WHERE DROPPED SOFFITS AND CEILINGS ARE SHOWN, THESE ARE IN ADDITION TO THE FIRE RATED GWB CEILING ABOVE

LOCATED IN FIRE RATED WALLS, PROVIDE FIRE RATED BOX IN

0.) WHERE PLUMBING VALVES (TUB, SHOWER, ETC) ARE

