

EACH GRAPH BLOCK = 2'

6" x 6" POST TO BE SET ATOP CONCRETE PILLAR 4' BELOW GRADE USING 12" SONOTUBE WITH A CONCRETE BELL BOTTOM. POST CAPS WILL BE USED TO FASTEN.

2" x 10" SOFST TO BE USED, SET 2' ON CENTER, ANCHORED TO HEADER AND LEDGER BOARDS USING 18 ga GALV HANGERS

LEDGER BOARDS TO BE FASTENED TO BUILDING USING 5" GRK CONCRETE LAGS EVERY 16"

BEAMS WILL BE DOUBLED 2x10 NAILED TOGETHER USING #10 GALVANIZED NAILS

RAILINGS WILL BE 42" HIGH 2" x 4" RAIL CONSTRUCTION AND 1" x 6" DECKING BOARD FOR CAP RAIL. BALUSTER SPACING WILL BE 8 1/2"

4x4 POSTS NOTCHED AND FASTENED WITH 4" LAGS AT EVERY 8'

1 SET OF STAIRS CONSISTING TWO STEPS CONSTRUCTED WITH 2" x 10" STRINGERS 1" x 6" TREADS AND RISERS

STEPS WILL BE 4' WIDE, 12" TREADS WITH 7" RISERS. NOSING WILL BE 3/4" FROM RISER. LANDING IS ASPHALT.

BASIC GATE DOOR TO BE CONSTRUCTED 42" TALL x 48" WIDE WITH PUSHBAR FOR EXIT. STAIR RAILING 42" IN HEIGHT.

ALL DECKING WILL BE 1" x 6" FASTENED WITH 2 1/2" EXTERIOR SCREWS

