

SEE SECTIONS FOR TYPICAL FLOOR BEARING DETAIL @ DOUBLE UNIT WALL.

NOTE: SEE DETAIL 'K' ON S2.1 FOR GENERAL STAIR DETAILS & (5) PLY OSB BEAM / INSIDE STRINGER TO STRINGER ATTACHMENT INFORMATION - TYP. FOR ALL UNITS

NOTE: ELEVATOR OPTION NOT USED - INSTALL 2X10 INFILL FRAMING @ 16\"/>

NOTE: TRUSS DESIGN LOAD @ EACH END = 825 lb. DL, 2,150 lb. LL, TYP. @ ALL UNITS

STEP WALL UP - FULL HEIGHT @ STAIR / ELEVATOR OPENING - TYP.

P.E. HEADER OR (2) 14\"/>

14\"/>

(2) 9-1/4\"/>

(3) 3/8\"/>

NOTE: COORDINATE TRUSSES FOR PSL CANT. BEAMS @ DECK W/ VERT. BLOCKING - TYP.

5-1/4\"/>

2X8 P.T. @ 16\"/>

1US HANGERS @ INSIDE FRAMING & LUC @ RIM TO CANT - TYP.

FULLY BLOCK @ CONNECTIONS & EACH TRUSS - TYP.

NOTE: TRUSS DESIGNER TO ACCOUNT FOR ADDITIONAL 600 lb. UPLIFT FROM CANT. DECK MEMBERS - TYP.

2X8 MIN. RAFTER @ 16\"/>

ALL HEADERS TO BE (2) 2X8 BOX BEAM W/ TOP & BOTTOM PLATE - TYP. UNO.

14\"/>

14\"/>


2X6 @ 16\"/>

2X4 @ 16\"/>

2X4 @ 16\"/>

FULL HEIGHT 1-1/4\"/>

1 SECOND FLOOR FRAMING PLAN
 S1.2 1/8" = 1'-0"



FRAMING PLAN SYMBOLS KEY	
□	WOOD POST
○	STEEL COLUMN
⊙	NUMBER OF WOOD STUDS IN POST BELOW
⊙	COLUMN ABOVE THIS LEVEL
⊙	COLUMN CONTINUOUS THROUGH THIS LEVEL
—	JOIST BEARING
—	CONTINUOUS JOIST WITH INTERMEDIATE BEARING
—	FLUSH FRAMED JOIST BEARING WITH HANGER
—	WOOD STUD BEARING WALL BELOW
—	NUMBER OF TRIM STUDS UNDER HEADER
—	NUMBER OF KING STUDS ADJACENT TO HEADER

- NOTES:
- SEE SHEET S1.0 FOR GENERAL STRUCTURAL NOTES
 - ALL WOOD COLUMNS IN 2x6 WALLS SHALL BE (3) 2x6 AND IN 2x4 WALLS SHALL BE (3) 2x4 UNLESS NOTED OTHERWISE ON PLANS
 - ALL BEAMS ARE FLUSH UNO
 - ALL HEADERS IN 2x BEARING WALLS ARE (2) 2X8 W/ TOP & BOTTOM PLATE - TYP. UNO.
 - ALL FLOOR JOIST TO BE 14\"/>
 - FLOOR SHEATHING TO BE 3/4\"/>
 - ALL TRUSS TO TRUSS CONNECTIONS BY MANUFACTURER - TYP. UNO.
 - TRUSS DESIGNER TO COORDINATE TRUSS LAYOUT WITH FLOOR OPENING, PLUMBING, AND UTILITY REQUIREMENTS - TYP.