

**City of Portland, Maine – Building or Use Permit Application** 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

Location of Construction: 180 Park Ave		Owner: intermed		Phone:		Permit No: 980042	
Owner Address:		Lessee/Buyer's Name:		Phone:		Business Name:	
Contractor Name: Ledgewood Inc		Address: P.O. Box 8107, Ptld 04104		Phone: 767-1866		<div style="border: 2px solid black; padding: 5px;"> <p style="text-align: center; font-weight: bold; font-size: 1.2em;">PERMIT ISSUED</p> <p style="text-align: center;">Permit Issued:</p> <div style="border: 1px solid black; padding: 5px; text-align: center;"> <p style="font-size: 1.5em; font-weight: bold;">JAN 22 1998</p> </div> <p style="text-align: center; font-weight: bold; font-size: 1.2em;">CITY OF PORTLAND</p> </div>	
Past Use: Commercial		Proposed Use: Commercial		<p><b>COST OF WORK:</b> \$ 35,000</p> <p><b>PERMIT FEE:</b> \$ 195.00</p>			
Proposed Project Description:  Interior Renovations		<p><i>DRS OFFICES - MEDICAL</i></p> <p>Signature: <i>[Signature]</i></p>		<p><b>FIRE DEPT.</b> <input checked="" type="checkbox"/> Approved <input type="checkbox"/> Denied</p> <p>INSPECTION: Use Group: <i>B</i> Type: <i>3A</i> <i>BOCA 96</i> Signature: <i>[Signature]</i></p>		<p>Zone: <i>R-10</i> CBL: <i>048-A-00127</i></p> <p>Zoning Approval: <i>53-B-10-34</i> <i>AKUS</i> <i>Belley is on this</i></p> <p><b>Special Zone or Reviews:</b></p> <p><input type="checkbox"/> Shoreland <input type="checkbox"/> Wetland <i>1/20/98</i> <input type="checkbox"/> Flood Zone <i>Existing use</i> <input type="checkbox"/> Subdivision <i>All interior</i> <input type="checkbox"/> Site Plan <i>major</i> <input type="checkbox"/> minor <input type="checkbox"/> mm <input type="checkbox"/></p>	
				<p><b>PEDESTRIAN ACTIVITIES DISTRICT (P.A.D.)</b></p> <p>Action: <input type="checkbox"/> Approved <input type="checkbox"/> Approved with Conditions <input type="checkbox"/> Denied</p> <p>Signature: _____ Date: _____</p>			
Permit Taken By: Sherry Pinard		Date Applied For: January 14, 1998					

1. This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules.
2. Building permits do not include plumbing, septic or electrical work.
3. Building permits are void if work is not started within six (6) months of the date of issuance. False information may invalidate a building permit and stop all work..

call for pick up 767-1866

PERMIT ISSUED WITH REQUIREMENTS

**CERTIFICATION**

I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit

<i>Thomas A. Herbert</i>		<i>1/14/98</i>	<i>767-1866</i>
SIGNATURE OF APPLICANT	ADDRESS:	DATE:	PHONE:
Tom Herbert			PHONE:
RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE			PHONE:

**Zoning Appeal**

Variance  
 Miscellaneous  
 Conditional Use  
 Interpretation  
 Approved  
 Denied

**Historic Preservation**

Not in District or Landmark  
 Does Not Require Review  
 Requires Review

**Action:**

Approved  
 Approved with Conditions  
 Denied

Date: *1/15/98*

*MA*

**CEO DISTRICT** 5

*D. Jordan*


COMMENTS

2-12-98 Hallway Exit light out #2<sup>nd</sup> Exit light out / Requested  
from (Tom Herbert) OK / check for Pb-Permits + Elec.

Inspection Record

Type	Date
Foundation: _____	_____
Framing: _____	_____
Plumbing: _____	_____
Final: _____	_____
Other: _____	_____

# BUILDING PERMIT REPORT

DATE: 12/1/94 ADDRESS: 180 Park Ave  
REASON FOR PERMIT: renovation  
BUILDING OWNER: Intermed  
CONTRACTOR: Hedgewood Inc.  
PERMIT APPLICANT: Thomas Hebert APPROVAL: \*1\*17\*18\*20\*26\*29\*30   
USE GROUP B BOCA 1996 CONSTRUCTION TYPE 3A


## CONDITION(S) OF APPROVAL

- \*1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)
3. Precaution must be taken to protect concrete from freezing.
4. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
5. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage means of 1/2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
6. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993).
7. Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's building code.
8. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".)
9. Headroom in habitable space is a minimum of 7'6".
10. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread, 7" maximum rise.
11. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6' 8")
12. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.
13. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
14. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's.
15. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.
16. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 19. 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
  - In the immediate vicinity of bedrooms
  - In all bedrooms



In each story within a dwelling unit, including basements  
In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

- 7. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an improved type.
- 18. The Fire Alarm System shall be maintained to NFPA #72 Standard.
- 19. The Sprinkler System shall maintained to NFPA #13 Standard.
- 20. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
- 21. No construction or demolition work shall begin until you have obtained permits for dumpsters or containers. A work Stop Order shall be issued if this requirement is not met.
- 22. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 23. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.  
This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's office.
- 25. Ventilation shall meet the requirements of Chapter 12 Sections 1210. of the City's Building Code.
- \* 26. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade.
- 27. All requirements must be met before a final Certificate of Occupancy is issued.
- 28. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National Building Code/1996).
- \* 29. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993).
- \* 30. This permit is being issued with the understanding that  
No structural (bearing beams) are being removed or altered.
- 31. \_\_\_\_\_
- 32. \_\_\_\_\_
- 33. \_\_\_\_\_
- 34. \_\_\_\_\_

  
Samuel Hoffes, Code Enforcement

cc: Lt. McDougall, PFD  
Marge Schmuckal

