Location of Construction:	Owner:	cement LLC	Phone:	Permit No: 980172
Owner Address:	Lessee/Buyer's Name:	Phone:	BusinessName:	PERMIT ISSUED
Contractor Name:	Address: 536 Riverside St	Ptld, HE 04103	Permit Issued:	
Past Use:	Proposed Use:	COST OF WOR		MAR - 4 1998
Ralti Fen	Stane	FIRE DEPT.		ype: CITY OF PORTLAND
		Signature:	Signature:	Zone: CBL: 048-A-016
Proposed Project Description:	ysten Done	PEDESTRIAN A	ACTIVITIES DISTRICT (P. Approved with Conditions: Denied	Zoning Approval:  Special Zone or Reviews: Shoreland Wetland Flood Zone Subdivision
Permit Taken By: Kary Greeik	Date Applied For:	23 Fabruary 19		☐ Site Plan maj ☐minor ☐mm ☐
2. Building permits do not include plumbin	started within six (6) months of the date of			☐ Variance ☐ Miscellaneous ☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied
			WITH REQUIREMENTS	Historic Preservation  Not in District or Landmark  Does Not Require Review  Requires Review  Action:
I hereby certify that I am the owner of record authorized by the owner to make this applica if a permit for work described in the applicat areas covered by such permit at any reasonal	ation as his authorized agent and I agree to ion is issued, I certify that the code official	I work is authorized by the conform to all applicable is authorized representated (s) applicable to such	ne owner of record and that I have laws of this jurisdiction. In a live shall have the authority to permit	ave been
SIGNATURE OF APPLICANT 8111 Las	ADDRESS:	DATE:	998 PHONE:	
RESPONSIBLE PERSON IN CHARGE OF V	WORK TITLE		DHONE.	
RESPONSIBLE PERSON IN CHARGE OF	YURK, IIILE		PHONE:	CEO DISTRICT

## PORTLAND FIRE DEPARTMENT

R	eview Date: 3/2/98 Contractor: Sentey
	Address: 133 6 v-27 50 CBL:
<u>P</u>	lease note marked Conditions of Approval
*-	The boiler or furnace shall be protected by enclosing with one hour fire rated construction including fire doors and ceiling or by providing automatic extinguishment and smoke protected enclosure. Sprinkler piping serving not more than six sprinklers may be connected to a domestic water supply system having a capacity sufficient to provide a 0.15 gpm per sq ft of floor throughout the entire area. An indicating shut-off valve shall be installed in an accessible location between the sprinkler and the connection to the domestic water supply. Minimum pipe size shall be 3/4" copper of 1" steel. Maximum coverage area of a residential sprinkler in 144 sq ft per sprinkler.  All required fire alarm systems shall have the capacity of zone disconnect via switches or key pad program provided the method is approved by the Fire Prevention Bureau.
*	All remote annunciators shall have a visible trouble indicator along with the fire alarm zone indicators.
*	Any master box connected to the system shall have a supervised municipal
*	disconnect switch.  All master box locations hall be munications.  A master box shall be located floor  All master box locations are r
_	A fire alarm acceptance reportance reportance with the
*	Department of Environmer  No cutting of tanks on site  The fire dispatcher must '  tanks.  Lisposal site.  I or transportation of
*	All above ground L/P to 58 standards.  Any tank located near
*	All piping shall be protected non.  A 4" storz fire department connection is required.
*	Any renovation of sprinkler system over 20 heads mus. Fire Marshall approval.
*	A sprinkler performance test shall be submitted to the P.F.D. and completion of work.  State Fire Marshall approval is required for this project.

Lt. Gaylen Mc Dougall
Portland Fire Prevention Bureau