



# Certificate of Design Application

From Designer: MARK D. LEE  
 Date: 06/02/15  
 Job Name: 55 EXETER ST. SBCD PROJECT 2015-011.1  
 Address of Construction: 55 EXETER ST, PORTLAND, ME 04102

## 2009 International Building Code

Construction project was designed to the building code criteria listed below:

Building Code & Year \_\_\_\_\_ Use Group Classification (s) BUSINESS  
 Type of Construction TYPE 5 UNPROTECTED  
 Will the Structure have a Fire suppression system in Accordance with Section 903.3.1 of the 2009 IRC \_\_\_\_\_  
 Is the Structure mixed use? No If yes, separated or non separated or non separated (section 302.3) \_\_\_\_\_  
 Supervisory alarm System? \_\_\_\_\_ Geotechnical/Soils report required? (See Section 1802.2) \_\_\_\_\_

### Structural Design Calculations

\_\_\_\_\_ Submitted for all structural members (106.1 - 106.11)

### Design Loads on Construction Documents (1603)

Uniformly distributed floor live loads (7603.11, 1807)

Floor Area Use	Loads Shown
_____	_____
_____	_____
_____	_____
_____	_____

### Wind loads (1603.1.4, 1609)

\_\_\_\_\_ Design option utilized (1609.1.1, 1609.6)  
 \_\_\_\_\_ Basic wind speed (1809.3)  
 \_\_\_\_\_ Building category and wind importance Factor,  $w$  (table 1604.5, 1609.5)  
 \_\_\_\_\_ Wind exposure category (1609.4)  
 \_\_\_\_\_ Internal pressure coefficient (ASCE 7)  
 \_\_\_\_\_ Component and cladding pressures (1609.1.1, 1609.6.2.2)  
 \_\_\_\_\_ Main force wind pressures (7603.1.1, 1609.6.2.1)

### Earth design data (1603.1.5, 1614-1623)

\_\_\_\_\_ Design option utilized (1614.1)  
 \_\_\_\_\_ Seismic use group ("Category")  
 \_\_\_\_\_ Spectral response coefficients,  $S_D$  &  $S_{D1}$  (1615.1)  
 \_\_\_\_\_ Site class (1615.1.5)

\_\_\_\_\_ Live load reduction  
 \_\_\_\_\_ Roof live loads (1603.1.2, 1607.11)  
 \_\_\_\_\_ Roof snow loads (1603.7.3, 1608)  
 \_\_\_\_\_ Ground snow load,  $P_g$  (1608.2)  
 \_\_\_\_\_ If  $P_g > 10$  psf, flat-roof snow load  $P_f$   
 \_\_\_\_\_ If  $P_g > 10$  psf, snow exposure factor,  $C_e$   
 \_\_\_\_\_ If  $P_g > 10$  psf, snow load importance factor,  $I_s$   
 \_\_\_\_\_ Roof thermal factor,  $C_t$  (1608.4)  
 \_\_\_\_\_ Sloped roof snowload,  $P_R$  (1608.4)  
 \_\_\_\_\_ Seismic design category (1616.3)  
 \_\_\_\_\_ Basic seismic force resisting system (1617.6.2)  
 \_\_\_\_\_ Response modification coefficient,  $R$ , and deflection amplification factor  $C_d$  (1617.6.2)  
 \_\_\_\_\_ Analysis procedure (1616.6, 1617.5)  
 \_\_\_\_\_ Design base shear (1617.4, 16175.5.1)

### Flood loads (1803.1.6, 1612)

\_\_\_\_\_ Flood hazard area (1612.3)  
 \_\_\_\_\_ Elevation of structure

### Other loads

\_\_\_\_\_ Concentrated loads (1607.4)  
 \_\_\_\_\_ Partition loads (1607.5)  
 \_\_\_\_\_ Misc. loads (Table 1607.8, 1607.6.1, 1607.7, 1607.12, 1607.13, 1610, 1611, 2404)