

ABBREVIATIONS LEGEND

ABBREVIATIONS WHEN USED IN COMPOSITION MAY INCLUDE PERIODS FOR CLARIFICATION

Table of abbreviations for various construction materials and components, including AIR, ANCHOR BOLT, ACID RESISTANT, etc.

Table of abbreviations for various construction materials and components, including MOD BIT, MOOFED BITUMEN, MONITOR, etc.

MATERIALS

Table of materials with corresponding hatching patterns, including COMPACTED SOIL, UNDISTURBED SOIL, COURSE POROUS FILL, SAND, BITUMINOUS PAVING, CONCRETE, TERRAZZO, CUT STONE, BRICK MASONRY, etc.

SYMBOLS LEGEND

Table of symbols for architectural elements, including SHEET NUMBER, NORTH ARROW, GRAPHIC SCALE, COLUMN SYMBOL & CENTER LINES, VERTICAL ELEVATION, SPOT ELEVATION, DATUM POINT, MATCH LINE, PROPERTY LINE, FENCING (WITH POSTS), BREAK LINE, DRAWING TITLE, NOTE, SHEET NOTE, KEY NOTE, ROOM NAME AND NUMBER, DOOR NUMBER, WINDOW TYPE SYMBOL, PARTITION TAG, etc.

REFLECTED CEILING LEGEND

Table of symbols for reflected ceiling elements, including ACUSTIC CEILING TILE AND GRID, ACCESS PANEL, DIFFUSER, RETURN, SMOKE AND HEAT DETECTORS, EXIT SIGN, SPRINKLER HEAD, CEILING LIGHT FIXTURES, etc.

GENERAL NOTES

- 1. NOTES APPEAR ON VARIOUS DRAWINGS FOR DIFFERENT SYSTEMS AND MATERIALS. REVIEW ALL SHEETS AND APPLY NOTES TO RELATED BUILDING COMPONENTS.
2. REFER TO COMPLETE SET OF ISSUED CONTRACT DOCUMENTS FOR OTHER APPLICABLE NOTES, ABBREVIATIONS, AND SYMBOLS.
3. WHERE MATERIALS ARE APPLIED TO, OR ARE IN DIRECT CONTACT WITH WORK INSTALLED BY ANOTHER SUBCONTRACTOR, COMMENCEMENT OF WORK IMPLIES ACCEPTANCE OF THE SUBSTRATE AS SUITABLE FOR THE APPLICATION INTENDED.
4. ISOLATE DISSIMILAR METALS TO PREVENT GALVANIC CORROSION.
5. PARTITION TYPES AND FIRE RESISTIVE RATINGS INDICATED ON A WALL ARE TO BE CONTINUOUS FOR THE LENGTH AND HEIGHT OF A PARTITION.
6. OPENINGS IN RATED WALL, FLOOR, CEILING AND ROOF ASSEMBLIES SHALL BE SEALED WITH PENETRATION SEALANT SYSTEMS MEETING OR EXCEEDING THE REQUIRED FIRE RESISTIVE RATINGS.
7. MAINTAIN THE FIRE RATING OF CONSTRUCTION AROUND CABINETS, PANELS, AND BOXES RECESSED IN FIRE RATED WALL, FLOOR, AND CEILING ASSEMBLIES.
8. PROVIDE CONTINUOUS PERIMETER FIRE SAFING BETWEEN FLOORS AND COORDINATE THE INSTALLATION WITH THE EXTERIOR WALL. FIRE RATING OF SAFING SHALL MATCH FIRE RATINGS OF FLOOR CONSTRUCTION.
9. DO NOT SCALE THE DRAWINGS.
10. FIELD MEASURE AND CONFIRM DIMENSIONS FOR OWNER PROVIDED EQUIPMENT AND FURNISHINGS.
11. PROVIDE STIFFENERS, BRACING, BACKING PLATES AND BLOCKING REQUIRED FOR SECURE INSTALLATION OF TOILET PARTITIONS, DOORS AND DOOR HARDWARE, INCLUDING WALL MOUNTED DOOR STOPS, HANDRAILS, WALL MOUNTED SHELVES, OPERABLE PARTITIONS, MISCELLANEOUS EQUIPMENT, AND SUSPENDED MECHANICAL AND ELECTRICAL EQUIPMENT.
12. COORDINATE ALL BASE AND HOUSEKEEPING PADS WITH MECHANICAL, PLUMBING AND ELECTRICAL EQUIPMENT.
13. LOCATE ACCESS PANELS AS INDICATED ON DRAWINGS. FOR ACCESS PANELS NOT SHOWN BUT REQUIRED BY PROVISIONS OF THE CONTRACT DOCUMENTS, LOCATED IN ACCORDANCE WITH APPLICABLE CODES. SUBMIT PROPOSED LOCATIONS TO THE ARCHITECT FOR REVIEW AND ACCEPTANCE PRIOR TO INSTALLATION.

POWER/DATA LEGEND

Table of symbols for power and data elements, including WIRING DEVICES, LOUDSPEAKERS, JUNCTION/PULL BOXES, TELECOMM (VOICE/DATA) DEVICES, FLOOR MTD CONVENIENCE OUTLETS, FLOOR CORE DRILL, CARD READER, etc.

MATERIALS LEGEND

Table of symbols for materials, including GYP. BOARD CEILING, CEILING MATERIAL AND HEIGHT, CEILING LIGHT FIXTURES, etc.

PARTITION & DOOR NOTES

- 1. PARTITIONS LOCATED BY DIMENSION STRINGS ARE DIMENSIONED TO THE UNFINISHED FACE OF THE WALL UNLESS NOTED OTHERWISE.
2. PARTITIONS NOT DIMENSIONED ARE GENERALLY LOCATED BY ONE OF THE FOLLOWING CRITERIA:
- CENTERLINE - CENTER OF PARTITION ALIGNS WITH THE CENTER OF GRIDLINE OR OBJECT CENTERLINE (SUCH AS A COLUMN OR WINDOW MULLION). CENTER THE OVERALL PARTITION WIDTH, RATHER THAN STUD WIDTH ON THE LINE.
- ALIGN - LOCATE PARTITION FLUSH WITH FACE OF GYPSUM BOARD, OR OTHER SURFACE INDICATED.
- MAINTAIN DIMENSIONS NOTED AS "MINIMUM" OR "CLEAR".
1. DOOR OPENINGS ARE DIMENSIONED TO CENTERLINE OF OPENING. IF NOT DIMENSIONED, THE HINGE SIDE OF DOOR JAMBS SHALL BE SPACED 4" FROM THE ADJACENT WALL.

PERKINS + WILL logo and contact information, including address (225 Franklin St., Suite 1100, Boston, MA 02110), phone (617.478.0300), website (www.perkinswill.com), and project details for 'Bean 2 Roof Addition' at 22 Bramhall Street, Portland, Maine 04102.