

ENGINEERING JUDGMENT FOR:	
01/05/15	
Michael Palmacci	
General Insulation	
378 Commercial Street	
Malden, MA 02148	
Fax: (781) 321-5350	

Project: Maine Med Bean 2	Contractor: Roland's Drywall
Fire Stopping Category: Joints / Head of Wall	Hourly Rating Requested/ Type: 1 and 2 Hour / F
Joint Type: Construction	Maximum Joint Width: 2 in.
Floor Assembly: Fluted Steel Deck/Concrete Floor	Wall Assembly: Gypsum Wallboard Assembly
Type of Movement: Dynamic	

Special Conditions: Field condition like UL System HW-D-0384 with deviation of max 8 in. joint between the wall and beam with spray applied fire resistive material (SFRM).

Application Details: To firestop this application, install in accordance with UL System HW-D-0384 with the following modifications/clarifications:

1. Install a minimum 20 ga. steel cover plate to the bottom side of the beam to reduce the joint width to max 6 in. Steel cover plate to overlap onto beam a min. of 3 in. Cover plate to be mechanically fastened to beam using steel fasteners with minimum 75 lb pull out strength in. conjunction with 1-1/4 in. steel washers every 4 in. on center.

3M Fire Barrier Material: FireDam Spray 200

Based On: HW-D-0384

This Engineering Judgment (EJ) is based upon the sole and exclusive use of 3M brand Fire Protection Products as described within. Modification of any of the parameters of this EJ, including, without limitation, the use of non-3M brand Fire Protection Products, shall render this EJ null and void. This fire-resistive joint design is expected to achieve the hourly rating indicated above. This engineering judgment is based on performance results obtained in testing with independent laboratories and / or internal 3M fire tests, which have been tested in accordance to ASTM E 1966 (UL 2079).

Engineering Judgment Prepared By:

Reviewed By:

AEK

563994 cc: Ryan Fenstermaker

Carrie Meis Technical Service Technician