Revisions

PLUMBING FLOOR
PLAN LEVEL 5 DEMOLITION

P01-05

Copyright © 2015 Perkins+Will



CONTRACTORS DUTY TO INSPECT:

DIFFERING CONDITION WARRANTS EQUITABLE ADJUSTMENT, IF ANY.

THE OWNER DISCLAIMS ANY WARRANTY ABOUT THE ACCURACY OR COMPLETENESS OF EXISTING CONDITIONS AFFECTED BY THIS WORK. PORTIONS OF THE AREAS TO BE DEMOLISHED AND ALTERED WHERE NOT ACCESSIBLE DURING FIELD SURVEY DISCOVERY EITHER DUE TO LIMITATIONS IN ACCESS BECAUSE OF CONCEALMENT OF PIPING UTILITIES BEHIND INACCESSIBLE CHASES, WALL, OR CEILINGS. THE CONTRACTOR SHALL EXERCISE REASONABLE DUE DILIGENCE TO DISCOVER ANY REASONABLE FORESEEABLE PHYSICAL CONDITIONS AFFECTED BY THIS WORK. THE DESCRIPTIONS ON THE DRAWING OF UTILITIES IN CONCEALED AREAS REQUIRING DEMOLITION, MODIFICATION, OR OFFSET IS BASED ON SIMILAR CONDITIONS ENCOUNTERED IN THE BUILDING, PIPING VISIBLE IN ADJACENT SPACES AND ON GENERAL ASSUMPTIONS ABOUT THE PLUMBING PIPING SYSTEMS. THE CONTRACTOR SHALL INCLUDE IN HIS PRICE ANY AND ALL COSTS ASSOCIATED WITH THE DEMOLITION AND ALTERATION OF CONCEALED WORK DESCRIBED ON THE PLANS AND REASONABLY INFERRED. ANY ACTUAL CONDITIONS DISCOVERED DURING DEMOLITION THAT DIFFER MATERIALLY FROM THOSE DESCRIBED ON THE PLANS SHALL BE BROUGHT TO THE ATTENTION OF THE OWNER FOR FURTHER COORDINATION AND INVESTIGATION. PROMPT NOTICE OF DIFFERING AND UNFORESEEN CONDITIONS BY THE CONTRACTOR IS OF THE ESSENCE TO ALLOW A REVIEW TO THE CONDITIONS BY THE OWNER BEFORE THEY ARE DISTURBED AND TO DETERMINE WHETHER THE

PLUMBING DEMOLITION KEYNOTES:

1	(E) 3/4"HW UP (ER) 2"W UP	7	(ER) 2"W UP	13	EXISTING 1"HW SUPPLY UP DEMOLITION/RENOVATION.
	(ER) 1/2"CW UP	8	CUT & CAP EXISTING 2"WASTE PIPING ABOVE THE CEILING AS SHOWN FOR RECONNECTION.	<u>(14)</u>	CUT, CAP & MAKE SAFE EX
<u>(2)</u>	CUT, CAP & MAKE SAFE EXISTING 1/2"CW AND 2"W PIPING ABOVE THE CEILING AS SHOWN.	9	(ER) 2"W & T UP (ER) 2"V UP	(T)	SHOWN FOR RECONNECTION
3	(ER) 1/2"CW UP (ER) 2"W UP	⟨10⟩	(ER) 4"VS UP	⟨15⟩⟨16⟩	(ER) 4"S UP (ER) 2"CW UP
4	(ER) 6"ST UP		(ER) 4"SS UP	_	(E) 1"HW UP
	(ER) 4"VS UP (ER) 4"SS UP	(11)	CUT, CAP & MAKE SAFE EXISTING 4"V & 4"S PIPING ABOVE THE CEILING AS SHOWN FOR RECONNECTION.		CUT, CAP & MAKE SAFE EXI CEILING AS SHOWN FOR RE
(5)	CUT, CAP & MAKE SAFE EXISTING 6"ST & 4"WASTE PIPING ABOVE THE CEILING AS SHOWN FOR RECONNECTION.	<u>(12</u>)	(ER) 2"CW UP (E) 2-1/2"CW DN	(18)	(E) 2"WASTE UP
6	EXISTING 3/4"HW SUPPLY UP SHALL BE PROTECTED AND REMAIN ACTIVE DURING DEMOLITION/RENOVATION.		(E) 1"HW UP (E) 1-1/4"HW DN	(19)	CUT, CAP & MAKE SAFE EXI CEILING AS SHOWN FOR RE
	AUTIVE DUNING DEMOLITION/NEMOVATION.				

0110144	13 >	DEMOLITION/RENOVATION.		(E) 3/4"HW UP (ER) 3"W & T UP (ER) 2"V UP (ER) 3/4"CW UP	
SHOWN	14				
	(15)	(ER) 4"S UP	21>	(ER) 1/2"HW UP (ER) 4"S UP (ER) 1-1/2"CW UP	
	16 >	(ER) 2"CW UP (E) 1"HW UP	(22)	CUT, CAP & MAKE SAFE EX	
	17 >	CUT, CAP & MAKE SAFE EXISTING 1/2"CW SUPPLY PIPING ABOVE THE CEILING AS SHOWN FOR RECONNECTION.	23 >	TO THE EXISTING 5TH FLOO	
	(18)	(E) 2"WASTE UP	<u>24</u> >	CUT, CAP & MAKE SAFE EX CEILING AS SHOWN FOR RI	
	(19)	CUT, CAP & MAKE SAFE EXISTING 1-1/2"CW & 4"W PIPING ABOVE THE CEILING AS SHOWN FOR RECONNECTION.	(25)	CUT, CAP & MAKE SAFE EX	

G CEILING AS	20>	(E) 3/4"HW UP (ER) 3"W & T UP (ER) 2"V UP (ER) 3/4"CW UP	26>	(E) 2"V UP (E) 1"HW UP (ER) 4"S UP (E) 2"CW UP
	21>	(ER) 1/2"HW UP (ER) 4"S UP (ER) 1-1/2"CW UP	<u>27</u> >	(E) 1"HW DN (E) 2"W DN & V RISE (E) 2"CW DN (E) 4"S DN
ABOVE THE	22	CUT, CAP & MAKE SAFE EXISTING 2"CW SUPPLY PIPING ABOVE THE CEILING AS SHOWN FOR RECONNECTION.	(28)	(E) 2"CW DN (E) 1"HW DN
	(23)	TO THE EXISTING 5TH FLOOR SYSTEM (TO REMAIN)	29 >	(E) 4"S DN
ADOVE THE	<u>\(24\)</u>	CUT, CAP & MAKE SAFE EXISTING 4"VENT PIPING ABOVE THE CEILING AS SHOWN FOR RE-CONNECTION.	(30)	(E) 1/2"CW UP
ABOVE THE	25>	CUT, CAP & MAKE SAFE EXISTING 1/2"HW SUPPLY PIPING ABOVE THE CEILING AS SHOWN FOR RECONNECTION.		(E) 2"W UP (E) 3/4"HW UP (E) 4"VS UP (E) 4"SS UP