



© 2015 RYAN SENATORE ARCHITECTURE

**PHARMACY RENOVATIONS**  
 MAINE MEDICAL CENTER  
 PORTLAND, MAINE



RYAN SENATORE  
 ARCHITECTURE  
 565 CONGRESS STREET  
 PORTLAND, MAINE  
 207-650-6414  
 senatorearchitecture.com

CONSULTANTS:

REVISIONS:

DATE: JULY 7, 2015

PROJECT No. 1509

DRAWN BY:

CHECKED BY: RJS

SCALE: AS NOTED

SHEET TITLE:  
**DOOR AND  
 FINISH  
 SCHEDULE**

**A7-0**

## DOOR SCHEDULE

**FRAME TYPES**

1 STEEL

**GLAZING SCHEDULE**

KEY	GLAZING TYPE
GL-1	INSULATED CLEAR GLAZING
GL-2	FIRE RATED INSULATED GLAZING
GL-3	CLEAR TEMPERED GLASS
GL-4	CLEAR INSULATED TEMPERED GLASS
GL-5	FIRE RATED GLAZING

1 DOOR TYPES  
1/8" = 1'-0"

2 TYPICAL DOOR JAMB  
(UNLESS OTHERWISE NOTED)  
NOT TO SCALE

DOOR SCHEDULE															
DOOR NO.	TYPE	DOOR			INSULATED	TYPE	FRAME			CLOSER	HANGING (HURLES)	GENERAL	REMARKS		
		WIDTH	HEIGHT	THICKNESS			MATERIAL	DETAILS	HEAD					JAMB	SILL
103.1	A	3'-6"	7'-0"	1-3/4"	WD/GL	CLR	-	1	STL	-	-	-	-	-	POCKET DOOR WITH BUMPER STOPS WITHIN WALL SYSTEM, SOLID CORE
103.2	B	3'-0"	7'-0"	1-3/4"	FG/GL	PTD	-	1	STL	-	-	-	-	-	FIBERGLASS DOOR (NON POUROUS) CLEAN ROOM STYLE
104.1	A	3'-6"	7'-0"	1-3/4"	WD/GL	CLR	-	1	STL	-	-	-	-	-	POCKET DOOR WITH BUMPER STOPS WITHIN WALL SYSTEM, SOLID CORE
105.1	F	3'-6"	7'-0"	1-3/4"	WD/GL	CLR	-	1	STL	-	-	-	-	-	POCKET DOOR WITH BUMPER STOPS WITHIN WALL SYSTEM, SOLID CORE
106.1	C	3'-0"	7'-0"	1-3/4"	WD	CLR	-	1	STL	-	-	-	-	-	SOLID CORE DOOR
107.1	E	4'-0"	7'-0"	1-3/4"	WD	CLR	-	1	STL	-	-	-	-	-	PAIR OF SOLID CORE DOORS
108.1	E	4'-0"	7'-0"	1-3/4"	WD	CLR	-	1	STL	-	-	-	-	-	PAIR OF SOLID CORE DOORS
109.1	E	4'-0"	7'-0"	1-3/4"	WD	CLR	-	1	STL	-	-	-	-	-	PAIR OF SOLID CORE DOORS
111.1	C	3'-0"	7'-0"	1-3/4"	WD	CLR	-	1	STL	-	-	-	-	-	SOLID CORE DOOR

## FINISH SCHEDULE

ROOM FINISH SCHEDULE												
ROOM #	ROOM NAME	WALLS					FLOOR	CEILINGS			REMARKS	PAINT COLOR
		NORTH	EAST	SOUTH	WEST	BASE		MTL.	HEIGHT	RATING		
100	OFFICE	1	1	1	1	10	20	30	-	-	PATCH AND REPAIR CEILING AT NEW WALL LOCATIONS	
101	PHARMACY	1	-	1	1	10	20	30	-	-	PATCH AND REPAIR CEILING AT NEW WALL LOCATIONS	
102	PHARMACY	-	1	1	1	10	20	30	-	-	PATCH AND REPAIR CEILING AT NEW WALL LOCATIONS	
103	COMPOUNDING	1	1	1	1	10	20	30	-	-	PATCH AND REPAIR CEILING AT NEW WALL LOCATIONS	
103A	HAZARDOUS COMPOUNDING	1	1	1	1	10	20	30	-	-	(BASE BID)	
103A	HAZARDOUS COMPOUNDING	2	2	2	2	11	21	31	-	-	CLEAN ROOM ENVIRONMENT (ADD ALTERNATE)	
104	PEDIATRIC PHARMACY	1	1	1	1	10	20	30	-	-	REFINISH EXISTING MECHANICAL COVER	
105	OFFICE	1	1	1	1	10	22	30	-	-	REFINISH EXISTING MECHANICAL COVER	
106	JASON'S OFFICE	1	1	1	1	10	22	30	-	-	REFINISH EXISTING MECHANICAL COVER	
107	STORAGE	1	1	1	1	10	20	30	-	-		
108	STORAGE	1	1	1	1	10	20	30	-	-		
109	STORAGE	1	1	1	1	10	20	30	-	-		
110	HALL	1	1	1	1	10	20	30	-	-	PATCH AND REPAIR CEILING AT NEW WALL LOCATIONS	
111	BREASTFEEDING	1	1	1	1	10	20	30	-	-	PATCH AND REPAIR CEILING AT NEW WALL LOCATIONS	

FINISH SCHEDULE KEY			
<b>WALLS</b>			
1	GWB - PAINTED		
2	FRP NON-POUROUS PANEL WITH SEALED JOINTS APPLIED OVER GWB		
3			
4			
5			
6			
7			
8			
<b>BASE</b>			
10	4" VINYL (OR RUBBER) COVE BASE - SEE STANDARD IMM SPECS		
11	4" BASE ROLLED UP FROM AND INTEGRAL TO FLOORING		
12			
13			
<b>FLOORS</b>			
20	VCT - 12X12 VINYL COMPOSITION TILE		
21	NON POUROUS SHEET FLOORING WITH ROLL UP BASE, WELDED SEAMS		
22	CARPET TILE - SEE MMC STANDARD SPECIFICATIONS		
23			
24			
25			
26			
27			
28			
<b>CEILINGS</b>			
30	2X2 ACOUSTICAL HUNG CEILING TILE AND GRID - MATCH ADJACENT		
31	2X2 CLEANROOM WASHABLE ACOUSTICAL HUNG CEILING TILE AND GRID CAULK IN PLACE		
32			
33			
34			

- ROOM FINISH GENERAL NOTES**
- ALSO SEE INTERIOR ELEVATIONS FOR GRAPHIC DEPICTIONS OF EXTENT OF FINISHES
  - INSTALL MOISTURE RESISTANT (MOLD AND MILDEW RESISTANT) GWB IN ALL AREAS WHERE PLUMBING FIXTURES EXIST (CEILING AND WALLS IN BATHROOMS)
  - CLOSETS SHALL BE FINISHED AS THE ROOMS THEY SERVICE
  - PREPARE ALL SLABS TO MEET NEW FINISHED FLOORING PER FLOORING MANUFACTURERS INSTRUCTIONS. REMOVE ALL GLUES AND ADHESIVES. PROVIDE FLOOR LEVELING MATERIALS AS REQUIRED
  - PROVIDE APPROPRIATE BLOCKING IN WALLS OF ALL BATHROOMS BEHIND FIXTURES, PARTITIONS AND ACCESSORIES. PROVIDE BLOCKING FOR GRAB BARS IN WALLS OF BATHROOMS
  - PROVIDE APPROPRIATE BLOCKING IN WALLS FOR DOOR STOPS
  - PROVIDE APPROPRIATE BLOCKING IN WALLS FOR WALL HUNG CABINETS
  - BOTTOM EDGE OF GWB ON WALL SURFACES TO BE HELD UP 1/2" FROM CONCRETE FLOOR SURFACES
  - PROVIDE VINYL TRANSITIONS STRIPS AT ALL FLOOR TRANSITIONS CENTERED UNDER DOORS UNLESS OTHERWISE NOTED
  - UNLESS OTHERWISE NOTED IN DRAWINGS THE TYPICAL WALL TYPE IS 'NA'. ALL OTHER PARTITION TYPES WILL BE INDICATED.
  - VERIFY UNDERLAYMENT MEETS MANUFACTURERS SPECIFICATION AT RESILIENT FLOORING
  - AT ALL LOCATIONS OF SLAB TRENCHES AND SLABS REMOVED, INSTALL NEW CONCRETE SLABS TO MATCH ADJACENT, THICKNESS, REINFORCING AND FINISH, APPLY SEALER