#### City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Location of Construction: Owner: Phone: 5-903 Cuberest Street 04101 Maine Medical, Center 5454 n Blackwell Owner Address: Lessee/Buyer's Name: Phone: BusinessName: Permit Issued: Contractor Name: Address: Phone: 84 Middle street Portland 04101 COST OF WORK: PERMIT FEE: Past Use: Proposed Use: \$ 31138.00 Dr. 's Offices Hospital INSPECTION: U FIRE DEPT. Approved Use Group: B Type: 1/9 ☐ Denied Zone: CBL: BOC 496 Signature: Zoning Approval: Proposed Project Description: PEDESTRIAN ACTIVITIES DISTRICT (P. Action: Approved Special Zone or Reviews: Pedatrian Valkway Over Congress Street Approved with Conditions: ☐ Shoreland Denied □Wetland ☐ Flood Zone ☐ Subdivision Signature: Date: ☐ Site Plan maj ☐minor ☐mm ☐ Permit Taken By: Date Applied For: Sept. 21 1999 E. Zoning Appeal □ Variance This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. ☐ Miscellaneous Building permits do not include plumbing, septic or electrical work. 2. ☐ Conditional Use Building permits are void if work is not started within six (6) months of the date of issuance. False informa-☐ Interpretation ☐ Approved tion may invalidate a building permit and stop all work... ☐ Denied **Historic Preservation** □ Not in District or Landmark ☐ Does Not Require Review ☐ Requires Review PERMIT ISSUED Action: WITH REQUIREMENTS CERTIFICATION □Appoved ☐ Approved with Conditions I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been □ Denied authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all Date: areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit Sept. 21 1999 SIGNATURE OF APPLICANT ADDRESS: DATE: PHONE: RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE PHONE: CEO DISTRICT

### THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

### Building or Use Permit Pre-Application Attached Single Family Dwellings/Two-Family Dwelling Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE\*\*If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

| Location/Addressof Construction (include Portion of Building)  | 883-90  | 3 CONGRE  | 55 ST.   |
|--|---|---|--|
| Total Square Footage of Proposed Structure   | Square  | Footage of Lot  |  |
| Tax Assessor's Chart, Block & Lot Number  Chart# 1953 Block# Lot#00  | Owner MAINE ME  | D. CTN  | #Telephone# MMBC<br>772 6009   |
| Owner's Address:<br>22 BMAMHALL ST.<br>PONTLAND, ME  | Lessee/Buyer's Name (If   | Applicable)   | SEE ATTACHER   |
| Proposed Project Description:(Please be as specific as possible)  PEDESTRIAN WALKUA  | 4 OVER  | CONGRES   | WOLLY SHEET  |
| Current Use: SHELL SPACE   |   | DOLE ST, used Use PHYSICIA  | PORBLES Rec'd By   |
| •All construction must be conducted in compli •All plumbing must be conducted •All Electrical Installation must comply to •HVAC(Heating, Ventililation and Air Conducted in comply to the conducted in compliance in the conducted | ance with the 1996 E<br>cted in compliance w<br>vith the 1996 National<br>litioning) installation<br>n: | 3.O.C.A. Building Cod<br>vith the State of Maine<br>al Electrical Code as a | le as amended by Section 6-Art II. e Plumbing Code. mended by Section 6-Art III. te 1993 BOCA Mechanical Code. |
| 2) A Copy of Minor or Major site plan review will be required for checklist outlines the minimum standards for a site  | of your Construction  3) A Plot Plan/Sit r the above proposed plan.  4) Building Pl                     | Contract, if available e Plan projects. The attached                        | SEP 2 1 1999   |
| Unless exempted by State Law, construction drawings showing a  Cross Sections w/Framing details (include Floor Plans & Elevations  Window and door schedules   | ll of the following eler  | nents of construction:<br>railings, and accessory                           |  |
| <ul> <li>Foundation plans with required drainage</li> <li>Electrical and plumbing layout. Mechaniequipment, HVAC equipment (air hand)</li> </ul>   | cal drawings for any s  | pecialized equipment so<br>work that may require s                          | uch as furnaces, chimneys, gas   |
| I hereby certify that I am the Owner of record of the named pro-<br>owner to make this application as his/her authorized agent. I ag   |   |   |  |

Signature of applicant: 1 Con Blackwell Date: 9/21/99

Building Permit Fee: \$25.00 for the 1st \$1000.cost plus \$5.00 per \$1,000.00 construction cost thereafter.

Additional Site review and related fees are attached on a separate addendum

application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to

enforce the provisions of the codes applicable to this permit.

## MMBC CONGRESS STR MOB/GARAGE/CONNECTOR Maine Medical Center Portland, ME 9/10/99

### **Building Permit Costs**

| 1 | Original permit construction value                                |            | \$8,194,000 |
|---|---|------------|-------------|
| 2 | (based on estimate of project including Actual Construction Value | connector) | \$8,010,478 |
|   | (not including  | connector) |             |
| 3 | Difference  |            | \$183,522   |
|   |   | (Line 1-2) |             |
| 4 | Connector Construction Cost                                       |            | \$702,000   |
| _ | Additional Value of Connector                                     |            | CE40 470    |
| 5 | Additional Value of Connector                                     | Line 4-3)  | \$518,478   |
|   |   | Line 4-3)  |             |
| 6 | Permit cost<br>\$25+ (\$5 x 518)                                  |            | \$2,615     |

|                 | BUILDING PERMIT REPORT   |
|-----------------|--|
| n               | DATE: 29/54/99 ADDRESS: 883-903 CONGRESS STE CBL: \$53-I-00/   |
| R               | REASON FOR PERMIT: Pedatrian Walkway over Congress ST.   |
| В               | BUILDING OWNER: MAINE MENTICAL CONTEN  |
| р               | PERMIT APPLICANT: 1Contractor Granger NorThorn In  |
|                 | ISE GROUP B/U CONSTRUCTION TYPE / A  |
|                 |  |
|                 | the City's Adopted Building Code (The BOCA National Building Code/1996 with City Amendments) The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)   |
|                 | CONDITION(S) OF APPROVAL   |
| T               | his permit is being issued with the understanding that the following conditions are met: $\frac{1}{2}$ $\frac{1}{2}$ $\frac{1}{2}$ $\frac{1}{2}$ $\frac{1}{2}$ $\frac{1}{2}$ $\frac{1}{2}$ $\frac{1}{2}$ $\frac{1}{2}$ proved with the following conditions:   |
| Α               | pproved with the following conditions:   |
| <del>X</del> 1. | This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.  |
| Q 2.            | Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained   |
|                 | (A 24 hour notice is required prior to inspection)" ALL LOT LINES SHALL BE CLEARLY MARKED  |
|                 | BEFORE CALLING."   |
| 3.              | Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than  |
|                 | 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the  |
|                 | footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the  |
|                 | top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter   |
|                 | membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor  |
|                 | elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2   |
| 4.              |  |
|                 | a maximum 6' o.c. between bolts. (Section 2305.17)   |
| 5.              | and the contract of the contra |
| 6.              |  |
| 7.              | THE PART SECRET OF THE CONTROL OF THE PART |
|                 | that the proper setbacks are maintained.   |
| 8.              | Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private   |
|                 | garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area  |
|                 | by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the  |
|                 | garage side. (Chapter 4, Section 407.0 of the BOCA/1996)   |
| 9.              |  |
|                 | Mechanical Code/1993). Chapter 12 & NFPA 211   |
| 10              |  |
| \/              | Code.  |
| X               | Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use   |
| , ,             | Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, 1-1, I-2, M and R and public garages and open  |
|                 | parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through  |
|                 | any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 3e4" but   |
|                 | not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section  |
|                 | with an outside diameter of at least 1 1/4" and not greater than 2". (Sections 1021 & 1022.0) - Handrails shall be on both sides of  |
|                 | stairway. (Section 1014.7)   |
| 12.             | 110  |
| X13.            | Stair construction in Use Group R-3 & R-4is a minimum of 10" tread and 7 ½" maximum rise. All other Use Group minimum 11"  |
|                 | tread, 7" maximum rise. (Section 1014.0)   |
| 14.             | The minimum headroom in all parts of a stairway shall not be less than 80 inches. (68") 1014.4   |

Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)

# COMMENTS

| 74 146         |  | Date              |   |
|----------------|--|-------------------|---|
| adsa of        |  | Inspection Record |   |
| and There      |  | Type              |   |
| Myor Is a      |  |                   | Framing:  Framing:  Plumbing:  Final:  Other: |
| STATE P        |  |                   |   |
| permit         |  |                   |   |
| My Information |  |                   |   |

- Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)
  All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0)
  The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)
- 19. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 &19. (Smoke detectors shall be installed and maintained at the following locations):
  - In the immediate vicinity of bedrooms
  - In all bedrooms
  - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and l-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2.

- 20. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)
  - The Fire Alarm System shall maintained to NFPA #72 Standard.

The Sprinkler System shall maintained to NFPA #13 Standard.

All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1996)

- 24. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 25. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
- Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).
- All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all electrical (min.72 hours notice) and plumbing inspections have been done.
  - 28. All requirements must be met before a final Certificate of Occupancy is issued.
  - 29. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building Code/1996).
  - 30. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)
  - 31. Please read and implement the attached Land Use Zoning report requirements.
- 32. Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code.
- 33. Glass and glazing shall meet the requirements of Chapter 24 of the building code.
- All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code 1996).
- \*35. All ramps shall be done in accordance with Section 10/6, \$ of

  179e bldg. Code

  \*36. Weephold Shall be done in accordance with Section 2111.8 of The bldg
  - Code (See pasker Section of Plans 1 A-2 Expansion Joint)
    31. All pedestrian walkways Shall Comply with Section 3106.0 of The
- A 38. Thor Swings Shall be done in accordance with Section 1014.8, 2

v. Shauel Hoffses, Building Inspector cc: 1,t. McDougall, PFD

Marge Schmuckal, Zoning Administrator

PSH 7/24.99 / What

<sup>\*\*</sup>On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.