



City of Portland.

OFFICE OF INSPECTOR OF BUILDINGS

...5-3-13.....191

To the Inspector of Buildings of the City of Portland:

The undersigned respectfully makes application for a permit to erect enlarge a building on.....
Waymouth St..... street, at number..... to be.....
Four..... stories high. Sixty-three..... feet long. Thirty-five.....
feet wide; also an addition to be..... stories high,.....
feet long,..... feet wide, and to be used as a Dwelling.....

CELLAR WALL--To be constructed of Stone..... to be 20..... inches wide on bottom and
better to 16..... inches on top.

UNDERPINNING--To be Brick..... Height of underpinning from top of cellar wall to bottom of
wall..... ft..... inches to be 12..... inches in thickness.

EXTERIOR WALLS--To be constructed of Wood..... If of Brick, Stone, etc. Total length of wall
..... ft..... inches. Thickness of 1st..... 2d..... 3d..... 4th.....
5th..... 6th..... story walls. If of reinforced concrete state mix and reinforcing system
to be used.

If wood construction, sills to be 4x8..... Girders..... 8-10.....
Posts 4-6"..... Girts 4-4..... Studs 2-4"..... to be spaced 16 in. on C.

This building will be used for the purposes of Dwelling..... (If for apartments,
tenements, or other family uses state number of families accommodated and number on each floor.
If for manufacturing or mercantile purposes state character of business and amount of estimated
weight to be carried by the floor.)

Number of families on floor..... six.....

Total number of families..... (26) Twenty-six.....

Manufacturing (state character).....

Estimated load on floors per sq. ft.....

Mercantile business (state character and load per sq. ft.).....

If building is used for tenement house or family use and more than one family, the following provisions of the Building Laws regarding dividing partitions shall be adhered to (Quote Law re. this).

ALL DIVIDING PARTITIONS SEPARATING ONE SUITE OF ROOMS FROM ANOTHER SUITE MUST BE METAL LATHED ON BOTH SIDES AND PROVIDED WITH A FIRESTOP EVERY FOUR FEET.

FIRESTOPS--All bearing and center partitions will have firestops cut in tight on top of each partition cap and between each set of floor timbers. Where ledger boards are used there shall be firestops cut in tight against bottom of ledger boards, of same size as wall studs. Also wherever the Inspector of Buildings may consider necessary.

STAIRWAYS--No. in building.. two..... location. Front & Rear..... to be enclosed
with..... walls to be lathed with..... lathing.

ROOF--To be constructed of Wood..... Rafters to be 2-8"..... inches to be spaced 16 in.....
..... inches on centers. Roof to be covered with 3 ply tar and gravel.....

Gutters to be made of..... Cornices to be made of.....

Bay windows to be made of..... to be covered with.....

Dormer Windows to be made of..... to be covered.....

Chimneys, Smoke flues to be lined with Vins Lining and provided with a 10 inch outside collar and an inside collar to go to the inside of the flue.

Estimated Cost of Building \$12000

INSPECTION--The Inspector of Buildings is to be notified when building is ready for lathing and at least 24 hours before the lathing is begun.

The Builder is G. E. Patterson & Co..... Address..... 451 St John St.

The Architect is..... Address.....

The Owner is J. E. Barron..... Address..... 1009 Congress St.

No Deviation will be made from the above application without written permission from the Inspector of Buildings.

The above petition was granted the..... day of..... 191

All floor timbers to be 2-8 in. and to be spaced 16 in. on centers.

(Applicant to sign here G. E. Patterson)