

SECTION 04810

UNIT MASONRY ASSEMBLIES

PART 1 - GENERAL

1.01 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.

1.02 SUMMARY

- A. This Section includes unit masonry assemblies consisting of the following:
 - 1. Concrete masonry units (CMUs).
 - 2. Concrete brick.
 - 3. Face brick.
 - 4. Mortar and grout.
 - 5. Reinforcing steel.
 - 6. Masonry joint reinforcement.
 - 7. Ties and anchors.
 - 8. Embedded flashing.
 - 9. Miscellaneous masonry accessories.
 - 10. Repair of existing masonry walls.
 - 11. Masonry waste disposal.
- B. Related Sections include the following:
 - 1. Division 7 Section "Flashing and Sheet Metal" for exposed sheet metal flashing.
 - 2. Division 7 Section "Through-Penetration Firestop Systems" for firestopping at openings in masonry walls.
 - 3. Division 7 Section "Fire-Resistive Joint Systems" for fire-resistive joint systems at heads of masonry walls.
 - 4. Division 7 Section "Joint Sealants" for sealing control and expansion joints in unit masonry.
 - 5. Division 7 Section "Fluid-Applied Air/Vapor Barrier System" for air/vapor barrier system.
- C. Products installed, but not furnished, under this Section include the following:
 - 1. Steel lintels for unit masonry, furnished under Division 5 Section "Metal Fabrications."
 - 2. Steel frames for doors set in unit masonry openings, furnished under Division 8 Section "Steel Doors and Frames."
 - 3. Installation of access doors set in masonry openings furnished under Division 8 Section "Access Doors."

1.03 DEFINITIONS

- A. Reinforced Masonry: Masonry containing reinforcing steel in grouted cells.

1.04 SUBMITTALS

- A. General: Submit in accordance with Section 01300.
- B. Product Data: For each type of product indicated.
- C. Shop Drawings: For the following:
 - 1. Masonry Units: Show sizes, profiles, and coursing.
 - 2. Reinforcing Steel: Detail bending and placement of unit masonry reinforcing bars. Comply with ACI 315, "Details and Detailing of Concrete Reinforcement." Show elevations of reinforced walls.

3. Fabricated Flashing: Detail corner units, end-dam units, and other special applications.
- D. Samples for Verification: For each type and color of the following:
 1. Face brick, in the form of straps of five or more bricks.
 2. Pigmented mortar to match existing mortar. Make Samples using same sand and mortar ingredients to be used on Project. Label Samples to indicate types and amounts of pigments used.
- E. Qualification Data: For firms and persons specified in "Quality Assurance" Article.
- F. Cold-Weather Procedures: Detailed description of methods, materials, and equipment to be used to comply with cold-weather requirements.

1.05 QUALITY ASSURANCE

- A. Installer Qualifications: Company specializing in performing the work of this Section with minimum 5 years experience.
- B. Source Limitations for Masonry Units: Obtain exposed masonry units of a uniform texture and color, or a uniform blend within the ranges accepted for these characteristics, through one source from a single manufacturer for each product required.
- C. Source Limitations for Mortar Materials: Obtain mortar ingredients of a uniform quality, including color for exposed masonry, from a single manufacturer for each cementitious component and from one source or producer for each aggregate.
- D. Fire-Resistance Ratings: Where indicated, provide materials and construction identical to those of assemblies with fire-resistance ratings determined per ASTM E 119 by a testing and inspecting agency, by equivalent concrete masonry thickness, or by other means, as acceptable to authorities having jurisdiction.
- E. Mockups: Build mockups to verify selections made under sample submittals and to demonstrate aesthetic effects and set quality standards for materials and execution.
 1. Prepare mockup of masonry repairs to demonstrate color match of masonry units and mortar with existing masonry; relationship of mortar and sealant colors to masonry unit colors; tooling of joints; and aesthetic qualities of workmanship.
 - a. Locate mockup on building in location directed by Architect.
 2. Prepare mockups for review at Preinstallation Conference.
 3. Clean one-half of exposed faces of mockups with masonry cleaner as indicated.
- F. Preinstallation Conference: Conduct conference at Project site to comply with requirements in Division 1 Section "Project Meetings."

1.06 DELIVERY, STORAGE, AND HANDLING

- A. Store masonry units on elevated platforms in a dry location. If units are not stored in an enclosed location, cover tops and sides of stacks with waterproof sheeting, securely tied. If units become wet, do not install until they are dry.
 1. Protect Type I concrete masonry units from moisture absorption so that, at time of installation, moisture content is not more than maximum allowed at time of delivery.
- B. Store cementitious materials on elevated platforms, under cover, and in a dry location. Do not use cementitious materials that have become damp.
- C. Store aggregates where grading and other required characteristics can be maintained and contamination avoided.
- D. Store masonry accessories, including metal items, to prevent corrosion and accumulation of dirt and oil.

1.07 PROJECT CONDITIONS

- A. Protection of Masonry: During construction, cover tops of walls, projections, and sills with waterproof sheeting at end of each day's work. Cover partially completed masonry when construction is not in progress.
1. Extend cover a minimum of **24 inches (600 mm)** down both sides and hold cover securely in place.
- B. Do not apply uniform floor or roof loads for at least 12 hours and concentrated loads for at least 3 days after building masonry walls or columns.
- C. Stain Prevention: Prevent grout, mortar, and soil from staining the face of masonry to be left exposed or painted. Immediately remove grout, mortar, and soil that come in contact with such masonry.
1. Protect base of walls from rain-splashed mud and from mortar splatter by spreading coverings on ground and over wall surface.
 2. Protect sills, ledges, and projections from mortar droppings.
 3. Protect surfaces of window and door frames, as well as similar products with painted and integral finishes, from mortar droppings.
 4. Turn scaffold boards near the wall on edge at the end of each day to prevent rain from splashing mortar and dirt onto completed masonry.
- D. Cold-Weather Requirements: Do not use frozen materials or materials mixed or coated with ice or frost. Do not build on frozen substrates. Remove and replace unit masonry damaged by frost or by freezing conditions. Comply with cold-weather construction requirements contained in ACI 530.1/ASCE 6/TMS 602 and the following:
1. Cold-Weather Construction: When the ambient temperature is within the limits indicated, use the following procedures:
 - a. **40 to 32 deg F (4 to 0 deg C)**: Heat mixing water or sand to produce mortar temperatures between **40 and 120 deg F (4 and 49 deg C)**.
 - b. **32 to 25 deg F (0 to -4 deg C)**: Heat mixing water and sand to produce mortar temperatures between **40 and 120 deg F (4 and 49 deg C)**. Heat grout materials to produce grout temperatures between **40 and 120 deg F (4 and 49 deg C)**. Maintain mortar and grout above freezing until used in masonry.
 - c. **25 to 20 deg F (-4 to -7 deg C)**: Heat mixing water and sand to produce mortar temperatures between **40 and 120 deg F (4 and 49 deg C)**. Heat grout materials to produce grout temperatures between **40 and 120 deg F (4 and 49 deg C)**. Maintain mortar and grout above freezing until used in masonry. Heat masonry units to **40 deg F (4 deg C)** if grouting. Use heat on both sides of walls under construction.
 - d. **20 deg F (-7 deg C) and Below**: Heat mixing water and sand to produce mortar temperatures between **40 and 120 deg F (4 and 49 deg C)**. Heat grout materials to produce grout temperatures between **40 and 120 deg F (4 and 49 deg C)**. Maintain mortar and grout above freezing until used in masonry. Heat masonry units to **40 deg F (4 deg C)**. Provide enclosures and use heat on both sides of walls under construction to maintain temperatures above **32 deg F (0 deg C)** within the enclosures.
 2. Cold-Weather Protection: When the mean daily temperature is within the limits indicated, provide the following protection, this is in addition to construction procedures specified above:
 - a. **40 to 25 deg F (4 to -4 deg C)**: Cover masonry insulating blankets for 48 hours after construction.
 - b. **25 deg F (-4 deg C) and Below**: Provide enclosure and heat to maintain temperatures above **32 deg F (0 deg C)** within the enclosure for 72 hours after construction.
 3. Cold-Weather Cleaning: Use liquid cleaning methods only when air temperature is **40 deg F (4 deg C)** and above and will remain so until masonry has dried, but not less than 7 days after completing cleaning.
- E. Hot-Weather Requirements: Protect unit masonry work when temperature and humidity conditions produce excessive evaporation of water from mortar and grout. Provide artificial shade and wind breaks and use cooled materials as required.
1. When ambient temperature exceeds **100 deg F (38 deg C)**, or **90 deg F (32 deg C)** with a wind velocity greater than **8 mph (13 km/h)**, do not spread mortar beds more than **48 inches (1200 mm)** ahead of masonry. Set masonry units within one minute of spreading mortar.

PART 2 - PRODUCTS

2.01 MANUFACTURERS

- A. In other Part 2 articles where titles below introduce lists, the following requirements apply to product selection:
1. Products: Subject to compliance with requirements, provide one of the products specified.
 2. Manufacturers: Subject to compliance with requirements, provide products by one of the manufacturers specified.

2.02 MASONRY UNITS, GENERAL

- A. Defective Units: Referenced masonry unit standards may allow a certain percentage of units to exceed tolerances and to contain chips, cracks, or other defects exceeding limits stated in the standard. Do not use units where such defects, including dimensions that vary from specified dimensions by more than stated tolerances, will be exposed in the completed Work or will impair the quality of completed masonry.

2.03 CONCRETE MASONRY UNITS (CMUs)

- A. Shapes: Provide shapes indicated and as follows:
1. Provide special shapes for lintels, corners, jambs, sashes, movement joints, headers, bonding, and other special conditions.
 2. Provide bullnose units for outside corners, unless otherwise indicated.
- B. Concrete Masonry Units: ASTM C 90.
1. Unit Compressive Strength: Provide units with minimum average net-area compressive strength of **2800 psi**.
 2. Weight Classification: Normal weight, unless otherwise indicated.
 3. Provide Type I, moisture-controlled units.
 4. Size (Width): Manufactured to dimensions 3/8 inch less than nominal dimensions.
 5. Exposed Faces: Provide color and texture matching the range represented by Architect's sample.
 6. Provide fire-rated block with ratings at locations indicated.
- C. Concrete Building Brick: ASTM C 55.
1. Unit Compressive Strength: Provide units with minimum average net-area compressive strength of **2800 psi**.
 2. Weight Classification: Normal weight.
 3. Provide Type I, moisture-controlled units.
 4. Size: Manufactured to dimensions 3/8 inch less than nominal dimensions.

2.04 MASONRY LINTELS

- A. General: Provide masonry lintels, complying with requirements below.
- B. Masonry Lintels: Prefabricated or built-in-place masonry lintels made from bond beam concrete masonry units with reinforcing bars placed as indicated and filled with coarse grout. Temporarily support built-in-place lintels until cured.

2.05 BRICK

- A. General: Provide shapes indicated and as follows for each form of brick required:
1. For ends of sills and caps and for similar applications that would otherwise expose unfinished brick surfaces, provide units without cores or frogs and with exposed surfaces finished.
 2. Provide special shapes for applications where stretcher units cannot accommodate special conditions, including those at corners, movement joints, bond beams, sashes, and lintels.
 3. Provide special shapes for applications requiring brick of size, form, color, and texture on exposed surfaces that cannot be produced by sawing.

4. Provide special shapes for applications where shapes produced by sawing would result in sawed surfaces being exposed to view.
- B. Face Brick: ASTM C 216, Grade SW, Type FBS.
1. Unit Compressive Strength: Provide units with minimum average net-area compressive strength of not less than **8000 psi (55.2 MPa)**.
 2. Initial Rate of Absorption: Less than **18 g/30 sq. in. (20 g/194 sq. cm)** per minute when tested per ASTM C 67.
 3. Efflorescence: Provide brick that has been tested according to ASTM C 67 and is rated "not effloresced."
 4. Size: Match existing.
 5. Application: Use where brick is exposed, unless otherwise indicated.
 6. Where shown to "match existing," provide face brick matching color range, texture, and size of existing adjacent brickwork.
 7. Product: Morin Light Flashed Waterstruck; Morin LaChance Brick Company.

2.06 MORTAR AND GROUT MATERIALS

- A. Portland Cement: ASTM C 150, Type I or II, except Type III may be used for cold-weather construction. Provide natural color or white cement as required to produce mortar color indicated.
- B. Hydrated Lime: ASTM C 207, Type S.
- C. Portland Cement-Lime Mix: Packaged blend of portland cement complying with ASTM C 150, Type I or Type III, and hydrated lime complying with ASTM C 207, Type S. Standard masonry cement is not acceptable. Provide one of the following portland cement-lime mix products:
1. Eaglebond; Lafarge North America Inc.
 2. Portland and lime; Cement Quebec, Inc.
- D. Mortar Pigments: Natural and synthetic iron oxides and chromium oxides, compounded for use in mortar mixes. Use only pigments with a record of satisfactory performance in masonry mortar.
1. Product: Solomon Grind-Chem Services, Inc.; SGS Mortar Colors.
 - a. Provide mortar pigments to match existing color.
- E. Aggregate for Mortar: ASTM C 144.
1. For mortar that is exposed to view, use washed aggregate consisting of natural sand or crushed stone.
- F. Aggregate for Grout: ASTM C 404.
- G. Water: Potable.

2.07 REINFORCEMENT

- A. Uncoated Steel Reinforcing Bars: ASTM A 615/A 615M or ASTM A 996/A 996M, **Grade 60 (Grade 420)**.

2.08 MASONRY JOINT REINFORCEMENT

- A. Masonry Joint Reinforcement, General: ASTM A 951.
1. Interior Walls: Hot-dip galvanized, carbon steel.
 2. Exterior Walls: Hot-dip galvanized, carbon steel.
 3. Spacing of Cross Rods, Tabs, and Cross Ties: Not more than **16 inches (407 mm)** o.c.
 4. Provide in lengths of not less than **10 feet (3 m)**, with prefabricated corner and tee units.
- B. Masonry Joint Reinforcement for Single-Wythe Masonry: Ladder type with single pair of side rods.
1. Products:
 - a. Block Walls: Continuous ladder type, ASTM A 153, Class B-2, hot dipped galvanized, with 3/16" side rods and No. 9 wire cross rods.

- 1) Dayton Superior Corporation, Dur-O-Wal Division; D/A 320 Ladur.
- 2) Heckman Building Products, Inc.; No. 1100 Ladder.
- 3) Hohmann & Barnard, Inc.; Lox-All Ladder-Mesh.
- 4) Wire Bond; Ladder Series 200.

2.09 TIES AND ANCHORS

- A. Materials: Provide ties and anchors specified in subsequent paragraphs that are made from materials that comply with eight subparagraphs below, unless otherwise indicated.
1. Hot-Dip Galvanized, Carbon-Steel Wire: ASTM A 82; with ASTM A 153/A 153M, Class B-2 coating.
 2. Galvanized Steel Sheet: ASTM A 653/A 653M, Commercial Steel, G60 (Z180) zinc coating.
 3. Steel Sheet, Galvanized after Fabrication: ASTM A 1008/A 1008M, Commercial Steel, hot-dip galvanized after fabrication to comply with ASTM A 153/A 153M.
- B. Corrugated Metal Ties for Brick: Metal strips not less than 7/8 inch (22 mm) wide with corrugations having a wavelength of 0.3 to 0.5 inch (7.6 to 12.7 mm) and an amplitude of 0.06 to 0.10 inch (1.5 to 2.5 mm) made from steel sheet, galvanized after fabrication not less than 0.067 inch (1.7 mm), 14 gage thick.
1. Products:
 - a. Heckman Building Products, Inc.; No. 187.
 - b. Hohmann & Barnard, Inc.; Corrugated Brick Anchor #345.
 - c. Wire Bond; Veneer Anchor No. 2501.

2.10 MISCELLANEOUS ANCHORS

- A. Unit Type Inserts in Concrete: Cast-iron or malleable-iron wedge-type inserts.
- B. Anchor Bolts: Steel bolts, L-shaped, complying with ASTM A 307, Grade A (ASTM F 568M, Property Class 4.6); with ASTM A 563 (ASTM A 563M) hex nuts and, where indicated, flat washers; hot-dip galvanized to comply with ASTM A 153/A 153M, Class C; of dimensions indicated.
- C. Postinstalled Anchors: Provide chemical or torque-controlled expansion anchors, with capability to sustain, without failure, a load equal to six times the load imposed when installed in solid or grouted unit masonry and equal to four times the load imposed when installed in concrete, as determined by testing per ASTM E 488 conducted by a qualified independent testing agency.
1. Corrosion Protection: Carbon-steel components zinc plated to comply with ASTM B 633, Class Fe/Zn 5 (5 microns) for Class SC 1 service condition (mild).
 2. Corrosion Protection: Stainless-steel components complying with ASTM F 593 and ASTM F 594, Alloy Group 1 or 2 (ASTM F 738M and ASTM F 836M, Alloy Group 1 or 4) for bolts and nuts; ASTM A 666 or ASTM A 276, Type 304 or 316, for anchors.

2.11 MISCELLANEOUS MASONRY ACCESSORIES

- A. Compressible Filler: Premolded filler strips complying with ASTM D 1056, Grade 2A1; compressible up to 35 percent; of width and thickness indicated; formulated from neoprene, urethane, or PVC.
- B. Reinforcing Bar Positioners: Wire units designed to fit into mortar bed joints spanning masonry unit cells with loops for holding reinforcing bars in center of cells. Units are formed from 0.142-inch (3.6-mm) steel wire, hot-dip galvanized after fabrication. Provide units with either two loops or four loops as needed for number of bars indicated.
1. Products:
 - a. Dayton Superior Corporation, Dur-O-Wal Division; D/A 810, D/A 812 or D/A 817.
 - b. Heckmann Building Products Inc.; No. 376 Rebar Positioner.
 - c. Hohmann & Barnard, Inc.; #RB or #RB-Twin Rebar Positioner.
 - d. Wire-Bond; O-Ring or Double O-Ring Rebar Positioner.

2.12 MASONRY CLEANERS

- A. Job-Mixed Detergent Solution: Solution of 1/2-cup (0.14-L) dry measure tetrasodium polyphosphate (Spic and Span) and 1/2-cup (0.14-L) dry measure laundry detergent dissolved in 1 gal. (4 L) of water.

- B. Proprietary Acidic Cleaner: Manufacturer's standard-strength cleaner designed for removing mortar/grout stains, efflorescence, and other new construction stains from new masonry without discoloring or damaging masonry surfaces. Use product expressly approved for intended use by cleaner manufacturer and manufacturer of masonry units being cleaned. Muriatic acid is not permitted.
 - 1. Cleaners for Brick:
 - a. Diedrich Technologies, Inc.; 202V Vana-Stop.
 - b. ProSoCo, Inc.; Sure Klean Vana Trol.

2.13 MORTAR AND GROUT MIXES

- A. General: Do not use admixtures, including pigments, air-entraining agents, accelerators, retarders, water-repellent agents, antifreeze compounds, or other admixtures, unless otherwise indicated.
 - 1. Do not use calcium chloride in mortar or grout.
 - 2. Limit cementitious materials in mortar for exterior and reinforced masonry to portland cement and lime.
- B. Mortar for Unit Masonry: Comply with BIA Technical Notes 8A, Proportion Specification. Provide the following types of mortar for applications stated unless another type is indicated or needed to provide required compressive strength of masonry.
 - 1. For masonry below grade or in contact with earth, use Type M.
 - 2. For reinforced masonry, brick veneer use Type S.
- C. Pigmented Mortar: Use colored cement product.
 - 1. Pigments shall not exceed 10 percent of portland cement by weight.
- D. Grout for Unit Masonry: Comply with ASTM C 476.
 - 1. Use grout of type indicated or, if not otherwise indicated, of type (fine or coarse) that will comply with Table 1.15.1 in ACI 530.1/ASCE 6/TMS 602 for dimensions of grout spaces and pour height.
 - 2. Provide grout with a slump of 8 to 11 inches (200 to 280 mm) as measured according to ASTM C 143/C 143M.
- E. Concrete for Unit Masonry: 3000 psi, 28-day compressive strength. Comply with requirements of Division 3 Section "Cast-In-Place Concrete."

PART 3 - EXECUTION

3.01 EXAMINATION

- A. Examine conditions, with Installer present, for compliance with requirements for installation tolerances and other conditions affecting performance of work.
 - 1. If unsatisfactory conditions are encountered, prepare written report, endorsed by Installer, listing conditions detrimental to performance of work.
 - 2. Verify that reinforcing dowels are properly placed.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.

3.02 INSTALLATION, GENERAL

- A. Thickness: Build cavity and composite walls and other masonry construction to full thickness shown. Build single-wythe walls to actual widths of masonry units, using units of widths indicated.
- B. Build chases and recesses to accommodate items specified in this and other Sections.
- C. Leave openings for equipment to be installed before completing masonry. After installing equipment, complete masonry to match the construction immediately adjacent to opening.
- D. Use full-size units without cutting if possible. If cutting is required to provide a continuous pattern or to fit adjoining construction, cut units with motor-driven saws; provide clean, sharp, unchipped edges.

Allow units to dry before laying, unless wetting of units is specified. Install cut units with cut surfaces and, where possible, cut edges concealed.

- E. Select and arrange units for exposed unit masonry to produce a uniform blend of colors and textures.
 - 1. Mix units from several pallets or cubes as they are placed.
- F. Matching Existing Masonry: Match coursing, bonding, color, and texture of existing masonry when infilling areas within existing masonry.
- G. Comply with construction tolerances in ACI 530.1/ASCE 6/TMS 602 and with the following:
 - 1. For conspicuous vertical lines, such as external corners, door jambs, reveals, and expansion and control joints, do not vary from plumb by more than **1/8 inch in 10 feet (3 mm in 3 m)**, **1/4 inch in 20 feet (6 mm in 6 m)**, or **1/2 inch (12 mm)** maximum.
 - 2. For vertical alignment of exposed head joints, do not vary from plumb by more than **1/4 inch in 10 feet (6 mm in 3 m)**, or **1/2 inch (12 mm)** maximum.
 - 3. For conspicuous horizontal lines, such as lintels, sills, parapets, and reveals, do not vary from level by more than **1/8 inch in 10 feet (3 mm in 3 m)**, **1/4 inch in 20 feet (6 mm in 6 m)**, or **1/2 inch (12 mm)** maximum.
 - 4. For exposed bed joints, do not vary from thickness indicated by more than plus or minus **1/8 inch (3 mm)**, with a maximum thickness limited to **1/2 inch (12 mm)**. Do not vary from bed-joint thickness of adjacent courses by more than **1/8 inch (3 mm)**.
 - 5. For exposed head joints, do not vary from thickness indicated by more than plus or minus **1/8 inch (3 mm)**. Do not vary from adjacent bed-joint and head-joint thicknesses by more than **1/8 inch (3 mm)**.
 - 6. For faces of adjacent exposed masonry units, do not vary from flush alignment by more than **1/16 inch (1.5 mm)** except due to warpage of masonry units within tolerances specified for warpage of units.

3.03 LAYING MASONRY WALLS

- A. Lay out walls in advance for accurate spacing of surface bond patterns with uniform joint thicknesses and for accurate location of openings, movement-type joints, returns, and offsets. Avoid using less-than-half-size units, particularly at corners, jambs, and, where possible, at other locations.
- B. Bond Pattern for Exposed Masonry: Unless otherwise indicated, lay exposed masonry in running bond for new construction; do not use units with less than nominal **4-inch (100-mm)** horizontal face dimensions at corners or jambs.
 - 1. Where openings are indicated to be infilled in existing construction, match existing bond pattern.
- C. Lay concealed masonry with all units in a wythe in running bond or bonded by lapping not less than **2 inches (50 mm)**. Bond and interlock each course of each wythe at corners. Do not use units with less than nominal **4-inch (100-mm)** horizontal face dimensions at corners or jambs.
- D. Stopping and Resuming Work: Stop work by racking back units in each course from those in course below; do not tooth. When resuming work, clean masonry surfaces that are to receive mortar, remove loose masonry units and mortar, and wet brick if required before laying fresh masonry.
- E. Built-in Work: As construction progresses, build in items specified in this and other Sections. Fill in solidly with masonry around built-in items.
- F. Fill space between steel frames, bent plate frames, and masonry solidly with mortar, unless otherwise indicated. Grout cores solid minimum of 16-inches each side of openings.
- G. Where built-in items are to be embedded in cores of hollow masonry units, place a layer of metal lath, wire mesh, or plastic mesh in the joint below and rod mortar or grout into core.
- H. Fill cores in hollow concrete masonry units with grout **24 inches (600 mm)** under bearing plates, beams, lintels, posts, and similar items, unless otherwise indicated.

- I. Build non-load-bearing interior partitions full height of story to underside of solid floor or roof structure above, unless otherwise indicated.
 - 1. Install compressible filler in joint between top of partition and underside of structure above.
- J. At fire-rated walls and partitions, coordinate size of joint between top of masonry and underside of structure and between masonry and adjacent construction to comply with Division 7 Section "Fire-Resistive Joint Systems."
- K. Dampproof concrete masonry walls that will be strapped to receive metal siding.

3.04 MORTAR BEDDING AND JOINTING

- A. Lay hollow concrete masonry units as follows:
 - 1. With face shells fully bedded in mortar and with head joints of depth equal to bed joints.
 - 2. With webs fully bedded in mortar in all courses of piers, columns, and pilasters.
 - 3. With webs fully bedded in mortar in grouted masonry, including starting course on footings.
 - 4. With entire units, including areas under cells, fully bedded in mortar at starting course on footings where cells are not grouted.
- B. Tool exposed joints slightly concave when thumbprint hard, using a jointer larger than joint thickness, unless otherwise indicated.

3.05 COMPOSITE MASONRY

- A. Bond wythe of masonry together using one of the following methods:
 - 1. Individual Metal Ties: Provide ties as shown installed in horizontal joints, but not less than one metal tie for 1.77 sq. ft. (0.16 sq. m) of wall area spaced not to exceed 16 inches (406 mm) o.c. horizontally and 16 inches (406 mm) o.c. vertically. Stagger ties in alternate courses. Provide additional ties within 12 inches (305 mm) of openings and space not more than 36 inches (915 mm) apart around perimeter of openings. At intersecting and abutting walls, provide ties at no more than 24 inches (610 mm) o.c. vertically.
- B. Collar Joints: Solidly fill collar joints by parging face of first wythe that is laid and shoving units of other wythe into place.

3.06 MASONRY JOINT REINFORCEMENT

- A. General: Install entire length of longitudinal side rods in mortar with a minimum cover of 5/8 inch (16 mm) on exterior side of walls, 1/2 inch (13 mm) elsewhere. Lap reinforcement a minimum of 6 inches (150 mm).
 - 1. Space reinforcement not more than 16 inches (406 mm) o.c.
 - 2. Provide reinforcement not more than 8 inches (203 mm) above and below wall openings and extending 12 inches (305 mm) beyond openings.
 - a. Reinforcement above is in addition to continuous reinforcement.
- B. Interrupt joint reinforcement at control and expansion joints, unless otherwise indicated.
- C. Provide continuity at wall intersections by using prefabricated T-shaped units.
- D. Provide continuity at corners by using prefabricated L-shaped units.

3.07 ANCHORING MASONRY VENEERS

- A. Anchor masonry veneers to concrete backup with masonry-veneer anchors to comply with the following requirements:
 - 1. Fasten screw-attached anchors to concrete backup with metal fasteners of type indicated. Use two fasteners unless anchor design only uses one fastener.

2. Space anchors as indicated, but not more than **16 inches (406 mm)** o.c. vertically and **16 inches (406 mm)** o.c. horizontally, with not less than 1 anchor for each **1.77 sq. ft. (0.164 sq. m)** of wall area. Install additional anchors within **12 inches (305 mm)** of openings and at intervals, not exceeding **8 inches (203 mm)**, around perimeter.

3.08 CONTROL AND EXPANSION JOINTS

- A. General: Install control and expansion joint materials in unit masonry as masonry progresses. Do not allow materials to span control and expansion joints without provision to allow for in-plane wall or partition movement.
 1. Where control joints are not shown, provide control joints in new construction at a maximum spacing of 30 feet; review proposed locations with Architect prior to installation.

3.09 LINTELS

- A. Install steel lintels where indicated.
- B. Provide masonry lintels where shown and where openings of more than **12 inches (305 mm)** for brick-size units and **24 inches (610 mm)** for block-size units are shown without structural steel or other supporting lintels.
- C. Provide minimum bearing of **8 inches (200 mm)** at each jamb, unless otherwise indicated.

3.10 REINFORCED UNIT MASONRY INSTALLATION

- A. Bracing of Walls During Construction: Provide temporary lateral bracing of masonry walls to prevent collapse in accordance with NCMA-TEC 72 and applicable OSHA standards. Contractor is solely responsible for the design and adequacy of bracing methods used.
- B. Placing Reinforcement: Comply with requirements in ACI 530.1/ASCE 6/TMS 602 and requirements indicated on Structural Drawings.
- C. Grouting: Do not place grout until entire height of masonry to be grouted has attained enough strength to resist grout pressure.
 1. Comply with requirements in ACI 530.1/ASCE 6/TMS 602 for cleanouts and for grout placement, including minimum grout space and maximum pour height.
 2. Definitions:
 - a. Grout Lift: Grout placed in one continuous operation. The maximum time span for grout placement in one lift is 1-1/2 hours measured from time water is added to grout mix. The minimum time span between successive grout lifts is one hour.
 - b. Grout Pour: Height of masonry to be grouted prior to erection of additional masonry.
 3. Do Not Exceed the Following Pour Heights for Fine Grout:
 - a. For minimum widths of grout spaces of 3/4 inch or for minimum grout space of hollow unit cells of 1 1/2 by 2 inches, pour height of 12 inches.
 - b. For minimum widths of grout spaces of 2 inches or for minimum grout space of hollow unit cells of 2 by 3 inches, pour height of 60 inches.
 - c. For minimum widths of grout spaces of 2-1/2 inches or for minimum grout space of hollow unit cells of 2-1/2 by 3 inches, pour height of 12 feet.
 - d. For minimum widths of grout spaces of 3 inches or for minimum grout space of hollow unit cells of 3 by 3 inches, pour height of 24 feet.
 4. Do Not Exceed the Following Pour Heights for Coarse Grout:
 - a. For minimum widths of grout spaces of 1-1/2 inches or for minimum grout space of hollow unit cells of 1-1/2 by 3 inches, pour height of 12 inches.
 - b. For minimum widths of grout spaces of 2 inches or for minimum grout space of hollow unit cells of 2-1/2 by 3 inches, pour height of 60 inches.
 - c. For minimum widths of grout spaces of 2-1/2 inches or for minimum grout space of hollow unit cells of 3 by 3 inches, pour height of 12 feet.
 - d. For minimum widths of grout spaces of 3 inches or for minimum grout space of hollow unit cells of 3 by 4 inches, pour height of 24 feet.

5. Provide cleanout holes at least 3 inches in least dimension for grout pours over 60 inches in height.
 - a. Provide cleanout holes at each vertical reinforcing bar.
 - b. At solid grouted masonry, provide cleanout holes at not more than 32 inches o.c.
6. Where grouting of cells does not extend full height of wall, install specified grout stop at bottom of lift.
7. Consolidate grout with a mechanical vibrator.
 - a. Use a low velocity vibrator with a 3/4- inch head.
 - b. Vibrate each cell in concrete masonry units twice. Insert vibrator to bottom of lift and activate for 1 to 2 seconds.
 - c. Perform initial consolidation at each cell immediately after grout placement.
 - d. Perform reconsolidation in each cell by reinserting vibrator when grout is still plastic.
8. Interior of block cells shall be dry before grouting operations occur to facilitate proper absorption of water from grout. Wet or saturated surface dry conditions are not allowed, and shall be allowed to fully dry before grout placement.

3.11 FIELD QUALITY CONTROL

- A. Testing Agency: Owner may engage a qualified independent testing and inspecting agency to perform field tests and inspections indicated below and prepare test reports:
 1. Payment for these services will be made by Owner.
 2. Retesting of materials failing to comply with specified requirements shall be done at Contractor's expense.
- B. Testing Frequency: One set of tests for each 5000 sq. ft. (465 sq. m) of wall area or portion thereof.
- C. Mortar Test (Property Specification): For each mix provided, per ASTM C 780.
- D. Grout Test (Compressive Strength): For each mix provided, per ASTM C 1019.
- E. Inspect cores and clean-out holes before grout is placed.

3.12 REPAIRING, POINTING, AND CLEANING

- A. Remove and replace masonry units that are loose, chipped, broken, stained, or otherwise damaged or that do not match adjoining units. Install new units to match adjoining units; install in fresh mortar, pointed to eliminate evidence of replacement.
- B. Pointing: During the tooling of joints, enlarge voids and holes, except weep holes, and completely fill with mortar. Point up joints, including corners, openings, and adjacent construction, to provide a neat, uniform appearance. Prepare joints for sealant application, where indicated.
- C. In-Progress Cleaning: Clean unit masonry as work progresses by dry brushing to remove mortar fins and smears before tooling joints.
- D. Final Cleaning: After mortar is thoroughly set and cured, clean exposed masonry as follows:
 1. Remove large mortar particles by hand with wooden paddles and nonmetallic scrape hoes or chisels.
 2. Test cleaning methods on sample wall panel; leave one-half of panel uncleaned for comparison purposes. Obtain Architect's approval of sample cleaning before proceeding with cleaning of masonry.
 3. Protect adjacent stone and nonmasonry surfaces from contact with cleaner by covering them with liquid strippable masking agent or polyethylene film and waterproof masking tape.
 4. Wet wall surfaces with water before applying cleaners; remove cleaners promptly by rinsing surfaces thoroughly with clear water.
 5. Clean brick by bucket-and-brush hand-cleaning method described in BIA Technical Notes 20 Revised, and manufacturer's printed instructions using the following masonry cleaner:
 - a. Job-mixed detergent solution to remove dirt and soil from standard block to be painted.

- b. Masonry cleaning compound to clean brick. Allow mortar to cure minimum 14 days before cleaning. Do not allow excessive time to elapse that would prevent thorough cleaning of surface or require stronger chemical cleaning.
 - 6. Clean concrete masonry by cleaning method indicated in NCMA TEK 8-2A applicable to type of stain on exposed surfaces.
 - 7. Do not use pressure washing in excess of 700 psi.
- E. Protection: Provide final protection and maintain conditions that ensure unit masonry is without damage and deterioration at time of Substantial Completion.

3.13 REMOVAL AND REPLACEMENT OF EXISTING DAMAGED BRICK

- A. Remove bricks that are damaged, or deteriorated. Carefully demolish or remove entire units from joint to joint, without damaging surrounding masonry, in a manner that permits replacement with full-size units.
 - 1. When removing single bricks, remove material from center of brick and work toward outside edges.
- B. Support and protect remaining masonry that surrounds removal area. Maintain flashing, reinforcement, lintels, and adjoining construction in an undamaged condition.
- C. Notify Architect of unforeseen detrimental conditions including voids, cracks, bulges, rotted wood, rusted metal, and other deteriorated items.
- D. Clean bricks surrounding removal areas by removing mortar, dust, and loose particles in preparation for replacement.
- E. Install replacement brick into bonding and coursing pattern of existing brick. If cutting is required, use a motor-driven saw designed to cut masonry with clean, sharp, unchipped edges.
- F. Lay replacement brick with completely filled bed, head, and collar joints. Butter ends with sufficient mortar to fill head joints and shove into place. Wet both replacement and surrounding bricks that have ASTM C 67 initial rates of absorption (suction) of more than 30 g/30 sq. in. per min. (30 g/194 sq. cm per min.). Use wetting methods that ensure that units are nearly saturated but surface is dry when laid. Maintain joint width for replacement units to match existing joints.
 - 1. Tool exposed mortar joints in repaired areas to match joints of surrounding existing brickwork.

3.14 MASONRY WASTE DISPOSAL

- A. Salvageable Materials: Unless otherwise indicated, excess masonry materials are Contractor's property. At completion of unit masonry work, remove from Project site.
- B. Excess Masonry Waste: Remove excess clean masonry waste and other masonry waste, and legally dispose of off Owner's property.

END OF SECTION