



OFFICE HOURS
10 TO 12 M
4 TO 8 P. M

City of Portland.

OFFICE OF INSPECTOR OF BUILDINGS

.....7-15-12.....191

To the Inspector of Buildings of the City of Portland:

The undersigned respectfully makes application for a permit to erect enlarge a building on.....
.....street, at number.....20.....to be.....
.....Three.....stories high.....Sixty.....feet long.....Eighteen
feet wide; also an addition to be.....stories high.....
feet long.....feet wide, and to be used as a.....Dwelling.....

CELLAR WALL—To be constructed of.....Stone.....to be.....20.....inches wide on bottom and
batter to.....inches on top.

UNDERPINNING—To be.....Undersided.....Height of underpinning from top of cellar wall to bottom of
sill.....ft.....inches to be.....inches in thickness.

EXTERIOR WALLS—To be constructed of.....Wood..... If of Brick, Stone, etc. Total length of wall
.....ft.....inches. Thickness of 1st..... 2d..... 3d..... 4th.....
5th..... 6th..... story walls. If of reinforced concrete state mix and reinforcing system
to be used.

If wood construction..... 6-8..... Girders..... 8-10
Posts..... Girts..... Studs..... 16 in. on c
..... to be spaced..... Dwelling

This building will be used for the purposes of..... (If for apartments,
tenements, or other family uses state number of families accommodated and number on each floor.
If for manufacturing or mercantile purposes state character of business and amount of estimated
weight to be carried by the floor.)

Number of families on floor..... One
Total number of families..... Three
Manufacturing (state character).....
Estimated load on floors per sq. ft..... 50 lbs.
Mercantile business (state character and load per sq. ft.).....

If building is used for tenement house or family use and more than one family, the following provisions
of the Building Laws regarding dividing partitions shall be adhered to (Quote Law re. this).

FIRESTOPS—All bearing and center partitions will have firestops cut in tight on top of each partition
and between each set of floor timbers. Where ledger boards are used there shall be firestops cut in
tight against bottom of ledger boards, of same size as wall studs. Also wherever the Inspector of
Buildings may consider necessary.

STAIRWAYS—No. in building..... Two..... location..... Front & Rear
with..... Stud..... walls to be lathed with..... Wood lathing.

ROOF—To be constructed of..... Wood..... Rafters to be..... 2-8..... inches to be spaced..... 16
..... inches on centers. Roof to be covered with..... Tar & Gravel.....

Gutters to be made of..... None..... Cornices to be made of..... Wood.....

Bay windows to be made of..... Wood..... to be covered with.....

Dormer Windows to be made of..... to be covered.....

Chimneys, Smoke flues to be lined with..... Plus Linings..... provided with a 10 inch outside collar and an
inside collar to go to the inside of the flue.

Estimated Cost of Building \$ 5000

INSPECTION—The Inspector of Buildings is to be notified when building is ready for lathing and at least
24 hours before the lathing is begun.

The Builder is..... Fred. E. Wallace..... Address..... Wilson St.....

The Architect is..... Address.....

The Owner is..... F. S. Greene..... Address..... 43 Angell Ave.....

No Deviation will be made from the above application without written permission from the Inspector of
Buildings.

The above petition was granted the..... day of..... 191

All floor timbers to be 2-8 in. and to be spaced 16 in. on centers.

(Applicant to sign here

F. S. Greene