

## Scale: 1/4" = 1'-0" (Shown over 1st Floor)

2nd FLOOR FRAMING PLAN

GENERAL INFORMATION:

BUILDING OWNER: TIMOTHY GEBHARDT BUILDING ADDRESS: 20 DOW ST. PORTLAND, MAINE

ZONE: R6

USE: RESIDENTIAL 3-UNITS

BUILDING DESCRIPTION:
FRAME TYPE: WOOD FRAMED
NO. STORYS 3 + BASMENT

## GENERAL NOTES:

- 1. THE ENGINEERS'S STAMP IS FOR THE REVIEW OF THE SPECIFIC STRUCTURAL GRAVITY COMPONENTS OF THIS BUILDING.
- 2. THE STRUCTURE IS DESIGNED TO BE SELF SUPPORTING AND STABLE AFTER THE BUILDING IS COMPLETE. IT IS THE CONTRACTOR'S SOLE RESPONSIBILITY TO DETERMINE ERECTION PROCEDURES AND SEQUENCE TO ENSURE SAFTY OF THE BUILDING AND COMPONENTS DURING ERECTION.
- 3. ALL APPLICABLE FEDERAL, STATE, AND MUNICIPAL REGULATIONS SHALL BE FOLLOWED, INCLUDING THE FEDERAL DEPARTMENT OF LABOR OCCUPATION SAFETY AND HEALTH ACT.
- 4. THE PROFESSIONAL ENGINEER'S STAMP DOES NOT IN ANY WAY WARRANTY THE INTERIOR SHEETROCK FINISH AGAINST CRACKING OR SPLITTING DUE TO WOOD SHRINKAGE, MOISTURE CHANGES, ECT.
- 5. ALL CONSTRUCTION SHALL CONFORM TO THE REQUIREMENTS OF IRC and IBC Latest Edition.

## STRUCTURAL DESIGN CRITERIA:

- 1. BUILDING CODE: MUBEC W/ IBC 2009
- 2. DESIGN FLAT ROOF SNOW LOADS: 42 psf
- 3. DESIGN FLOOR LIVE LOADS: 40 psf
- 4. DESIGN DEAD LOAD @ FLOORS: 10 psf
  DESIGN DEAD LOAD @ ROOF : 15 psf

## WOOD FRAMING NOTES:

1. STRUCTURAL LUMBER: No. 2 KILN DRIED, SPRUCE PINE FIR (SOUTH) OR BETTER. MECHANICAL PROPERTIES:  $F_{\text{B}} = 750 \text{ psi} \qquad F_{\text{V}} = 70 \text{ psi} \\ F_{\text{c}} = 975 \text{ psi} \qquad E = 1,100,000 \text{ psi}$ 

LVL MATERIAL SHALL BE BY BOISE, Fb=2800psi, OR EQUAL

- 2. DESIGN CODE: NATIONAL DESIGN SPECIFICATIONS FOR WOOD CONSTRUCTION BY THE NATIONAL FOREST PRODUCTIONS ASSOCIATION.
- 3. FASTENERS: COMPLY WITH RECOMMENED FASTENING SCHEDULE OF IRC, UNLESS SHOWN OTHERWISE ON THE DRAWINGS.
- 4. NAILING REQUIREMENTS FOR PLYWOOD ROOF DECK:
  PROVIDE 8D NAILS AS FOLLOWS UNLESS SHOWN OTHERWISE,
  8D NAILS @ 6" oc ALONG PANEL EDGES.
  8D NAILS @ 12" oc ALONG INTERMEDIATE MEMBERS.
- 5. SPIKE TOGETHER ALL FRAMING MEMBERS WHICH ARE BUILT-UP USING MULTIPLE 2x LUMBER.
- 6. PROVIDE PRESSURE TREATED LUMBER FOR ALL LUMBER IN CONTACT WITH MASONRY OR CONCRETE.
- 7. ALL STEEL SHAPES AND PLATES TO BE ASTM A36 UNLESS NOTED



