

City of Portland, Maine – Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

Location of Construction: 192 Brackett Street 04102		Owner: Nancy Flood		Phone: 207-772-3303		Permit No: 991193
Owner Address: SAA		Lessee/Buyer's Name: N/A		Phone: N/A		
Contractor Name: Screentech Tom		Address: Biddeford, ME		Phone: 207-2125		Permit Issued: NOV 7 1999 CITY OF PORTLAND
Past Use: Mixed Use Apt/Vet Clinic		Proposed Use: Same		COST OF WORK: \$ 0 FIRE DEPT. <input type="checkbox"/> Approved <input type="checkbox"/> Denied Signature:		
				PERMIT FEE: \$ 34.08 INSPECTION: 5197490 Use Group: Type: Signature:		Zone: CBL: 056-C-008 Zoning Approval: Special Zone or Reviews: <input type="checkbox"/> Shoreland <input type="checkbox"/> Wetland <input type="checkbox"/> Flood Zone <input type="checkbox"/> Subdivision <input type="checkbox"/> Site Plan maj <input type="checkbox"/> minor <input type="checkbox"/> mm <input type="checkbox"/>
Proposed Project Description: 2 Signs 1 Sign - 14.4' 1 Sign - 6' Total 20.5 sq. ft.				PEDESTRIAN ACTIVITIES DISTRICT (P.A.D.) Action: Approved <input type="checkbox"/> Approved with Conditions: <input type="checkbox"/> Denied <input type="checkbox"/> Signature: Date:		
Permit Taken By: UB		Date Applied For: 10/7/99				

1. This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules.
2. Building permits do not include plumbing, septic or electrical work.
3. Building permits are void if work is not started within six (6) months of the date of issuance. False information may invalidate a building permit and stop all work..

****Please Send To:** John Flood
192 Brackett St.
Portland, ME 04102

CERTIFICATION

I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit

SIGNATURE OF APPLICANT ADDRESS: DATE: PHONE:

RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE PHONE:

White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

CEO DISTRICT



**THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE
PERMIT IS ISSUED**

**Sign Permit Pre-Application
Attached Single Family Dwellings/Two-Family Dwelling
Multi-Family or Commercial Structures and Additions Thereto**


In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTEIf you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.**

Location/Address of Construction (include Portion of Building): <div style="text-align: right; font-size: 1.2em;">192 BRACKETT 04102</div>		
Total Square Footage of Proposed Structure <div style="text-align: right; font-size: 1.2em;">1500</div>	Square Footage of Lot <div style="text-align: right; font-size: 1.2em;">3952</div>	
Tax Assessor's Chart, Block & Lot Number Chart# 056 Block# C Lot# 008	Owner: <div style="text-align: right; font-size: 1.2em;">NANCY FLOOD</div>	Telephone#: <div style="text-align: right; font-size: 1.2em;">207 772 3385</div>
Owner's Address: <div style="text-align: right; font-size: 1.2em;">192 Brackett St Same</div>	Lessee/Buyer's Name (If Applicable) <div style="text-align: right; font-size: 1.2em;">—</div>	Total Sq. Ft. of Sign Fee <div style="text-align: right; font-size: 1.2em;">20.5 21 S.F. \$ 34.08</div>
Proposed Project Description: (Please be as specific as possible) <div style="text-align: right; font-size: 1.2em;">1 Sign 6 S.F. (Total 2 signs) Free stand 21 S.F. Sign 1 Sign 22" x 8" BRACKETT STREET VETERINARY CLINIC</div>		
Contractor's Name, Address & Telephone <div style="text-align: right; font-size: 1.2em;">DOUGHERTY / JOHN FLOOD</div>		Rec'd By <div style="text-align: right; font-size: 1.2em;">UB</div>
Current Use: <div style="text-align: right; font-size: 1.2em;">remodel MIXED USE vet clinic</div>	Proposed Use: <div style="text-align: right; font-size: 1.2em;">vet clinic SAME</div>	
Screen tech, Biddeford Me <div style="text-align: right; font-size: 1.2em;">Tom @ 282-5125</div>		
Signature of applicant: <div style="text-align: right; font-size: 1.2em;">JG Snow</div>	Date: <div style="text-align: right; font-size: 1.2em;">10/</div>	

Signage Permit Fee: \$30.00 plus .20 per square foot of signage

* Send to: John Flood
192 Brackett St
Portland 04102



SIGNAGE PRE-APPLICATION

PLEASE ANSWER ALL QUESTIONS

ADDRESS: 192 Brackett St 04102

ZONE: B-1

Contract Zone
for Vet use -
underlying zone
for All
other Reg

OWNER: Nancy Flood

APPLICANT: John Flood

ASSESSOR NO. 056-C-008

SINGLE TENANT LOT? YES ☒ NO ☐

MULTI TENANT LOT? YES ☐ NO ☐

FREESTANDING SIGN? YES ☒ NO ☐

(ex. pole sign. . .)

on fence

DIMENSIONS 22" x 8' = 14.4 = 2.88

MORE THAN ONE SIGN?

YES ☒ NO ☐

(2 signs)

DIMENSIONS ~~1.5 x 4~~

BLDG. WALL SIGN? YES ☒ NO ☐

(attached to bldg)

DIMENSIONS 1 1/2 x 4

1.5 x 4 = 6 = 1.20

MORE THAN ONE SIGN?

YES ☒ NO ☐

DIMENSIONS

(TOTAL SQ FT = 20.5)

4.08

LIST ALL EXISTING SIGNAGE AND THEIR DIMENSIONS:

interior lit
sign front of building 4' x 4' to be removed

LOT FRONTAGE (FEET):

38

BLDG FRONTAGE (FEET):

32

AWNING YES ☐ NO ☐ IS AWNING BACKLIT? YES ☐ NO ☐

HEIGHT OF AWNING: _____

IS THERE ANY COMMUNICATION, MESSAGE, TRADEMARK OR SYMBOL ON IT? _____

*** TENANT BLDG. FRONTAGE (IN FEET) _____

*** REQUIRED INFORMATION

AREA FOR COMPUTATION

(6'10")
1.5 x 8.933 = 13.25 # MAX 6# shown
1.5 x 15.166 = 22.749 # MAX 14.4# shown

A SITE SKETCH AND BUILDING SKETCH SHOWING EXACTLY WHERE EXISTING AND NEW SIGNAGE IS LOCATED MUST BE PROVIDED. SKETCHES AND/OR PICTURES OF PROPOSED ARE ALSO REQUIRED.

SIGNATURE OF APPLICANT: John Flood

DATE: 10/7/99

Oct 1, 1999

To whom it may concern,

I give my permission to
John Flood to construct a
sign on my property

Nancy Snow

NANCY FLOOD

BUILDING PERMIT REPORT

DATE: EOCT. 99 ADDRESS: 192 Brackett ST. CBL: 056-C-008
 REASON FOR PERMIT: Signage
 BUILDING OWNER: Nancy Flood
 PERMIT APPLICANT: _____ /Contractor Screen Tech.
 USE GROUP Signage CONSTRUCTION TYPE _____

The City's Adopted Building Code (The BOCA National Building Code/1996 with City Amendments)
 The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)


CONDITION(S) OF APPROVAL

This permit is being issued with the understanding that the following conditions are met: *1, *34.

Approved with the following conditions: _____

- X 1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) **"ALL LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING."**
3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
4. Foundations anchors shall be a minimum of 1/2" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' o.c. between bolts. (Section 2305.17)
5. Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.
6. Precaution must be taken to protect concrete from freezing. Section 1908.0
7. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage means of 1/2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1996)
9. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211
10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.
11. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 36" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". (Sections 1021 & 1022.0) - Handrails shall be on both sides of stairway. (Section 1014.7)
12. Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
13. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use Group minimum 11" tread, 7" maximum rise. (Section 1014.0)
14. The minimum headroom in all parts of a stairway shall not be less than 80 inches (6'8") 1014.4
15. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1014.4)

16. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)
17. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0)
18. The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)
19. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basementsIn addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2.
20. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)
21. The Fire Alarm System shall maintained to NFPA #72 Standard.
22. The Sprinkler System shall maintained to NFPA #13 Standard.
23. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1996)
24. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
25. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
26. Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).
27. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. **No closing in of walls until all electrical (min.72 hours notice) and plumbing inspections have been done.**
28. All requirements must be met before a final Certificate of Occupancy is issued.
29. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building Code/1996).
30. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)
31. Please read and implement the attached Land Use Zoning report requirements.
32. Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code.
33. Glass and glazing shall meet the requirements of Chapter 24 of the building code.
34. All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code 1996).
35. _____
36. _____
37. _____
38. _____


P. Samuel Hoffes, Building Inspector
cc: Lt. McDougall, PFD
Marge Schmuckal, Zoning Administrator

PSH 7/24/99

****On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.**