

Page 223 - LKG Philmore

Basic HTML Version

[Table of Contents](#)

[View Full Version](#)

SWITCHES STANDARD TOGGLE

HEAVY DUTY BAT HANDLE TOGGLE SWITCHES - DPST & DPDT

C

Mounting Hole: 0.500"

Terminal

SPECIFICATIONS:

Current Rating: 20A @125V AC, 10A @ 277V AC
 1-1/2 HP @ 125-250V AC
 Initial Contact Resistance: 50 Meg ohm (Max)
 Insulation Resistance: 100 Meg ohm (Min.) @ 500VDC
 Dielectric Strength: 1000V AC 50/60 Hz for 1 minute
 Contact Material: Brass - Bright Nickel Plate
 Terminal Material: Brass
 Terminal Type: .250" Quick Connect

Part No.	Type	Action	Actuator
30-345	DPST	ON - OFF	Metal
30-320	DPDT	ON - ON	Metal
30-325	DPDT	ON OFF ON	Metal
30-330	DPDT	(ON) OFF (ON)	Metal

NOTE: () = Momentary

HEAVY DUTY BAT HANDLE TOGGLE SWITCHES - DPST & DPDT

C

Mounting Hole: 0.500"

Terminal

SPECIFICATIONS:

Current Rating: 20A @125V AC, 10A @ 277V AC
 1-1/2 HP @ 125-250V AC
 Initial Contact Resistance: 50 Meg ohm (Max)
 Insulation Resistance: 100 Meg ohm (Min.) @ 500VDC
 Dielectric Strength: 1000V AC 50/60 Hz for 1 minute
 Contact Material: Brass - Bright Nickel Plate
 Terminal Material: Brass
 Terminal Type: Screw

Part No.	Type	Action	Actuator
30-312	DPST	ON - OFF	Metal
30-365	DPST	ON - (OFF)	Metal
30-046	DPDT	ON - ON	Metal
30-048	DPDT	ON OFF ON	Metal
30-051	DPDT	ON OFF (ON)	Metal
30-050	DPDT	(ON) OFF (ON)	Metal

NOTE: () = Momentary

HEAVY DUTY BAT HANDLE TOGGLE SWITCHES - DPST & DPDT

C

Mounting Hole: 0.500"

Terminal

SPECIFICATIONS:

Current Rating: 20A @125V AC, 10A @ 277V AC
 1-1/2 HP @ 125/250V AC
 Initial Contact Resistance: 50 Meg ohm (Max)
 Insulation Resistance: 100 Meg ohm (Min.) @ 500VDC
 Dielectric Strength: 1000V AC 50/60 Hz for 1 minute
 Contact Material: Brass - Bright Nickel Plate
 Terminal Material: Brass
 Terminal Type: Solder - Tin Dipped

Part No.	Type	Action	Actuator
30-012	DPST	ON - OFF	Metal
30-052	DPDT	ON - ON	Metal
30-049	DPDT	ON OFF ON	Metal

NOTE: () = Momentary

HEAVY DUTY BAT HANDLE TOGGLE SWITCHES - 3PST & 3PDT

Mounting Hole: 0.500"

Terminal

SPECIFICATIONS:

Current Rating: 17A @125V AC, 12A @ 250V AC
 1-1/2 HP 250V AC 1, 2 or 3 Phase
 Insulation Resistance: 100 Meg ohms
 Dielectric Strength: 1000V (min.)
 Base Material: Phenolic
 Actuator & Bushing Material: Brass/Nickel Plate
 Terminal Type: Screw (#6-32 NC-2 Thread)

Part No.	Type	Action	Actuator
30-10239	3PST	ON - OFF	Metal
30-10240	3PDT	ON OFF ON	Metal
30-10241	3PDT	ON - ON	Metal