










Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 02/21/17




S-5-E



(2X) 3/8-24 THREADED HOLE

General Notes:

1. S-5-E Clamp
2. M8-1.25 bolt
3. 2x 3/8-24 x .500" Setscrews
4. Example roof



FOR STANDING SEAM SPECIFIC MECHANICAL LOAD TEST INFORMATION AND CLAMP INSTALLATION INFORMATION PLEASE VISIT: WWW.S-5.COM

MATERIAL: 6061 T6				METAL ROOF INNOVATIONS, LTD. 8655 TABLE BUTTE RD COLORADO SPRINGS, CO 80908 719-495-0518 719-495-0045(FAX)	
EST ASSEMBLY WEIGHT 0.23 lbs					
SUPPLIED HARDWARE: M8-1.25 x 16 mm Bolt 3/8-24 x .500" Setscrews	TITLE S-5-E Clamp				
SCALE: 1:1	DRAWING NO. E03-B-18-C	DRAWN BY Kati Kadakas	DATE 10/17/2016		
EST. WEIGHT: Clamp: 0.1645 lbs Setscrew: 0.0105 lbs Bolt: 0.0360 lbs	S-5!® PRODUCTS ARE PROTECTED BY MULTIPLE U.S. PATENTS INCLUDING 5,228,248, 5,983,588 AND 6,164,033 (OTHERS ISSUED AND PENDING). EUROPEAN PATENTS ARE ALSO APPLIED FOR AND PENDING UNDER THE PATENT COOPERATION TREATY WITH DIVISIONAL FILING RIGHTS RETAINED. METAL ROOF INNOVATIONS, LTD. (LICENSOR OF S-5!® TECHNOLOGY) AGGRESSIVELY PROSECUTES PATENT INFRINGEMENT.				