



PLAN B FLOOR PLAN

Exterior Door Swing Left or Right Hand Reverse Out Swing, Right Hand Reverse Out Swing Shown.

BUYER ACCEPTANCE PLAN B SIGN AND DATE

0106 2006-09-23

GENERAL

All glazing within 2' arc of doors, whose bottom edge is less than 60" above the floor, and all glazing in door shall be safety glazed, tempered or acrylic plastic sheet.
 Minimum corridor width shall not be less than 36".
 Exterior windows and sliding doors shall be labeled as conforming to AAMA/WDMA/CSA1011.5.2/A440.
 Windows in buildings located in windborne debris regions shall be protected in accordance with Section 301.2.1.2 of the residential code.

DOOR SCHEDULE

Mark	Description	Hardware	Header	Jack Studs	Jamb Studs
Ⓐ	36"x39" Steel Door with 22"x22" window, closer and ball knob	Ball Knob	(1) 2x4 #2 SPF	1	1

WINDOW SCHEDULE

Mark	Description	Glazed Area	Vent Area	Header	Jack Studs	Jamb Studs
Ⓚ	36" x 39" Horizontal Slider, Vinyl Clad Thermal Pane	9.75 ft ²	4.87 ft ²	(1) 2x4 #2 SPF	0	1
Ⓛ	36" x 39" Horizontal Slider, Vinyl Clad Thermal Pane, Tempered Safety Glazing	9.75 ft ²	4.87 ft ²	(1) 2x4 #2 SPF	0	1
Ⓜ	36" x 39" Fixed, Vinyl Clad Thermal Pane	9.75 ft ²	4.87 ft ²	(1) 2x4 #2 SPF	0	1
Ⓨ	36" x 39" Fixed, Vinyl Clad Thermal Pane, Tempered Safety Glazing	9.75 ft ²	4.87 ft ²	(1) 2x4 #2 SPF	0	1

SHEARWALL CONSTRUCTION

- Alternate holdown of equal or greater capacity may be substituted for holdowns specified.
- Holdowns to be installed in accordance with manufacturer's installation instructions.

SHEARWALL SCHEDULE

Mark	Sheathing	Fastening	Framing
Ⓐ	7/16" Structural Sheathing, One Side, Blocked	0.113" x 2.5" nails 8/12 (edge/field)	2x4 SPF @ 16" oc

Twin Modular Services Inc.
 Blackwood, NJ

TITLE:	FLOOR PLAN B	JOB NO:	1MS032212-19
MODEL:	812 GUARD BOOTH	DRAWING NO:	3B

SCALE:	1/2" = 1'-0"	APPROVED BY:	
DATE:	03/26/2012	DRAWN BY:	R. Knowles