City of Portland, Maine – Building or Use Permit Application 389 Congress Street, 04101, Tell (207) 874-8703, FAX: 874-8716

Location of Construction:	Owner:		Phone:		Permit No:
350 Danforth Street	Betsy & Ward Lessee/Buyer's Name:	en Dilworth Phone:		508-448-5873 essName:	71278
Owner Address:	Lessee/Buyer s Ivame.	rnone.	Busilles	siname.	
Contractor Name: Yankee Restoration and Buil	Permit issued				
Past Use: Proposed Use:			COST OF WORK:		
l-fam	l-fam w/interior		\$ 40,000.00		
	renovations	FIRE DEPT.		INSPECTION:	
			Denied	Use Group 13 Type: 5	Zone: CBL: (1 H 1)
		Signature:		Signature: Auffan	R-1 01-H-11
Proposed Project Description:		PEDESTRIAN	ACTIVITIE	<u> </u>	Zoning Approval:
Tatonion Demonstics	Action: Approved Approved with Conditions:			Special Zone or Reviews:	
Interior Renovations (remodel Kitchen adding 1 b				□ Shoreland	
(remoter Areenen addring i b	denitoom remodering 2)		Denied		□ Wetland □ Flood Zone
		Signature:		Date:	
Permit Taken By:	Date Applied For:				□ Site Plan maj □minor □mm □
Sherry Pinard		November 1	9, 1997		Zoning Appeal
1. This permit application does not preclude	□ Variance				
2. Building permits do not include plumbin					
3. Building permits are void if work is not st	□ Conditional Use □ Interpretation				
tion may invalidate a building permit and					
	Denied				
 Sherry Pinard This permit application does not preclude Building permits do not include plumbin Building permits are void if work is not st tion may invalidate a building permit and 				MACUER	Historic Preservation
	□ Not in District or Landmark				
	Does Not Require Review				
	a new a alkration				
	Action why set				
	Appoved i ait.				
I hereby certify that I am the owner of record of	Approved with Conditions				
authorized by the owner to make this applicat					
if a permit for work described in the application areas covered by such permit at any reasonab	Date: 11/21/97				
areas covered by such permit at any reasonab	ie nour to enforce the provisions of the e	oue(s) applicable to suc	n permit		
					1 m
SIGNATURE OF APPLICANT	ADDRESS:	DATE:		PHONE:	- () () ()
Will Cheever					
RESPONSIBLE PERSON IN CHARGE OF W	ORK, TITLE			PHONE:	CEO DISTRICT S MS MUBSOT
White	-Permit Desk Green–Assessor's C	anary–D.P.W. Pink–P	ublic File	lvory Card–Inspector	Mc Muncon
					11311402011

COMMENTS . 23/98 Did Graming inspection - Nork going well - appears to be done for plans. -27-99 I went to see Dext: ear decks at the Request of the owner I have Found that their is no Permit for Extient work and that Two Decks have Been Built along with a Shead IP 9-27-99 **Inspection Record** Туре Date Foundation: Framing: _____ Plumbing: Final: Other: _____

BUILDING PERMIT REPORT

DATE: <u>21 NOU, 97</u>	ADDRESS:	350 Danforth	SY.
REASON FOR PERMIT:	o make interior	renovaTions (OI	1/2~)
BUILDING OWNER: Bei	tsy Warden D	1/worth	
CONTRACTOR: Yank	ee Restoration	and Bldg	
PERMIT APPLICANT:	APPRO	WAL: ×1, ×8 ×9 ×10, ×11×12	
USE GROUP R. 3	BOCA 1990	₩30₩37/17 CONSTRUCTION TYPE	53
~		•	

CONDITION(S) OF APPROVAL

- XI. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
 - 2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)
 - 3. Precaution must be taken to protect concrete from freezing.
 - 4. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
 - 5. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of $\frac{1}{2}$ inch gypsum board or the equivalent applied to the garage means of $\frac{1}{2}$ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
 - 6. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993).
- 7. Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's building code.
- Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, 1-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".)
- Headroom in habitable space is a minimum of 7'6".
- × 9. × 10. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread, 7" maximum rise.
- ⊀ 11. ∦ 12. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6' 8")
- Every sleeping room below the fourth story in buildings of use Groups R and I-I shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.
 - 13. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
 - 14. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's.
- 15. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.
- A16. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms

In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and 1-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

- 17. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
- 18. The Fire Alarm System shall be maintained to NFPA #72 Standard.
- 19. The Sprinkler System shall maintained to NFPA #13 Standard.
- 20. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023, & 1024. Of the City's building code. (The BOCA National Building Code/1996)
- 21. No construction or demolition work shall begin until you have obtained permits for dumpsters or containers. A work Stop Order shall be issued if this requirement is not met.
- 22. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 23. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
- 24. This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's office.
- 25. Ventilation shall meet the requirements of Chapter 12 Sections 1210. of the City's Building Code.
- All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade.
- 27. All requirements must be met before a final Certificate of Occupancy is issued.
- 28. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National Building Code/1996).
- 29. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993).

X30. This permit doesn't Authorize any exterior work-

permit doesn't autorize any New ×31. dwelling 32. 33. 34.

ode Enforcement

cc: Lt. McDougall, PFD Marge Schmuckal