City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Owner: Location of Construction: Phone: Permit No 9 8.0 5 7 3 273-4110 1 11 056 61 THE ROLL OF THE SHEET OF Owner Address: Lessee/Buyer's Name: Phone: BusinessName: Permit Issued: Contractor Name: Phone: Address: Burn Brook & Bar 50.00.100.00.00 41 3 A Strain San Brown 189-3434 1N - 41998COST OF WORK: PERMIT FEE: Past Use: Proposed Use: \$ **145.**00 **FIRE DEPT.** □ Approved INSPECTION: Use Group A-3Type: 5.43 1 35 0 ☐ Denied Zone: BOC491 33 1 January 1 3 Signature: Signature: Zoning Approval: Proposed Project Description: PEDESTRIAN ACTIVITIES DISTRICT Action: Approved Special Zone or Reviews: Approved with Conditions: ☐ Shoreland LANGE TO BUT DOWN IN Denied □Wetland ☐ Flood Zone □ Subdivision Signature: Date: ☐ Site Plan mai ☐minor ☐mm ☐ Permit Taken By: Date Applied For: Lang Sate & A 1.9 **Zoning Appeal** □Variance This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. ☐ Miscellaneous Building permits do not include plumbing, septic or electrical work. ☐ Conditional Use Building permits are void if work is not started within six (6) months of the date of issuance. False informa-☐ Interpretation □ Approved tion may invalidate a building permit and stop all work.. □ Denied **Historic Preservation** □ Not in District or Landmark ☐ Does Not Require Review ☐ Requires Review Action: CERTIFICATION ☐ Appoved ☐ Approved with Conditions I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been □ Denied authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all Date: areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit 1 7 7 1937 SIGNATURE OF APPLICANT ADDRESS: DATE: PHONE: RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE PHONE: **CEO DISTRICT**

White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

COMMENTS

4/11/98 - Savna tube (just holes) - Holes 4'-0" + relivilding porch - brick Steps need to be addressed - seriously deteriorating - told contractor they should be rebuilt.
porch - brick steps need to be addressed - seriously
deteriorating - told contractor they should be rebuilt.
6/12/98-Framing-OK need to build temp. Step in fort- over top brick step due to deterioration.
over top brick step due to deterioration.
9-3-99 Porsk is compleated oktoclose (R)
Inspection Record

BUILDING PERMIT REPORT

DATE: 3 MAY 98 ADDRESS: 1/2 M/5 TST. (963-A-9/3) REASON FOR PERMIT: To Make Ext. Renovation (repairs) BUILDING OWNER: Hank & Hang Beast T CONTRACTOR: Hundrew T. General T CONTRACTOR: Hundrew T. General T USE GROUP R-3 BOCA 1996 CONSTRUCTION TYPE 5 B CONDITION(S) OF APPROVAL This Permit is being issued with the understanding that the following conditions are met: Approved with the following conditions: 1 2 B S S S S S S S S S S S S S S S S S S					
BUILDING OWNER: Hank & Hong Beart CONTRACTOR: Buckey J. Gree. PERMIT APPLICANT: USE GROUP R-3 BOCA 1996 CONSTRUCTION TYPE 5.73 CONDITION(S) OF APPROVAL This Permit is being issued with the understanding that the following conditions are met: Approved with the following conditions: A B J. B					
DECA 1996 CONSTRUCTION TYPE 5 BOCA 1					
BOCA 1996 CONSTRUCTION TYPE 5 1/3 CONDITION(S) OF APPROVAL This Permit is being issued with the understanding that the following conditions are met: Approved with the following conditions: 4 1/4 1/4 1/4 1/4 1/4 1/4 1/4 1/4 1/4 1					
CONDITION(S) OF APPROVAL This Permit is being issued with the understanding that the following conditions are met: Approved with the following conditions: Before concrete for freeze of concrete for freezing. Before concrete for foundation is placed, approvate from the Development Review Coordinator and Inspection Service obtained. (A 24 hour notice is required prior to inspection) Precaution must be taken to protect concrete from freezing. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is verify that the proper setbacks are maintained. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated if adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fir rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOC Mechanical Code/1993). Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the cibuilding code. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevate surfaces for the pu					
CONDITION(S) OF APPROVAL This Permit is being issued with the understanding that the following conditions are met: Approved with the following conditions: ** ** ** ** ** ** ** ** ** **					
This Permit is being issued with the understanding that the following conditions are met: Approved with the following conditions: ** ** ** ** ** ** ** ** ** **					
1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. 2. Before concrete for foundation is placed, approvale from the Development Review Coordinator and Inspection Service obtained. (A 24 hour notice is required prior to inspection) 3. Precaution must be taken to protect concrete from freezing. 4. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is verify that the proper setbacks are maintained. 5. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fir rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996) 6. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOC Mechanical Code/1993). 7. Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city building code. 8. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevate surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a lad (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more I Handrail grip size shal					
 This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Service obtained. (A 24 hour notice is required prior to inspection) Precaution must be taken to protect concrete from freezing. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This verify that the proper setbacks are maintained. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fir rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOC Mechanical Code/1993). Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the cibuilding code. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevate surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and public garages and open parking structures, open guards shall have balusters or be of solid material su					
 Before concrete for foundation is placed, approvale from the Development Review Coordinator and Inspection Service obtained. (A 24 hour notice is required prior to inspection) Precaution must be taken to protect concrete from freezing. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is verify that the proper setbacks are maintained. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated to adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fir rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOC Mechanical Code/1993). Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the cibuilding code. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevate surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere diameter of 4" cannot pass through any opening. Guards shall not have an ornamental patter	_				
obtained. (A 24 hour notice is required prior to inspection) Precaution must be taken to protect concrete from freezing. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is verify that the proper setbacks are maintained. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fir rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOC Mechanical Code/1993). Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the cibuilding code. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevate surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a lad (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". Headroom in habitable space is a minimum of 7'6".					
 Precaution must be taken to protect concrete from freezing. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is verify that the proper setbacks are maintained. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fir rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsoard or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOC Mechanical Code/1993). Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the cibuilding code. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevate surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a lad (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more Handrail grip size shall have a circular cross section	s must be				
 It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is verify that the proper setbacks are maintained. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fir rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOC Mechanical Code/1993). Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the cibuilding code. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevate surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a lad (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". Headroom in habitable space is a minimum of 7'6". Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7					
 verify that the proper setbacks are maintained. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fir rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOC Mechanical Code/1993). Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the cibuilding code. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevate surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a lad (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". Headroom in habitable space is a minimum of 7'6". Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group 					
 Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fir rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOC Mechanical Code/1993). Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the cibuilding code. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevate surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level, height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a lad (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". Headroom in habitable space is a minimum of 7'6". Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group 	s done to				
spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypboard or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996) 6. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOC Mechanical Code/1993). 7. Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the cibuilding code. 8. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevate surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a lad (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". Headroom in habitable space is a minimum of 7'6". 9. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group	e resisting				
 board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOC Mechanical Code/1993). Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the cibuilding code. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevate surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a lad (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". Headroom in habitable space is a minimum of 7'6". Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group 					
 Mechanical Code/1993). Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the cibuilding code. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevate surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a lad (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more thandrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". Headroom in habitable space is a minimum of 7'6". Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group 	·				
 building code. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevate surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a lade (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". Headroom in habitable space is a minimum of 7'6". Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group 	A National				
 Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevate surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a lad (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more thandrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". Headroom in habitable space is a minimum of 7'6". Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group 	iy's				
public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a lad (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". Headroom in habitable space is a minimum of 7'6". Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group	Minimum				
 (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 4 Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". Headroom in habitable space is a minimum of 7'6". Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group 	vith a				
Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". Headroom in habitable space is a minimum of 7'6". Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group					
 Headroom in habitable space is a minimum of 7'6". Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group 	1an 38".)				
10. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group	* ***				
11" tread. 7" maximum rise.	ninimum				
11. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6' 8")					
12. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window					
exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of	wor				
knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height no					
than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear					
opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches	special t more				
and a minimum net clear opening of 5.7 sq. ft.	pecial t more et clear				
13. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable	special t more et clear (508mm),				
exits directly from the apartment to the building exterior with no communications to other apartment units. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors	special t more et clear (508mm),				
closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.)	epecial t more et clear (508mm), when it				
The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by prautomatic extinguishment.	epecial t more et clear (508mm), when it				

All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the

8

16.

provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):

- In the immediate vicinity of bedrooms
- In all bedrooms
- In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

- 17. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
- 18. The Fire Alarm System shall be maintained to NFPA #72 Standard.
- 19. The Sprinkler System shall maintained to NFPA #13 Standard.
- 20. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
- 21. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a 22. certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
- 23. Ventilation shall meet the requirements of Chapter 12 Sections 1210. Of the City's Building Code.
- 24. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade.
- 25. All requirements must be met before a final Certificate of Occupancy is issued.
- **∑** 26. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National Building Code/1996).

27.	Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993).
28. 29.	Please read and implement the attached Land Use-Zoning report requirements.
30.	
31.	
32.	

die Enforcement

cc: Lt. McDougall, PFD Marge Schmuckal

— Proposal =



ANDREW J. GREER

General Contractor

167 Mussey Street SOUTH PORTLAND MAINE 04106 (207) 767-5489

PROPOSAL SUBMITTED TO	/	HONE	DATE
STREET SCALE WE Chara Se	hart	ファッシュア <u>スパー</u> OB NAME	5/1/98
17 9/10 P P. 1	3	OB NAME	·
CITY, STATE and ZIP CODE		OB LOCATION	
CITY, STATE and ZIP CODE green JY10 2 ARCHITECT			
ARCHITECT	DATE OF PLANS		JOB PHONE
			772-1625
We hereby submit specifications and estimates for:			
Q .	Ink on front p.	net - 1) Kept	are cerating supports
In Sock will ment ?"	sometimes and	VIVPI pusts ?	I Replace all existing
healing with ment to a			
report and or replace is	Explorable so	more def. 4.) Key	something up no
Il columns no neceled	to malel.	evisting 5) Repl	no lettres inclinents
leak will now squeeze o			
worlding and a term on ,			
Along the con of this p			
8) its stans will no	y be removed -	rebuiltable 2	alo detel
Photography to me. Thank	lago sign s	typ while copy	ad relum the yellow
upy he me. Thente	3 ;		
We Propose hereby to furnish	material and labor — co	ned in accordance with	above specifications, for the sum of:
Payment to be made as follows:	nels + 101/6		dollars (\$).
Those weekly with	remainin ans	word ada & roll	Is determed to the in?
Grand due of the into	completion	and the second	
All material is guaranteed to be as specified All work manner according to standard practices. Any alteration or involving extra costs will be executed only upon written	deviation from above specifications	Authorized 20 9. /	face.
charge over and above the estimate. All agreements or delays beyond our control. Owner to carry fire, tornar Our workers are fully covered by Workman's Compensation	contingent upon strikes, accidents do and other necessary insurance.	Note: This proposal r withdrawn by us if not accepted	
			
Acceptance of Proposal $- au$	he above prices, specifications		
and conditions are satisfactory and are hereby to do the work as specified. Payment will be m	•	Signature	
V/13/GR	idae as outlined above.		
Date of Acceptance:		Signature	

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Application Additions/Alterations/Accessory Structures

To Detached Single Family Dwelling

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Address of Construction: 107 West 5	treet		
Tax Assessor's Chart, Block & Lot Number Chart# (} Block# A Lot# / 3	Owner (Henry) Hank & Anna Bensi	Telepho 773	one#:
Owner's Address: 107 Wist street	Lessee Buyer's Name (If Applicable)	Cost Of Work	0,00,
Proposed Project Description:(Please be as specific as possible	No fortpunt (Rost : 1) vere sheet lattice & Me	seived or areala	PURCHUNLY) TO COLUMNS WITH
Separate permits are required for I	nternal & External Plumbing	HVAC and Electrical	installation.
•All construction must be conducted in comp •All plumbing must be cond •All Electrical Installation must comply •HVAC(Heating, Ventilation and Air Cond You must Include the following with you	ucted in compliance with the Sta with the 1996 National Electrica ditioning) installation must comp	te of Maine Plumbing Cod I Code as amended by Sec	e. tion 6-Art III. fechanical Code.
2) A Copy of	our Deed or Purchase and Syour Construction Contraction	et, if available	45 <u>00</u> W
If there is expansion to the structure, a co The shape and dimension of the lot, all e property lines. Structures include decks pools, garages and any other accessory s Scale and required zoning district setbace	existing buildings (if any), the propo porches, a bow windows cantilever structures.	must include: sed structure and the distant	
4) Bu	ild jing Plans (Sample Attac	ehed)	
A complete set of construction drawings Cross Sections w/Framing details (include Floor Plans & Elevations Window and door schedules Foundation plans with required drainage Electrical and plumbing layout. Mechanic equipment, HVAC equipment (air handled I hereby certify that I am the Owner of record of the named propowner to make this application as his/her authorized agent. I agapplication is issued, I certify that the Code Official's authorized application is sisued, I certify that the Code Official's authorized agent.	and dampproofing and dampproofing ical drawings for any specialized equing or other types of work that ma Certification perts, or that the proposed work is authorized the conform to all applicable laws of this	uipment such as furnaces, consequences are required special review must by the owner of record and that I liprisdiction. In addition, if a permit	himneys, gas at be included. have been authorized by the for work described in this
enforce the provisions of the codes applicable to this permit. Signature of applicant:	<u> </u>	Date: 5/8/98	

su bock side

3.) Repair & Well (Failing) as revealed then replace existing aluminum siding with new pine clapbonds

4) Replace all cleeking with new deeking to match existing

5.) Replace supports for cleek with new 8" sonstribes and support posts (4xypt) where needed (filled with concrete)

6) Replace and or prepair any missing trin to match existing

7.) He some stairs to the cheek will be removed promption with plans for new stairs to be submitted at a later date

8.) Frachy repairing any rot that is parountered along the way, which possibly could involve the beam above the culumns

