City of Portland Maine -	- Building or Use Permit Application	389 Congress Street 04101	Tel: (207) 874-8703 FA	X · 874-8716
City of a of fiand, Manie -	building of Ose I crimit Application	Jos congress succi, otioi	, 101. (207) 017-0700, 1M	A. 014-0110

Location of Construction:	Owner:		Phone:	773-6622	Permit No: 9 80732
Owner Address:	Lessee/Buyer's Name:	Phone:	Busines		The second secon
SAA 04102	Lessee/Duyer straine.	r none.	Dusines	or value.	PERMIT ISSUED
Contractor Name:	Address:	Phon	e:		Permit Issued:
Deat Line	Drap good Llog:	COST OF WOR	K.	PERMIT FEE:	JUL - 7 1998
Past Use:	Proposed Use:	\$ 450.00	K .	\$ 25.00	
1-f.mm		FIRE DEPT.	Approved	INSPECTION:	CITY OF PORTLAND
			Denied	Use Group:// Type: 🐓	
		0.		Stranger 1	Zone: CBL: 063-6-019
Proposed Project Description:		Signature: PEDESTRIAN	CTIVITIE	Signature: S DISTRICT (P.A.D.)	Zoning Approval:
		Action:	Approved		Special Zone or Reviews:
Lower existing bulkhead 6 en	pand deck & rail system		Approved v	with Conditions:	Special Zone of Reviews.
Not exceeding footprints			Denied		Lavecturia
		Signature:		Date:	Flood Zone Subdivision
Permit Taken By:	Date Applied For:			Dure.	Site Plan maj Eminor Emm
MG		30 June 1998			Zoning Appeal
1. This permit application does not preclude	the Applicant(s) from meeting applicable	e State and Federal rules.			□ Variance
2. Building permits do not include plumbin					Conditional Use
 Building permits are void if work is not st 		issuance. False informa-			
tion may invalidate a building permit and					
			WIT	PERMIT ISSUED H REQUIREMENTS	Historic Preservation
				REDUSSUED	□ Not in District or Landmark □ Does Not Require Review
				REMENTO	Requires Review
				-11/2.	
					Action:
	CERTIFICATION				Appoved
I hereby certify that I am the owner of record of					Denied
authorized by the owner to make this applicat if a permit for work described in the application					
areas covered by such permit at any reasonab				te die uddiorny to erner an	Date:
	÷				
		01 July 1998			
SIGNATURE OF APPLICANT	ADDRESS:	DATE:		PHONE:	[
RESPONSIBLE PERSON IN CHARGE OF W	ORK, TITLE			PHONE:	CEO DISTRICT 2
	-Permit Desk Green-Assessor's C				

COMMENTS 13/98 - Called owner - left message -8/18/98 MR. FOOTEWILL REDUCE THE DECK ON THE LEFT TO FIT ON THE ERISFING BUCKHEAD FOUR PRINE + USE THE BULK HEAD FOUNDATION TO HOLD THE DECK INSTEAD OF SUNOR TUBES. 1/15/00- work trushed and apprais to most permit requirements 020 permit # 980732 CR1# 163-6-19 **Inspection Record** Type Date Foundation: Framing: Plumbing: Final: Other:

Applicant: Stephen Foote	Date: 7/2/98
	C-B-L: 63-G-19
CHECK-LIST AGAINST ZONING	ORDINANCE
Date - Tristan - Zone Location - P-4	
Interior or corner lot -	
Proposed Use/Work -	
Servage Disposal -	
Lot Street Frontage -	*
Front Yard - NA	Flammer Eh
Rear Yard - 25 reg - News Section 21	5 Slown - Using see lon
Front Yard - NA Rear Yard - 25 'reg - News Section 21's Side Yard - 10 ' reg - 11,5 Abun 14-	453 MAN ALLEN april
Projections -	
Width of Lot -	
Height -	
Lot Area -	
Lot Coverage/ Impervious Surface -	
Area per Family -	
Off-street Parking -	
Loading Bays -	
Site Plan -	
Shoreland Zoning/ Stream Protection - W	
Flood Plains - NA	

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

ding on Use Donmit Dre Applicat

Building or Use Permit Pre-Application

Additions/Alterations/Accessory Structures

To Detached Single Family Dwelling

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on any property within the ______ City, payment arrangements must be made before permits of any kind are accepted.

Location/Address of Construction:	171	VAUghan	ST.	PORTLAND	04102	
						-

Tax Assessor's Chart, Block & Lot Number Chart#063 Block# & Lot#019	Owner: STEPHEN W. FOOTE	Telephone#: 773-6622
Owner's Address: 171 Vaughan St.		st Of Work: Fee 450. § 25
Proposed Project Description:(Please be as specific as possible)		

LOWER EXISTING BULKHEAD & EXPANDING DECK + Rail SYSTEM NOT EXCEDING FOOTPRINT

Contractor's Name, Address & Telephone

Separate permits are required for Internal & External Plumbing, HVAC and Electrical installation. •All construction must be conducted in compliance with the 1996 B.O.C.A. Building Code as amended by Section 6-Art II.

Rec'd By:

JUN 3 D 1998

•All plumbing must be conducted in compliance with the State of Maine Plumbing Code.

•All Electrical Installation must comply with the 1996 National Electrical Code as amended by Section 6-Art III. •HVAC(Heating, Ventilation and Air Conditioning) installation must comply with the 1993 BOCA Mechanical Code. You must Include the following with you application:

1) A Copy of Your Deed or Purchase and Sale Agreement

2) A Copy of your Construction Contract, if available

3) A Plot Plan (Sample Attached)

If there is expansion to the structure, a complete plot plan (Site Plan) must include:

- The shape and dimension of the lot, all existing buildings (if any), the proposed structure and the distance from the actual property lines. Structures include decks porches, a bow windows cantilever sections and roof overhangs, as well as, sheds, pools, garages and any other accessory structures.
- Scale and required zoning district setbacks

4) Building Plans (Sample Attached)

A complete set of construction drawings showing all of the following elements of construction:

- Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)
- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.

Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.

Signature of applicant: Achurul.	Inte	Date:
	#05 00 C 1 \$1000	5 00 \$1 000 00

Site Review Fee: \$150.00/Building Permit Fee: \$25.00 for the 1st \$1000.cost plus \$5.00 per \$1,000.00 construction cost thereafter.

BUILDING PERMIT REPORT

DATE: 7 July 98 ADDRESS: 171 Vaughan ST, Ø63-G-Ø19 REASON FOR PERMIT: EXTERIOR YENOVATIONS
REASON FOR PERMIT: FXTerior renovations
BUILDING OWNER: S. FOOTE
contractor: SAA
PERMIT APPLICANT: SAA
USE GROUP $R-3$ BOCA 1996 CONSTRUCTION TYPE 3 B
CONDITION(S) OF APPROVAL

This Permit is being issued with the understanding that the following conditions are met:

Approved with the following conditions: $\frac{1}{2}$, $\frac{$

- 1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
- 4 2. Before concrete for foundation is placed, approvalg from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)
 - 2.5 Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material.
 - 3. Precaution must be taken to protect concrete from freezing.
 - 4. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
 - 5. Private garages located <u>beneath habitable rooms</u> in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
 - 6. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993).
 - ^{*}7. Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's building code.
- K8. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36" In occupancies in Use Group A, B, H-4, I-I, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2"
 - 9. Headroom in habitable space is a minimum of 7'6"
- $\sqrt{10}$. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread. 7" maximum rise.
- 11. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6' 8")
- 12. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension.

shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.

- Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable 13. when it exits directly from the apartment to the building exterior with no communications to other apartment units.
- All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with 14. self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.)
- The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by 15. providing automatic extinguishment.
- All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the 16. provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and 1-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

.

- A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an 17. approved type.
- The Fire Alarm System shall be maintained to NFPA #72 Standard. 18.
- 19. The Sprinkler System shall maintained to NFPA #13 Standard.
- All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 20. 1023, & 1024, Of the City's building code. (The BOCA National Building Code/1996)
- Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to 21. excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a 22. certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
- Ventilation shall meet the requirements of Chapter 12 Sections 1210. Of the City's Building Code. (crawl spaces & attics) 23.
- All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. 24.
- 25. All requirements must be met before a final Certificate of Occupancy is issued.
- All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA -26. National Building Code/1996).
- Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National 27. Mechanical Code/1993).
- Please read and implement the attached Land Use-Zoning report requirements. 28. Achors (Fasthers) Shall be phyced between Foundation and Frammer

members.

\$ 29.

30.

31.

32.

Samhel Hoffses, Building Inspector


cc: L1. McDougall, PFD Marge Schmuckal

PSH 6-28-48



0 CANOPY-Jois T - 246 216 30 Deck 5/4 bolts 1/2" 4 OC Guard 36" 2×6 334 1/2" PENACY LATICE (ALSO OVERS BULKHAD) GRADE-2

171 VAUGHAN - PROPOSAL PROJECT WOULD ENTAIL LOWERING EXISTING BULKHEAD TO GRADE LEVEL, AND EXTENDING THE EXISTING PORCH TO ENLARGE DECK SPACE -NOT TO EXCEED CURRENT FOOTPRINT. DECK SURFACE WOULD BE HINGEP AGAINST THE HOUSE TO ALLOW BULKHEAD TO BE OPENED. ALL MATERIALS TO BE STANDARD, PRESSURE - TREATED LUMBER. PROJECT NOT TO EXCEED \$ 450. AND WILL BE ONNER-BULLT. THE STRUCTURE IS NOT VISIBLE FROM THE STREET. SCALE ONE-SQUARE = 6" - 0



-> SHOWS AREA DISCUSSED ABOVE



1