City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

Location of Construction:	Owner:	Phone:		Permit No:
Owner Address: John St. #132 Owner Address: John St. #102 O410	Lessee/Buyer's Name:	Phone: Busines	N/A sName: lvermen/Jone Welso	991159
Contractor Name:	Address:	Phone:		Permit Issued: 0CT 2 6 1999
Past Use:	Proposed Use:	COST OF WORK:	PERMIT FEE:	001 2 0 1333
Office	hassage Therepy	FIRE DEPT. □ Approved □ Denied	INSPECTION: Use Group P Type 3 P BOCA & GLODE	Zone: CBL: 064-A-002
Proposed Project Description:		Signature: PEDESTRIAN ACTIVITIE	Signature:	Zoning Approval:
Chauge of Une from Office to Ha	anage Therapy.	Action: Approved	with Conditions:	☐ Shoreland
Permit Taken By:	Date Applied For:	10-20-99	Date,	☐ Site Plan maj ☐minor ☐mm ☐
 This permit application does not preclude Building permits do not include plumbing Building permits are void if work is not station may invalidate a building permit and 	g, septic or electrical work. arted within six (6) months of the date of	issuance. False informa- Bead To: Valerie H. B. Body logic Mr. 222 St. John Portland HE	T Inc. St. #132	☐ Miscellaneous ☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied Historic Preservation ☐ Not in District or Landmark ☐ Does Not Require Review ☐ Requires Review Action:
I hereby certify that I am the owner of record of authorized by the owner to make this application if a permit for work described in the application areas covered by such permit at any reasonable	on as his authorized agent and I agree to in is issued, I certify that the code officia	conform to all applicable laws of the l's authorized representative shall have	is jurisdiction. In addition,	□ Denied
SIGNATURE OF APPLICANT	ADDRESS:	DATE:	PHONE:	PERMITISSUED
RESPONSIBLE PERSON IN CHARGE OF W	ORK, TITLE		PHONE:	CEO DISTRICT
White	Darmit Dook Cross Assessaria C	onen: D.D.W. Dink Dublic File I	han Card Innanta	MP

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application

Attached Single Family Dwellings/Two-Family Dwelling

Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

	¥-	
Location/Addressof Construction (include Portion of Building)	222 St. John St. #13	2 Por Hand. ME 0/102
Total Square Footage of Proposed Structure	Square Footage of Lot	
Tax Assessor's Chart, Block & Lot Number	Owner ST John Roelly	To (/Telephone#:
Chart DG U Block#A Lot# (D)	* XBODY LOGIC N	MT 773 1215
Owner's Address:	Lessee/Buyer's Name (If Applicable)	Cost Of Work: Fee
282 St John St # 102	Valery M. Blur , Ilonas Joan Velson	\$ 0 \$ 30.00
Proposed Project Description:(Please be as specific as possible)		
Change of use from oh	Ree to mossage there	pa aRice
Contractor's Name, Address & Telephone N/A	ophico	Rec'd By UB
Current Use:	Proposed Use: 46	Massage Thereby
•All construction must be conducted in compl	ected in compliance with the State of with the 1996 National Electrical Co	ng Code as amended by Section 6-Art II. Maine Plumbing Code. de as amended by Section 6-Art III.
You must Include the following with you application		DEPT. OF BUILDING INSPECTIO
1) ACopy of	Your Deed or Purchase and Sale Ag	
2) A Copy o	of your Construction Contract, if ava 3) A Plot Plan/Site Plan	OCT 2 0 1999
Minor or Major site plan review will be required fo	r the above proposed projects. The atta	
checklist outlines the minimum standards for a site	4) Building Plans	ULEGEIVE
Unless exempted by State Law, constru		The second secon
A complete set of construction drawings showing a	ll of the following elements of construc	tion:
Cross Sections w/Framing details (includ	ing porches, decks w/ railings, and according	essory structures)
Floor Plans & Elevations		
Window and door schedules	and the control of th	
Foundation plans with required drainage Electrical and plumbing layout. Mechanic		nent such as furnaces, chimneys, oas
equipment, HVAC equipment (air handli		
equipment, 111710 equipment (an nanun	Certification	free a strange and said would be ween and
bereby certify that I am the Owner of record of the named prop		he owner of record and that I have been authorized by the

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.

		The second secon	
Signature of applicant:	len	4 Blais	Date: 9/30/99

Building Permit Fee: \$30.00 for the 1st \$1000.cost plus \$6.00 per \$1,000.00 construction cost thereafter.

Additional Site review and related fees are attached on a separate addendum

BodyLogic NMT

222 St. John Street, # 132, Portland, ME 04102 207-773-1215

Valerie M. Blais RN, BSN, LMT Certified Neuromuscular Therapist

Mor The Will ornorm: Delaw is a decivery of the Seal (132) which I where with Olora Letwermen and Joanne splean-We east practice massage therepy and share -the westery room and storage. Hall way STOROGE Valoria Blais 11X 16 Parking Lot at boile of building

BUILDING PERMIT REPORT

DATE 21001.99 , ADDRESS: 222.51. John ST. #132 CBL: 064-A-602	
REASON FOR PERMIT: Viange of USE From Office To Massage Therasy	e.
BUILDING OWNER: ST. John RealTy	
PERMIT APPLICANT: Bod 4/091C NMI Inc. (Contractor	
USE GROUP B CONSTRUCTION TYPE 3 B	
The City's Adopted Building Code (The BOCA National Building Code/1996 with City Amendments)	
The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993) Construction Cost: Permit Fees:	_
CONDITION(S) OF APPROVAL	
This permit is being issued with the understanding that the following conditions are met: * (, *27 *33	

1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.

Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained.
 (A 24 hour notice is required prior to inspection)" <u>ALL</u> LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING."

- 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
- 4. Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' o.c. between bolts. (Section 2305.17)
- 5. Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.
- 6. Precaution must be taken to protect concrete from freezing. Section 1908.0
- 7. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- 8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1996)
- All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211
- Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.
- Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 3e4" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 ½" and not greater than 2". (Sections 1021 & 1022.0) Handrails shall be on both sides of stairway. (Section 1014.7)
- 12. Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
- 13. Stair construction in Use Group R-3 & R-4is a minimum of 10" tread and 7 3/4" maximum rise. All other Use Group minimum 11" tread, 7" maximum rise. (Section 1014.0)
- 14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4
- Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1010.4)

15.	Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)
17.	All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0)
18.	The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)
19.	All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 &19. (Smoke
	detectors shall be installed and maintained at the following locations):
	 In the immediate vicinity of hedrooms
	 In all bedrooms
	 In each story within a dwelling unit, including basements
	In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall
	receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2.
20.	A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)
21.	The Fire Alarm System shall maintained to NFPA #72 Standard.
22,	The Sprinkler System shall maintained to NFPA #13 Standard.
23.	All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1996)
24.	Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
25.	The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
26.	Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).
\(\frac{1}{27}\) 27.	All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all electrical (min.72 hours notice) and plumbing inspections have been done.
28.	All requirements must be met before a final Certificate of Occupancy is issued.
29.	All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building Code/1996).
30.	Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)
31.	Please read and implement the attached Land Use Zoning report requirements.
32.	Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code.
χ^{33}_{34}	Glass and glazing shall meet the requirements of Chapter 24 of the building code.
34.	All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code

35. 36. 37. 38.

Samuel Molkes, Building Inspector
Lt. McDougall, PFD
Marge Schmuckal, Zoning Administrator

PSH 7/24/99

^{**}On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.