# City of Portland, Maine – Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

Location of Construction:	Owner:		Phone:	Permit No 80880
			7 1 4 5	
Owner Address:	Lessee/Buyer's Name:	Phone:	BusinessName:	PERMIT ISSUED
LARXEREN 1. N. SINGER - OATLA	a sa			
Contractor Name:	Address:	Phone	2:	Permit Issued:
She was all the first and a	133 Constant St. Etta.	·····································		AUG 1'1 1998
Past Use:	Proposed Use:	COST OF WORI	K: PERMIT FEE:	
		\$	\$	
		FIRE DEPT.		CITY OF PORTLAND
				OTT OT FORTERING
North 1010日 (11日本			Denied Use Group 77 Type:	Zanat CPL
aliatin a substantia ang ang ang ang ang ang ang ang ang an			BOCAGE	Zone: CBL:
	<u>+</u>	Signature:	Signature	
Proposed Project Description:		PEDESTRIAN A	CTIVITIES DISTRICT (P.A.D.)	Zoning Approval:
		Action:	Approved	Special Zone or Reviews:
Whoge SURE TO Add MUSICHESS/C1	encleally Service			opecial zone of iteriews.
			Demeu	
			_	
		Signature:	Date:	
Permit Taken By:	Date Applied For:	a		□ Site Plan maj □minor □mm □
3P		vă Auxuat 1942		
				Zoning Appeal
1. This permit application does not preclude the	Applicant(s) from meeting applicable Sta	ate and Federal rules.		
2. Building permits do not include plumbing, se	eptic or electrical work.			
	-			
3. Building permits are void if work is not started		ance. False informa-		□ Interpretation
tion may invalidate a building permit and sto	p all work			
				Denied
			Do	
			WITCHRAGE	
			APECISO	□Not in District or Landmark
			CUIDSUED	Does Not Require Review
			NEME	Requires Review
			"INTO	
			WITH REQUIREMENTS	Action:
	CERTIFICATION			
I hereby certify that I am the owner of record of the				
authorized by the owner to make this application a				
if a permit for work described in the application is	issued, I certify that the code official's a	uthorized representati	ive shall have the authority to enter	all Date:
areas covered by such permit at any reasonable ho	our to enforce the provisions of the code(	(s) applicable to such	permit	
	-	••	-	
	-4 Au	Qual 1995		
SIGNATURE OF APPLICANT	ADDRESS:	DATE:	PHONE:	—
SIGNALORE OF ALL LICANT		DALE.	THOME.	
RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE PHONE:				
RESPONSIBLE FERSON IN UNARGE OF WORK, HILE PHUNE:				CEO DISTRICT 3
Albita Da	mit Dock Groop Accosor's Cons		blic Filo Ivon Card Increator	
white-Pe	ermit Desk Green–Assessor's Cana	iy-D.F.W. Fillk-PU	bit rile ivory card-inspector	ml/mu

BUILDING PERMIT REPORT					
DATE: 7/AU9/98 ADDRESS: 253 Valley ST (064-E-002)					
REASON FOR PERMIT: Change of USE Ladd CLeaning Business					
BUILDING OWNER: T. CUMMI195					
CONTRACTOR: 2. Lawrence					
PERMIT APPLICANT:					
USE GROUP <u>P-3</u> BOCA 1996 CONSTRUCTION TYPE <u>J</u>					
<u>CONDITION(S) OF APPROVAL</u>					
This Permit is being issued with the understanding that the following conditions are met:					
Approved with the following conditions: $\frac{x_1}{x_2} + \frac{x_3}{3} + \frac{x_4}{3} + \frac{x_5}{3} + \frac{x_6}{3} $					
<ol> <li>This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.</li> <li>Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)</li> </ol>					
2.5 Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 size. The drain shall extend a minimum of 12 inches					
beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material.					
2.6 Foundations anchors shall be a minimum of 1 1/2" in diameter, 7" into the foundation wall, minimum of 12"form corners of From corners of foundation and a maximum 6'o.c. between bolts. (Section 2305.17)					
<ol> <li>Precaution must be taken to protect concrete from freezing.</li> <li>It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is</li> </ol>					
<ul> <li>done to verify that the proper setbacks are maintained.</li> <li>5. Private garages located <u>beneath habitable rooms</u> in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ¼ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)</li> <li>6. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA</li> </ul>					
<ul> <li>National Mechanical Code/1993).</li> <li>Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's</li> </ul>					
building code.					
8. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". (Sections 1021 & 1022.0)					
9. Headroom in habitable space is a minimum of 7'6". (Section 1204.0)					
10. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread. 7" maximum rise. (Section 1014.0)					
11. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8")					
12. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door upproved for emergency current or process. The units must be concrubed from the incide without the use of					
exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as <u>means of egress or rescue</u> they shall have a sill height					

not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)

- 13. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
- 14. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.)
- 15. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.
- 16. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
  - In the immediate vicinity of bedrooms
  - In all bedrooms
  - In each story within a dwelling unit, including basements
  - In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)
- A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
- 18. The Fire Alarm System shall be maintained to NFPA #72 Standard.
- 19. The Sprinkler System shall maintained to NFPA #13 Standard.
- 20. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
- 21. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excivate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 22. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
- 23. Ventilation shall meet the requirements of Chapter 12 Sections 1210. Of the City's Building Code. (crawl spaces & attics)
- 24. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade.
- 25. All requirements must be met before a final Certificate of Occupancy is issued.
- 26. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National Building Code/1996).
- 27. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)

Please-read and implement the attached Land Use-Zoning report requirements. 28. erni For signage 15 reguire 29. Servic **X** 30. 20 mm 1 ranind 31. 32. ۰. **Building** Inspector cc: Lt. McDougall, PFD

Marge Schmuckal

PSH 6-28-98

#### THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE

#### PERMIT IS ISSUED

## **Building or Use Permit Pre-Application**

#### Additions/Alterations/Accessory Structures

#### **To Detached Single Family Dwelling**

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE\*\*If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Address of Construction: 203 UAI	ey St Portland MECX	1102	
Tax Assessor's Chart, Block & Lot Number Chart# 064 Block# E Lot# 002	UNITE COMPASS	Telephone#: ZCT - TTA -2	189
Owner's Address 12AStroct, Porthand MECHICZ	Lessee Buyer's Name (If Applicable)	Cost Of Work: <b>\$</b> w1/4	Fee \$25
Proposed Project Description:(Please be as specific as possible	)		
Contractor's Name, Address & Telephone	cleaning service	Ræ'd By:	

Separate permits are required for Internal & External Plumbing, HVAC and Electrical installation. All construction must be conducted in compliance with the 1996 B.O.C.A. Building Code as amended by Section 6-Art II.

•All plumbing must be conducted in compliance with the State of Maine Plumbing Code. •All Electrical Installation must comply with the 1996 National Electrical Code as amended by Section 6-Art III. •HVAC(Heating, Ventilation and Air Conditioning) installation must comply with the 1993 BOCA Mechanical Code.

You must Include the following with you application:

## TA Copy of Your Deed or Purchase and Safe Agreement

2) A Copy of your Construction Contract, if available of Building INSPECTION TTY OF PORTLAND, ME

### 3) A Plot Plan (Sample Attached)

If there is expansion to the structure, a complete plot plan (Site Plan) must include

- The shape and dimension of the lot, all existing buildings (if any), the proposed struct property lines. Structures include decks porches, a bow windows cantilever sections a f overhangs. pools, garages and any other accessory structures.
- Scale and required zoning district setbacks

## 4) Building Plans (Sample Attached)

A complete set of construction drawings showing all of the following elements of construction:

- Cross Sections w/Framing defails (including porches, decks w/ railings, and accessory structures)
- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnades, chimneys, gas equipment. HVAC equipment (air handling) or other types of work that may require special review must be included.

#### Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.

Signature of applicant: Sim M. Source	Date: &-3-9

Building Permit Fee: \$25.00 for the 1st \$1000.cost plus \$5.00 per \$1.000.00 construction cost thereafter. O:: INSP:CORRESP/MNUGENT/APADSFD.WPD