City of Portland, Maine – Buildin	g or Use Permit Applica	tion 389 Congress	s Street,	04101, 1el: (207) 8	8/4-8/03, FAX: 8/4-8/16
Location of Construction:	Owner:	,	Phone:		Permit No: 9 9 0 0 4 5
Owner Address:	Lessee/Buyer's Name:	Phone:	Busines	ssName:	
Contractor Name:	Address:	Phor	Phone:		Fermat GRANT ISSUED
Past Use:	Proposed Use:	COST OF WOR	RK:	PERMIT FEE:	JAN 2 0 1999
		FIRE DEPT. □	Approved Denied	\$ INSPECTION: Use Group: Type:	CITY OF PORTLAND
Proposed Project Description:		Signature:	A CTIVITI	Signature:	Zoning Approval:
And the Control of th		PEDESTRIAN ACTIVITIES DIS Action: Approved Approved with Co Denied		with Conditions:	Special Zone or Reviews: Shoreland Wetland Flood Zone
Permit Taken By:	Date Applied For:	Signature:		Date:	☐ Subdivision ☐ Site Plan maj ☐minor ☐mm ☐
 This permit application does not preclude the Building permits do not include plumbing, s Building permits are void if work is not starte tion may invalidate a building permit and store 	eptic or electrical work. ed within six (6) months of the date of				□ Variance □ Miscellaneous □ Conditional Use □ Interpretation □ Approved □ Denied
			WI	PERMIT ISSUED TH REQUIREMENTS	Historic Preservation Not in District or Landmark Does Not Require Review Requires Review Action:
I hereby certify that I am the owner of record of the authorized by the owner to make this application if a permit for work described in the application is areas covered by such permit at any reasonable has	as his authorized agent and I agree s issued, I certify that the code office	sed work is authorized by t to conform to all applicab ial's authorized representa	ole laws of thative shall ha	his jurisdiction. In additio	n, Denied
SIGNATURE OF APPLICANT	ADDRESS:	DATE:		PHONE:	
RESPONSIBLE PERSON IN CHARGE OF WOR	K, TITLE			PHONE:	CEO DISTRICT
	ermit Desk Green-Assessor's	Canary-D.P.W. Pink-P	ublic File		OLO DISTRICT

Inspection Record Type Foundation: Framing: Plumbing: Final: Other:	2-12-99 Talked to hadger kinderson he has ched the Salid had to the the Salid had the Salid had the Salid had the Salid the the the the gadead with the ensembles of the group of a salid when the Report has the Roll to project to the Roll to salid the the salid to the the Roll to salid the salid to should to should to should to should the Roll to salid the Sheathing the Roll to say Report on the documents is sout in the Sheathing the Roll water the Sag Report on the documents is
Date	Cos is the second of the secon

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application Additions/Alterations/Accessory Structures

To Detached Single Family Dwelling

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Address of Construction: 3 CHERRY 57

Tax Assessor's Chart, Block & Lot Number

Chart# 065 Block# A Lot# 007 IONEL POSTOLA CHE 772-1934 X37.

Owner's Address:

Lessee/Buyer's Name (If Applicable)

Cost Of Work: Fee

\$ 5,000 \$45

Proposed Project Description:(Please be as specific as possible)

Proposed Project Description:(Please be as specific as possible)

Telephone#:

Cost Of Work: Fee

\$ 5,000 \$45

CHANGE 2 ** FLORE TO ADD LIVABLE SPACE

Contractor's Name, Address & Telephone

OY/O Y Rec'd By:

IONEL POSTOLA CHE P.O.BOX 1319 TEL: 772-1934 X382

Separate permits are required for Internal & External Plumbing, HVAC and Electrical installation.

•All construction must be conducted in compliance with the 1996 B.O.C.A. Building Code as amended by Section 6-Art II.
•All plumbing must be conducted in compliance with the State of Maine Plumbing Code.

•All Electrical Installation must comply with the 1996 National Electrical Code as amended by Section 6-Art III.
•HVAC(Heating, Ventilation and Air Conditioning) installation must comply with the 1993 BOCA Mechanical Code.
You must Include the following with you application:

A Copy of Your Deed or Purchase and Sale Agreement
 A Copy of your Construction Contract, if available

3) A Plot Plan (Sample Attached)

If there is expansion to the structure, a complete plot plan (Site Plan) must include:

The shape and dimension of the lot, all existing buildings (if any), the proposed structure and the composed structure and the co

Scale and required zoning district setbacks

4) Building Plans (Sample Attached)

A complete set of construction drawings showing all of the following elements of

- Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)
- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.

Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.

Signature of applicant: Date: 01-05-99

Building Permit Fee: \$25.00 for the 1st \$1000.cost plus \$5.00 per \$1,000.00 construction cost thereafter. O:\INSP\CORRESP\MNUGENT\APADSFD.WPD

5 1999

LAND USE - ZONING REPORT

201 200 1/19/99
ADDRESS: 3 Cherry of DATE: 1/19/99
REASON FOR PERMIT: Construct SMAJE in menor renovations
BUILDING OWNER: I arel Postolache C-B-L: 65-A-7
PERMIT APPLICANT: Owner
APPROVED: With conditional DENIED:
45#9 #9 # (O)
CONDITION(S) OF APPROVAL
1. During its existence, all aspects of the Home Occupation criteria, Section 14-410, shall be maintained.
2. The footprint of the existing shall not be increased during maintenance
reconstruction.
3. All the conditions placed on the original, previously approved, permit issued on are still in effect for this amendment.
4. Your present structure is legally nonconforming as to rear and side setbacks. If you were
to demolish the building on your own volition, you will not be able to maintain these same
setbacks. Instead you would need to meet the zoning setbacks set forth in today's
ordinances. In order to preserve these legally non-conforming setbacks, you may only rebuild the in place and in phases.
This property shall remain a single family dwelling. Any change of use shall require a
separate permit application for review and approval.
6. Our records indicate that this property has a legal use of units. Any change
in this approved use shall require a separate permit application for review and approval.
7. Separate permits shall be required for any signage. Separate permits shall be required for future decks, sheds, pool(s), and/or garage.
Separate permits shall be required for future decks, sheds, pool(s), and/or garage. This is <u>not</u> an approval for an additional dwelling unit. You <u>shall not</u> add any additional
kitchen equipment, such as stoves, microwaves, refrigerators, or kitchen sinks, etc.
without special approvals.
10.) Other requirements of condition this proval is based upon the
Complation of The deal to purchase The PINP propert
At 65-A-9 (in part) a order to give This New garas
Proper Street riccess,
Marge Schmuckal, Zoning Administrator
City of Portland

BUILDING PERMIT REPORT
DATE: 20 January 1999 ADDRESS: 3 Cherry ST. CBL 65-A-60
REASON FOR PERMIT: 10 CONSTRUCT GTached garage Interior Resour Tions
BUILDING OWNER: JONE POSTOLACKE
CONTRACTOR:
PERMIT APPLICANT:
USE GROUP β -3 (U) BOCA 1996 CONSTRUCTION TYPE β
CONDITION(S) OF APPROVAL
This Permit is being issued with the understanding that the following conditions are met:
Approved with the following conditions: $\frac{1}{12}$, $\frac{2}{2}$, $\frac{5}{2}$, \frac
1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
 Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be
obtained. (A 24 hour notice is required prior to inspection)
2.5 Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more
than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside
edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the
floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with
an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be
higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6"
of the same material. Section 1813.5.2
2.6 Foundations anchors shall be a minimum of 1/2" in diameter, 7" into the foundation wall, minimum of 12" from corners of
foundation and a maximum 6 'o.c. between bolts. (Section 2305.17)
Precaution must be taken to protect concrete from freezing. Section 1908.0
4. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to
verify that the proper setbacks are maintained.
Private garages located <u>beneath habitable rooms</u> in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from
adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting
rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior
spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board
or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National
Mechanical Code/1993). Chapter 12 & NFPA 211 Sound transmission control in posidortial building shall be done in constant with Chapter 12 postion 1214 0 of the city's
Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's building code.
. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking
surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum
height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and
public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a
diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.
(Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".)
Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". (Sections
1021 & 1022.0) - Handrails shall be on both sides of stairway. (Section 1014.7)
Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum
'11" tread. 7" maximum rise.(Section 1014.0)
The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4

Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special

L2.

knowledge or separate tools. Where windows are provided as means of excess or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)

- Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it 13. exits directly from the apartment to the building exterior with no communications to other apartment units. Section 1010.1
- All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self 14. closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) Section 710.0
- The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing 15. automatic extinguishment. Table 302.1.1
- All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the **₩**6. provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2

- 17. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. Section 921.0
- The Fire Alarm System shall be maintained to NFPA #72 Standard. 18.
- The Sprinkler System shall maintained to NFPA #13 Standard. 19.
- All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 20. 1024. Of the City's building code. (The BOCA National Building Code/1996)
- Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate 21. or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a 22. certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
- Ventilation shall meet the requirements of Chapter 12 Sections 1210. Of the City's Building Code. (crawl spaces & attics) 23.
- All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls <u>X</u>24. until all electrical (min. 72 hours notice) and plumbing inspections have been done.
- <u>X</u>25. All requirements must be met before a final Certificate of Occupancy is issued.
- All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National <u>L</u> 26. Building Code/1996).
- <u>L</u> 27. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)
- Please read and implement the attached Land Use-Zoning report requirements.
- Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.3. of the City's building code.

£30. Glass and glazing shall meet the requirements of Chapter 24 of the building code.

Setone any roof work is started. This office is requiring a structu ¥ 31. Analysis of all work complete and proposed work-This work must be done by a professional structural engineer. I know you have been working with Associated Design Partners Inc. and They are aware of my concern on your project. 32.

33.

Hoffses, Building Inspector

cc: Lt. McDougall, PFD

Marge Schmuckal, Zoning Administrator

PSH 8-1-98

Tom Johns Plan No Permet. ? ROOF RAFTER 3 CHERRY ST: 2'X 10" HEABER 2" X4" FRAME WALL GARAGE DETAIL 2" x 6" BOLTED IN CONCRETE CROSS SECTION 2" x8" X10' PINE 1/2" PLY WOOD ASPHAUT SHINGLES CONCR. PILLAR - SUPPORT BEAM CONCRETE SANDWICH ": 2"x6"+ 6" I BEAM +2"x6" PINE SUPPORT PILLAR BACK GARAGE \ DOOR 9'X7' J'X81/8PINE PITCH: Ng 2" x4" OPTIONAL: CONCRETE 30"x78" DOOR 21/x 4" FRAME WALL 1/2" PLYWOOD -VINIL SIDING IN THE BACK - WOOD SIDING PATIO LEVEL IN FRONT I' REINFORLED CONCRETE PAD