City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

Location of Construction: 312 St John St	Owner: Reali, Dom	ninic	Phone:	Permit No9 7 0 8 2 4
Owner Address: Ameri	Lessee/Buyer's Name: can Cash Express	Phone:	BusinessName:	PERMIT ISSUED
Contractor Name: Great Falls Builders		Phone:	839-7008	Flermic Issued:
Past Use:	Proposed Use:	COST OF WORK \$ 40,000.00	\$ 225.00	
Vacant Space	Office Check Cashing	FIRE DEPT. ☑ A		CITY OF PORTLAND
Proposed Project Description:	Check Cashing		INT Signature:	Zone: CBL: 065-A-011 Zoning Approval: 7
Proposed Project Description.		Action: A	TIVITIES DISTRICT (P.A.D.) pproved	Special Zone or Reviews:
Change Use/Make Interior	Renovations		pproved with Conditions: enied	Shoreland Sap Permits Wetland Flood Zone (eq. 6)
Permit Taken By:	Date Applied For:	Signature:	Date:	□ Subdivision School School Site Plan maj □ minor □ mm □
Mary Gresik	Date Applied For.	25 July 1997		Zoning Appeal
 Building permits do not include plumbing, s Building permits are void if work is not starte tion may invalidate a building permit and sto 	d within six (6) months of the date of	issuance. False informa-		☐ Miscellaneous ☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied
Call 739-	Tex Pla	્,૦,		Historic Preservation □ Not in District or Landmark □ Does Not Require Review □ Requires Review Action:
I hereby certify that I am the owner of record of the authorized by the owner to make this application if a permit for work described in the application is areas covered by such permit at any reasonable h	as his authorized agent and I agree to s issued, I certify that the code officia	conform to all applicable I's authorized representativ	laws of this jurisdiction. In additi e shall have the authority to enter	ion, Denied /
SIGNAPORE OF APPLICANT John Smith	ADDRESS:	25 July DATE:	1997 PHONE:	- la-
RESPONSIBLE PERSON IN CHARGE OF WOR	K, TITLE		PHONE:	CEO DISTRICT
White-P	ermit Desk Green-Assessor's C	anary-D.P.W. Pink-Pub	lic File Ivory Card-Inspector	D. Jodan

COMMENTS

8-1-97-5-21 Min - For foots in undelle area one tobe	
ine colud-	
8/25/97 - Need to add some exit signs, fire exting visher	ζ
8/25/97 - Need to add some exit signs, fire exting visher. 4 seal some fire penetrations - Lt. plac checking but 4 this p.m Appears to be done per plans -	ck
This p.m Appears to be done per plans -	

		mspection Record	
	Type		Date
Foundation: _			

CITY OF PORTLAND, MAINE



Department of Building Inspection

Certificate of Occupancy

· A	LO	OCATION 311 Dr 46	ib 1 51 (0 6 5 -6~0) 1 ;	
Issued to	omit is helds	Da	ate of Issue	
This is t	o certify that the building,	premises, or part thereof,	at the above location, built — aftere	d
 changed as t substantially to occupancy or u 	o use under Building Permit N	o. 97004 , has had final nance and Building Code olicated below.	l inspection, has been found to conform of the City, and is hereby approved for APPROVED OCCUPANCY	n
\$^ 1	rat Pacci/Hi h it Front		Oltica - chack cashlag#	
Limiting Condit	cions:			
This certificate certificate issue			·	, ,
Approved:			· · · · · · · · · · · · · · · · · · ·	/
(Date)	Inspector		Inspector of Baildings	d_

Notice: This certificate identifies lawful use of building or premises, and ought to be transferred from owner to owner when property changes hands. Copy will be furnished to owner or lessee for one dollar.

BUILDING PERMIT REPORT

DATE:	7/29/97	ADD	ress: <i>3</i>	12 St John	5		
REASON FOR I	PERMIT:	conduction					
BUILDING OW	ner: D.	Reali					
CONTRACTOR	: Gre	+ Fills Build	he-				
PERMIT APPL	CANT: Joh	2 Smith	_APPROVAL:	x/ 44 × 1.	2 ×18	A 26	<u>-</u>
				1 9	/		

CONDITION(S) OF APPROVAL

This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.

- 2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)
- 3. Precaution must be taken to protect concrete from freezing.
- 4. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
- 6. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993) U.L. 103.
- 7. Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's building code.
- 8. Guardrail & Handrails A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.
- 9. Headroom in habitable space is a minimum of 7'6".
- 10. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread. 7" maximum rise.
- 11. The minimum headroom in all parts of a stairway shall not be less than 80 inches.
- 12. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.
- Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.

 All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's.
- 15. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.
- All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and

	I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)
(17.)	A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of a approved type.
(18)	The Fire Alarm System shall be maintained to NFPA #72 Standard.
19.	The Sprinkler System shall maintained to NFPA #13 Standard.
20.	All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
21.	All construction and demolition debris must be disposed at the City's authorized reclamation site. The fee rate is attached. Proof of such disposal must be furnished to the office of Inspection Services before final Certificate of Occupancy is issued or demolition permit is granted.
22.	Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
23.	The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
24.	This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's office.
_. 25.	Ventilation shall meet the requirements of Chapter 12 Sections 1210. of the City's Building Code.
X26 .	All electrical and plumbing permits must be obtained by a Master Licensed holders of their trade.
27.	
28.	
20	
29.	$\frac{\partial}{\partial x} \frac{\partial}{\partial x} \frac{\partial}$
(10/c/m	el Hopses Chief of Code Enforcement
الله المراجع	color biology Chica of Code Emoleciment
cc: Lt.	McDougall, PFD
	ge Schmuckal
14.	y Mc Oause
VI	· · · · · · · · · · · · · · · · · · ·

SBITILIDAR BOR MR SS: +0 Te-TS-NUT

St Joh Street

SPECIFICATIONS

- 1 Frame partitions as required from floor to floor on common wall
 -Security wall will have a barricade from top of wall to bottom of floor above
- 2 Install 1/2 gypsum board on new partitions
- 3 Install security wall as specified by plans
- 4 Install wainscotting, cap rail, and base on security wall and out to the exterior wall 36'+-
- 5 Install HVAC diffusers to A.C.E. and one to back unit
- 6 Install carpet/vct in A.C.E. as specified, paint concrete in back hall, back unit to remain as is
- 7 Ceiling to be installed as specified in A.C.E. and standard in back unit
- 8 3 mailbox units will be installed (units supplied by owner)
 (Recommended location was as far away from tellers as possible for security because the mailbox units are not bullet proof)
- 9 Plumbing in second bath will be completed
- 10 Phone system will be done by owner
- 11 Electrical as required in A.C.E. minimum lighting in back unit
- 12 Painting will be as specified in A.C.E. prime exposed gypsum board in back unit no exterior paint required
- 13 Security system including power to electric strikes will be by owner
- 14 All doors will be solid core 1 3/4" birch in steel jamb except rear exit from A.C.E. to be steel door in steel jamb. All doors will be dressed as specified.
- 15 All cabinets and counters will be as specified for A.C.E.