



SECOND FLOOR FRAMING PLAN

1. SEE SHEET S-1.0 FOR GENERAL STRUCTURAL NOTES

LEVEL	SHEATHING	HOLDOWNS
FIRST FLOOR	7/16" OSB ON BOTH SIDES OF WALL FASTENED W/ 8d @ 3" O.C.	HDU8-SDS2.5 W/ 7/8" Ø THRU BOLT
SECOND FLOOR	7/16" OSB ON BOTH SIDES OF WALL FASTENED W/ 8d @ 4" O.C.	MSTC66 EACH FAC EACH END
THIRD FLOOR	7/16" OSB ON ONE SIDE OF WALL FASTENED W/ 8d @ 4" O.C.	MSTC40 EACH FAC EACH END

NUMBER OF WOOD STUDS IN POST BELOW COLUMN ABOVE THIS LEVEL COLUMN CONTINUOUS THROUGH THIS LEVEL → TRUSS OR JOIST BEARING FLUSH FRAMED JOIST BEARING WITH HANGER WOOD STUD BEARING WALL BELOW SHEAR WALL, SEE SCHEDULE -TYP EXISTING FRAMING MEMBER

WOOD POST

NEW FRAMING MEMBER NUMBER OF TRIM STUDS UNDER HEADER NUMBER OF KING STUDS ADJACENT TO HEADER Stabilization/ Fire Damage Repairs
Park Ave
Portland, ME 04101