City of Portland, Maine	- Building or Use Permit Application	389 Congress Street, 04101, Tel	: (207) 874-8703, FAX: 874-8716
-------------------------	--------------------------------------	---------------------------------	---------------------------------

Location of Construction:	Owner: G.L. Smally		Phone:	Permit No:
Owner Address:	Lessee/Buyer's Name:	Phone:	BusinessName:	88115
Contractor Name:	Address: 7 Thomas Drive, Westbrook	Phone:	PERMIT ISSUED	
Past Use:	Proposed Use:	COST OF WORK: \$ 8940.00	PERMIT FEE: \$ 65.00	e OCT 9 19em
	NVAC Unit dept.	FIRE DEPT. AI		POITI OF PORTLAND
Proposed Project Description:			TIVITIES DISTRICT (P.A.D.)	Zoning Approval 65-6-1
HVAC Unit Dept.		A	pproved with Conditions:	 Special Zone or Reviews: □ Shoreland □ Wetland □ Flood Zone
		Signature:	Date:	
Permit Taken By:	Date Applied For:			□Site Plan maj □minor □mm □
 Building permits do not include plumbing, septic or electrical work. Building permits are void if work is not started within six (6) months of the date of issuance. False information may invalidate a building permit and stop all work 				☐ Miscellaneous ☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied
		WITH	PERMIT ISSUED REQUIREMENTS	Historic Preservation
authorized by the owner to make this appli if a permit for work described in the applic	CERTIFICATION rd of the named property, or that the proposed w cation as his authorized agent and I agree to c ation is issued, I certify that the code official's nable hour to enforce the provisions of the cod	onform to all applicable l authorized representative e(s) applicable to such pe	aws of this jurisdiction. In addition shall have the authority to enter a	n, Denied
	10/	7/9B		
SIGNATURE OF APPLICANT	ADDRESS:	DATE:	PHONE:	
RESPONSIBLE PERSON IN CHARGE OF	WORK, TITLE		PHONE:	
W	hite-Permit Desk Green-Assessor's Car	ary-D.P.W. Pink-Publ	c File Ivory Card-Inspector	

Volet Wen unit is lighter then alil unit dalled with Doug. He will call when unit is installed Au And this twentes less the old with 1498 for ver mit ok 16198 New mit installed close out me

Insp	ection	Record
------	--------	--------

Туре	Date
oundation:	
raming:	
lumbing:	
inal:	
Other:	

Additions/Alterations/Accessory Structures

To Detached Single Family Dwelling

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

Location/Address of Construction: VERMONT TRANSIT - 950 Congress St. Portand

Tax Assessor's Chart, Block & Lot Number Chart# 065 Block# G Lot# 00	Owner: GEREALTY	Telephone#:		
Owner's Address,	Lessee/Buyer's Name (If Applicable)		Cost Of Work: Fee \$ 8,940.00 \$65	
Proposed Project Description: (Please be as specific as possible) HVAC UNIT REPLACEMENT				
Contractor's Name, Address & Telephone AVERY SERVICES INC. 7th	omas Drives Westbeach, Me	Rec'd By:	S	

Separate permits are required for Internal & External Plumbing, HVAC and Electrical installation. •All construction must be conducted in compliance with the 1996 B.O.C.A. Building Code as amended by Section 6-Art II. •All plumbing must be conducted in compliance with the State of Maine Plumbing Code.

•All Electrical Installation must comply with the 1996 National Electrical Code as amended by Section 6-Art III. •HVAC(Heating, Ventilation and Air Conditioning) installation must comply with the 1993 BOCA Mechanical Code. You must Include the following with you application:

1) A Copy of Your Deed or Purchase and Sale Agreement 2) A Copy of your Construction Contract, if available Cry of PORTLAND, ME

1:1

3) A Plot Plan (Sample Attached)

If there is expansion to the structure, a complete plot plan (Site Plan) must include

- The shape and dimension of the lot, all existing buildings (if any), the proposed structure and the distance from the actual property lines. Structures include decks porches, a bow windows cantilever sections and roof overhangs, as well as, sheds, pools, garages and any other accessory structures.
- Scale and required zoning district setbacks

4) Building Plans (Sample Attached)

A complete set of construction drawings showing all of the following elements of construction:

- Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)
- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and dampproofing
- Flectrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas
 equipment. HVAC equipment (air handling) or other types of work that may require special review must be included.

Certification


I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued. I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.


Date:

Signature of applicant:

wee

· · · · · · · · · · · · · · · · · · ·			6		
	Brop	psąl	, øge v	<u> </u>	1
H 865377 AVERY WESTBR (2) FAX	SERVIC	CES, INC.			
7 WESTER	Thomas D	rive			
	ROOK, MAI	687			
FAX	(207) 874	-0933			
PROPOSAL SUBMITTED TO		-CHE 772-6	587	DATE	
STREET V27MONE TAANSEL CO., Inc./Lou Parada		Fax# 871-13	42	9/28/	98
950 CONDACSS STAZZE		Reofter Uni	1 Replacem	ent	
CITY STATE AND ZIP CODE Portland, ME 04102	1	18 LOCATION 750 Congres	St - Po	atland b	NF
ARCHIVECT DATE OF PLANS		-			JOB PHONE
We hereby submit specifications and estimates for	1	DOUG AVERY			
Avery Services, Inc. is pleased to quote Carrier gas/elec. rooftop unit. Scope o				ment of y	your excisting
2		-			
Removal & desposal of the existing rocht Install an adapter curb onto the existin	tep unit	as per cra	caus.		
Supply & install a 7.5 ton Carrier g	gas/elec.	rooftop	unat with	zconomiz	zer onto the
adapter curb. Supply & install a new Carrier non-pro	ouranmab	le thermos	tat, the h	nto exis	sting control
wining.					
The new unit into existing services, it: Start-up & check system operation.			e wereny,	yas pipi	ngı.
I Year warranty by manufacturer & Avery	Services	s, Inc.			
-NOTE: Maintenance contracts are available option.	li, plia	se contact	me, if you	s wesh to	o pursue that
	power u	viring, ad	equacy of	existi	ing systems,
maintenance contract.					
理r Propose hereby to furnish material and lat	bor - oom	plete in accord	ance with abo	ve specifica	tions, lot the sum of
Eight Thousand Nine Hundred Forty **	*******	********		oilars (\$ 8,9	
Paymentito be made as todows 258 Upon acceptance - Progress billes	nalnat 1	0 days - R			
If payment is not made as outlined above, e service charge					
collection, including attorney's fees will be paid.		/			2.19
All meterial is guaranteed to be as specified all work to be completed in a with menner scearching to all and and precises. Any statistical or deviation (rom above ap involving satis costs will be executed only upon written orders and will become any any and any statistical and will become approximate and any upon written orders. Any statistical and written orders. The approximate any upon written orders and written and any statistical any	Decisicationa	Authorized Signature	prafu	di-	61 leary
charge near and above the astimate ari egreements contingent upon strikes or delays beyond our control. Owner to carry fire tomado and other necessan	Accidents	Note Tr windrawn by us a	noi accepted with		d JRY6
Our workers are furly covered by Workman's Compensation Insurance					
Acceptance of Broposal - The above prices spe		, A.	~ · · · ~	(Fr	to An
and collations are valistacions and one nervols accepted you are . to do the work as specified agrimment with be made as outlined abo	authorided (Ove	Signature		~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	aluginete
Date of Acceptance 9-30-98		Signature			
	Te Recri		· •		





BUILDING PERMIT REPORT

	DATE:	<u>BOCT98</u> ADDRESS: <u>950 Congress ST</u> CBL <u>\$65-6-\$\$</u> ON FOR PERMIT: <u>Replace HVAC UNIT Dept</u> .			
	REAS	DNFORPERMIT: REPLACE HVAC UNIT DEDT.			
BUILDING OWNER: G.L. ReaLTY					
	CONT	ning owner: G.L. RealTy ractor: Allery Services			
	PERM	IT APPLICANT: //			
USE GROUP BOCA 1996 CONSTRUCTION TYPE					
		CONDITION(S) OF APPROVAL			
	This P	ermit is being issued with the understanding that the following conditions are met:			
		X1 X21			
	Approv	wed with the following conditions: $\frac{X}{4}\frac{3}{3}$			
Х	1.	This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.			
	2.	Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services			
		must be obtained. (A 24 hour notice is required prior to inspection)			
	2.5	Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing			
		not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches			
		beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the			
		bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The			
		top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used,			
		the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or			
		crushed stone, and shall be covered with not less than 6" of the same inaterial. Section 1813.5.2			
	2.6	Foundations anchors shall be a minimum of 1/2" in diameter, 7" into the foundation wall, minimum of 12" from corners of			
		foundation and a maximum 6 'o.c. between bolts. (Section 2305.17)			
	3.	Precaution must be taken to protect concrete from freezing. Section 1908.0			
	4.	It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is			
		done to verify that the proper setbacks are maintained.			
	5.	Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from			
		adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire			
		resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from			
		the interior spaces and the attic area by means of $\frac{1}{2}$ inch gypsum board or the equivalent applied to the garage means of $\frac{1}{2}$ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)			
	6.	All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA			
	0.	National Mechanical Code/1993). Chapter 12 & NFPA 211			
	7	Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's			
		building code.			
	8.	Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated			
		walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower			
		level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A. B, H-4, I-			
		1. I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such			
		that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be			
		less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at			
		least 1 1/4" and not greater than 2" (Sections 1021 & 1022.0) - Handrails shall be on both sides of stairway. (Section			
		1014.7)			
	9.	Headroom in habitable space is a minimum of 7'6". (Section 1204.0)			
	10.	Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group			
		minimum 11" tread. 7" maximum rise.(Section 1014.0)			

11 The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6' 8") 1014.4

- 12. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as <u>means of egress or rescue</u> they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)
- Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. Section 1010.1
- 14. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) Section 710.0
- 15. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment. Table 302.1.1
- 16. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Sinoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2

- 17. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. Section 921.0
- 18. The Fire Alarm System shall be maintained to NFPA #72 Standard.
- 19. The Sprinkler System shall maintained to NFPA #13 Standard.
- 20. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
- 21 Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year"
- 22. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
- 23. Ventilation shall meet the requirements of Chapter 12 Sections 1210. Of the City's Building Code. (crawl spaces & attics)
- 24. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade.
- 25. All requirements must be met before a final Certificate of Occupancy is issued.
- 26. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National Building Code/1996).
- 27. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)
- 28. Please read and implement the attached Land Use-Zoning report requirements.
- 29. Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.3. of the City's building code.
- 30. Glass and glazing shall meet the requirements of Chapter 24 of the building code.

I under stand that This is a replacement unit. If The weigh increases with the New Unit, a structural analysis should A31. be done of The roof system To varity The rook system Can 22 The New Load -Carry

33.

S Building Inspector

cc: Lt. McDougall, PFD Marge Schmuckal, Zoning Administrator