City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Location of Construction: Owner: Phone: Permit No: 871-2447 930 Congress Street Maine Medical Center Lessee/Buyer's Name: Owner Address: Phone: BusinessName: Street 04101 Permit Issued Address: Phone: Contractor Name: Gus Doughty ## 248 Warren Ave Portland ME *** COST OF WORK: PERMIT FEE: Proposed Use: Past Use: \$ 234,00 \$ 34,928,00 FIRE DEPT. Approved INSPECTION: Medical SAMO ☐ Denied Use Group: Type: Zone: | CBL; Signature: Signature: Zoning Approval: Proposed Project Description: PEDESTRIAN ACTIVITIES DISTRICT (P.A.D.) Action: Approved Onterior renovations to sleep lab on third fdoor Special Zone or Reviews Approved with Conditions: ☐ Shoreland Denied □ Wetland ☐ Flood Zone ☐ Subdivision Signature: Date: ☐ Site Plan mai ☐minor ☐mm ☐ Permit Taken By: Date Applied For: Dec. 28 1999 K Zoning Appeal □ Variance This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. ☐ Miscellaneous Building permits do not include plumbing, septic or electrical work. ☐ Conditional Use Building permits are void if work is not started within six (6) months of the date of issuance. False informa-□Interpretation ☐ Approved tion may invalidate a building permit and stop all work... ☐ Denied Historic Preservation Not in District or Landmark ☐ Does Not Require Review ☐ Requires Review WITH REQUIREMENTS Action: CERTIFICATION ☐ Appoved ☐ Approved with Conditions I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been ☐ Denied authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all Date: areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit Dec. 28 1999 PERMIT ISSUED SIGNATURE OF APPLICANT ADDRESS: DATE: PHONE: RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE PHONE: CEO DISTRICT

White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

	BUILDING PERMIT REPORT									
1	DATE: 29-DEC99 ADDRESS: 930 Congress ST. CBL: 065-H-002									
F	REASON FOR PERMIT: InTerior renovations To Sleep Lab									
H	BUILDING OWNER: MAINE Medical Center									
	PERMIT APPLICANT: /CONTRACTOR Gus Doughty									
τ	USE GROUP: T-2 CONSTRUCTION TYPE: CONSTRUCTION COST: 34,978.0 PERMIT FEES: 4234.0									
	he City's Adopted Building Code (The BOCA National Building code/1996 with City Amendments) he City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)									
	CONDITION(S) OF APPROVAL									
T	his permit is being issued with the understanding that the following conditions are met: */ *20 *21 *22 *23 *27 *27 *36,									
X 1.	This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.									
2.										
	24 hour notice is required prior to inspection) "ALL LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING."									
3.										
	percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not									
	less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain									
	tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations									
	shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and									
	shall be covered with not less than 6". of the same material. Section 1813.5.2									
4.	Foundations anchors shall be a minimum of 1/2" in diameter, T' into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' O.C. between bolts. Section 2305.17									
5.	and the second of the second o									
6.	Precaution must be taken to protect concrete from freezing. Section 1908.0									
7.										
8.	proper setbacks are maintained. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior									
0.	spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached									
	side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch									
	gypsum board or the equivalent applied to the garage means of 1.2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4,									
0	Section 407.0 of the BOCA/1996) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical									
9.	Code/1993). Chapter 12 & NFPA 211									
10.	Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.									
11.	Guardrails & Handrails: A guardrail system is a system of building components located near the of pen sides of elevated walking surfaces for									
	the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42",									
	except Use Group R which is 36". In occupancies in Use Group A.B.H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall									
	not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3									
	shall not be less than 30", but not more than 38"). Handrail grip size shall have a circular cross section with an outside diameter of at least 1 %									
	and not greater than 2". (Sections 1021 & 1022.0). Handrails shall be on both sides of stairway. (Section 1014.7)									
12.	Headroom in habitable space is a minimum of 7'6'. (Section 1204.0) Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 %" maximum rise. All other Use Group minimum 11" tread,									
13.	7" maximum rise. (Section 1014.0)									
14.	The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4 (3'14) 3 3 3 4 4 3 3 3 4 3 3 3 3 3 3 3 3 3 3									
15.	Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door									
	approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All									
	egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum									
	net clear opening width dimension shall be 20 inches (508)mm, and a minimum net clear opening of 5.7 sq. ft. (Section 1010.4)									
16.	Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly									
	from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)									
17.	All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's.									
10	(Over 3 stories in height requirements for fire rating is two (2) hours. (Section 710.0) The boiler shall be protected by enclosing with (1) hour fire rated construction including fire doors and ceiling, or by providing automatic									
10.	The coner shall be protected by character and character an									

extinguishment. (Table 302.1.1)

also

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application

Attached Single Family Dwellings/Two-Family Dwelling

Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Addressof Construction (include Portion of Building): 930 Congress ST. MMC								
Total Square Footage of Proposed Structure 3200		Square Footage of Lot						
Tax Assessor's Chart, Block & Lot Number	Owner		Telephone#					
Chart# () (65 Block# H Lot# CO)	MAINE	Merical Center	871-a	7447				
Owner's Address: 22 Bramhall ST. Portland, Me.	Lessec/Buyer's N	ame (If Applicable)	Cost Of Work: \$ 34928	Fee DI (0				
portiona, me.			\$ 34,448	034.00				
Proposed Project Description: (Please be as specific as possible) Renovate a small area of the third floor which is the Sleep Lab.								
Ca Dandala								
Contractor's Name, Address & Telephone Rec'd By Rec'd By Rec'd By								
Current Use: Nedicar		Proposed Use: Sam	e					

Separate permits are required for Internal & External Plumbing, HVAC and Electrical installation.

- •All construction must be conducted in compliance with the 1996 B.O.C.A. Building Code as amended by Section 6-Art II.
 •All plumbing must be conducted in compliance with the State of Maine Plumbing Code.
 - •All Electrical Installation must comply with the 1996 National Electrical Code as amended by Section 6-Art III.
- •HVAC(Heating, Ventililation and Air Conditioning) installation must comply with the 1993 BOCA Mechanical Code. You must Include the following with you application:
 - 1) ACopy of Your Deed or Purchase and Sale Agreement
 - 2) A Copy of your Construction Contract, if available

3) A Plot Plan/Site Plan

Minor or Major site plan review will be required for the above proposed projects. The attached checklist outlines the minimum standards for a site plan.

4) Building Plans

Unless exempted by State Law, construction documents must be designed by a registered design professional.

A complete set of construction drawings showing all of the following elements of construction:

- Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)
- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas
 equipment, ITVAC equipment (air handling) or other types of work that may require special review must be included.

Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.

Signature of applicant:	Sel Dayly	Date: /2/28/99	

Building Permit Fee: \$00.00 for the 1st \$1000.cost plus \$6.00 per \$1,000.00 construction cost thereafter.

Additional Site review and related fees are attached on a separate addendum