City of Portland,		_			<u> </u>	mit No: 01-1031	Issue Date:		CBL:	
389 Congress Street,	04101 Tel:	<u> </u>	, Fax:	(207) 874-871			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		066A B	024001
Location of Construction: Owner Name:				Owner Address:			Phone:			
		Ayer Nancy I			33 Roberts St # 2			207-772-5277		
			Contractor Name:		Contractor Address:			Phone		
		Adams, Craig	g S.		RR1 Box 312 Naples			2076933535		
Lessee/Buyer's Name Phone:					1			Zone:		
n/a		n/a			Alterations - Dwellings			<u> </u>		
Past Use:		Proposed Use:			Permit Fee: Cost of Work:			.: (CEO District:	
Multi Fam/ 3 Units Same: Replace			e Front Stairs/Porch		\$30.00 \$950.00					
					FIRE	DEPT:	Approved Denied	INSPEC Use Gro	TION:	Type: 5 0
			٠,	3.5		<u> </u>	Demod		TISSUED,	GE.
		3 legal w	its p	a madic	e,			HOW	XX XX ENER	1991
Proposed Project Descript		U	•	•	a			MAD		11111
Replace Front Stairs/F	Porch				Signat PEDE	STRIAN ACTI		Signale RICI (I	A.D.)	MA
					Action	n: Approv	ed App	roved w/0	Conditions	Defied
		ų-			Signat	ture:			Date:	
Permit Taken By: cih	- 1	Applied For: 21/2001				Zoning	Approva	1		
<u> </u>			Sne	cial Zone or Revie	WC.	Zonin	g Appeal	$\overline{}$	Historic Pre	servotion
1. This permit appli		•			W3	l			1	
Applicant(s) from meeting applicable State Federal Rules.		icable State and	☐ Shoreland		Variance			Not in District or Landma		
2. Building permits do not include plumbing, septic or electrical work.		Wetland		Miscellaneous			Does Not Require Review			
3. Building permits are void if work is not started within six (6) months of the date of issuance. False information may invalidate a building permit and stop all work			Flood Zone			Conditional Use			Requires Review	
			Subdivision		Interpretation			Approved		
			☐ Si	te Plan		Approve	d		Approved w	/Conditions
			Maj Minor MM			Denied			Denied	
			DC	Kw45	" · C	Data				
			Date:	consider	<u>~~</u>	Date:		Da		$\overline{}$
			`	~ 5 8/2	8/0/			WI ⁷	PERMIT ISS TH REQUIR	SUED EMENTS
			(CERTIFICATION	ON					
I hereby certify that I a	m the owner o	of record of the na	med pro	operty, or that th	e pror	oosed work is	authorized	by the c	owner of reco	rd and tha
I have been authorized	by the owner	to make this appli	cation	as his authorized	l agent	t and I agree t	o conform t	o all ap	plicable laws	of this
jurisdiction. In addition	n, if a permit f	for work described	in the	application is is	sued,	I certify that t	he code offi	cial's a	uthorized rep	resentative
shall have the authority such permit.	to enter all ar	eas covered by su	ich perr	nit at any reasor	iable h	our to enforc	e the provis	ion of t	the code(s) ap	oplicable to
SIGNATURE OF APPLICA	ANT			ADDRESS	 3	<u>.</u>	DATE		PHO)NF.
							2		1110	
RESPONSIBLE PERSON	IN CHARGE OF	WORK TITTE					DATE		DEXC	ME
LENOUIT	CLIM MACOL OI	··· ··································					DAIC		rnu	ONE

DATE

PHONE

All Purpose Building Permit Application

If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

me City, payment attangements that be made before permits of any kind are accepted.					
Location/Address of Construction: 33 Roberts St. Pretland, Me 04102					
Total Square Footage of Proposed Structure Square Footage of Lot					
Tax Assessor's Chart, Block & Lot Owner: Chart# 066 Block#AB Lot# Of Nancy I Ayer 772-527					
Lessee/Buyer's Name (If Applicable) Applicant name, address & Cost Of Work: \$ 750% Croig Adams 4th DNA Buildeu's RELIBOR 312 Naples we CHOSS *63-3535 Fee: \$ 30,00					
Current use: Apartment Building 3 family?					
If the location is currently vacant, what was prior use:					
Approximately how long has it been vacant:					
Proposed use:					
Project description: tearing out old Stone Stairs and metal handralls and replacing them with same size pressure treated stairs. Main Set of STair					
Contractor's name, address & telephone: Craig S. Adams RRI Box 312 Naples, Me 04055 693-3535					
Who should we contact when the permit is ready: Craig S. Adams XX Mailing address: RR 1 Box 312 Naples, Me 04655 Phone: 693-3535					
IF THE REQUIRED INFORMATION IS NOT INCLUDED IN THE SUBMISSIONS THE PERMIT WILL BE AUTOMATICALLY DENIED AT THE DISCRETION OF THE BUILDING/PLANNING DEPARTMENT, WE MAY REQUIRE ADDITIONAL INFORMATION IN ORDER TO APROVE THIS PERMIT.					
I hereby certify that I am the Owner of record of the named property, or that the owner of record authorizes the proposed work and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.					
Signature of applicant: Date: 8/17/01					

This is not a permit, you may not commence ANY work until the permit is issued

	BUILDING PERMIT REPORT
	DATE: 22/AUGUST 200 [ADDRESS: 33 RoberTS STreeT CBL: 066A-0-6-
	REASON FOR PERMIT: Replace From T STAIRS/ Porch
	BUILDING OWNER: NANCY T AJET
	PERMIT APPLICANT: /CONTRACTOR Craig S. Adams
	USE GROUP: A-2 CONSTRUCTION TYPE: 5B CONSTRUCTION COST: 950 6 PERMIT FEES. 30,60
l,	The City's Adopted Building Code (The BOCA National Building Code/1999 with City Amendments) The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)
•	CONDITION(S) OF APPROVAL
	This permit is being issued with the understanding that the following conditions shall be met: 41,413
X	 This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) "ALL LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING."
	3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not

tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2

Foundations anchors shall be a minimum of 1/2" in diameter, 7' into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' O.C. between bolts. Section 2305.17

Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.

6. Precaution must be taken to protect concrete and masonry. Concrete Sections 1908.9-19.8.10/ Masonry Sections 2111.3-2111.4.

It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the

less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain

proper setbacks are maintained.

Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1999)

All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical

Code/1993). Chapter 12 & NFPA 211

10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.

11. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42". In occupancies in Use Group A, B.H-4, I-1, I-2, M, R, public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. Handrails shall be a minimum of 34" but not more than 38". Exception: Handrails that form part of a guard shall have a height not less than 36 inches (914 mm) and not more than 42 inches (1067 mm). Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/2" and not greater than 2". (Sections 1021 & 1022.0). Handrails shall be on both sides of stairway. (Section 1014.7) R-3 (ONE & TWO FAMILY DWELLINGS) GUARD HEIGHT IS 36" MINIMUM.

12. Headroom in habitable space is a minimum of 7'6'. (Section 1204.0)

X 13. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 %" maximum rise. All other Use Group minimum 11" tread, 7' maximum rise. (Section 1014.0) Sel attach (6'8") 1014.4

14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4

15. The Minimum required width of a corridor shall be determined by the most restrictive of the criteria cities section 1011.3 but not less then 36.

16. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508)mm, and a minimum net clear opening of 5.7 sq. ft. (Section 1010.4)

17. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly

from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)

All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closure's. (Over 3 stories in height requirements for fire rating is two (2) hours. (Section 710.0)

The boiler shall be protected by enclosing with (1) hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1) w/mohr prof. A-

- 20. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1999), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements
- 21. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)
- 22. The Fire Alarm System shall be installed and maintained to NFPA #72 Standard.
- 23. The Sprinkler System shall be installed and maintained to NFPA #13 Standard.
- 24. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1999)
- 25. Section 25 135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 26. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
 - 27. Ventilation and access shall meet the requirements of Chapter 12 Sections 1210.0 and 1211.0 of the City's Building Code. (Crawl spaces & attics).
- 28. All electrical, plumbing and HVAC permits must be obtained by Master Licensed holders of their trade. No closing in of walls until all electrical (min. 72 hours notice) and plumbing inspections have been done.
- 29. All requirements must be met before a final Certificate of Occupancy is issued.
- 30. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (The BOCA National Building Code/1996).
 - 31. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical code (The BOCA National Mechanical Code/1993). (Chapter M-16)
- 434. Bridging shall comply with Section 2305.16.
- 35. Glass and glazing shall meet the requirements of Chapter 24 of the building code. (Safety Glazing Section 2406.0)
- 36. All flashing shall comply with Section 1406.3.10.
- 37. All signage shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code/1999).

 38. In Permi alate nandrails are required So That all Parts.

189 Duning ConsTruction No Means of egross Stall be blocker

McDougall, PFD

Marge Schmuckal, Zoning Administrator
Michael Nugent, Inspection Service Manager
WH 194

esu initim

** This permit is herewith issued, on the basis of plans submitted and conditions placed on these plans, any deviations shall require a separate approval.

...THIS PERMIT HAS BEEN ISSUED WITH THE UNDERSTANDING THAT ALL THE CONDITIONS OF THE APPROVAL SHALL BE COMPLETED. THEREFORE, BEFORE THE WORK IS COMPLETED A REVISED PLAN OR STATEMENT FROM THE PERMIT HOLDER SHALL BE SUBMITTED TO THIS OFFICE SHOWING OR EXPLAINING THAT THE CONDITIONS HAVE BEEN MET. IF THIS REQUIREMENT IS NOT RECEIVED YOUR CERTIFICATE OF OCCUPANCY SHALL BE WITHHELD. (You Shall Call for Inspections)

****ALL PLANS THAT REQUIRE A PROFESSIONAL DESIGNER'S SEAL, (AS PER SECTION 114.0 OF THE BUILDING CODE) SHALL ALSO BE PRESENTED TO THIS DIVISION ON AUTO CAD LT. 2000, DXF FORMAT OR EQUIVALENT.

*****CERTIFICATE OF OCCUPANCY FEE \$50.00

LAND USE - ZONING REPORT

ADDRESS: 33 Roberts ST DATE: 0/28
REASON FOR PERMIT: Replace Front Stains & Forch
BUILDING OWNER: NANcy Ayer C-B-L: 066A-B-24
PERMIT APPLICANT: Crag S. Adams
APPROVED: With Conclutions: #1, #4, #7, #10
CONDITION(S) OF APPROVAL
This permit is being approved on the basis of plans submitted. Any deviations shall require a separate approval before starting that work. During its existence, all aspects of the Home Occupations criteria, Section 14-410, shall be maintained. All the conditions placed on the original, previously approved, permit issued on
Marge Schmuckal, Zoning Administrator

Peopeety Adams boilder NANCY AYERS GRaig Adoms Corred (of ch Intermediate handral son That house starts.

Intermediate handral son all properties are required width of starts.

The required width of a handral 5-4

of the within 39" of a handral 5-4

are within 39" of a handral. DENTENDAY 1/1. wih. 52'3" 86 TREE

DUPLICATE

CITY OF PORTLAND, MAINE

DEPAR	TMENT	DATE	0.1
W.	Montre	5/	20101
(PED FROM	<u> </u>	
ADDRE 33	Level !	•	
UNIT	; ITEM	REVENUE CODE	DOLLAR AMOUNT
	Durino la		3000
•	Agrica		
(752006 AR	03	4
		·	
	Thoch # 15	5	
	/		
Осл	ASH CHECK OTHER	TOTAL	20 nd
	Qual /		
RECEI	VED BY	207) 774-1482	200747-BP