

PHYSICAL DATA

ORDERING NO.	FIELD—INSTALLED HEAT (kW)	NOMINAL COOLING CA- PACITY (BTUH)	DIMENSIONS			SHIPPING WEIGHT lb / kg
			Height	Width	Depth	
FE4ANF002000	5, 8, 9, 10, 15, 20	18,000	42-11/16-in 84 mm	17-5/8-in 448 mm	22-1/16-in 560 mm	135 lb
FE4ANF002T00		to				61 kg
FE4ANF002L00		36,000				
FE4ANF003000	5, 8, 9, 10, 15, 18, 20	24,000	53-7/16-in 1357 mm	21-1/8-in 537 mm	22-1/16-in 560 mm	150 lb
FE4AN(B,F)003T00		to				68 kg
FE4AN(B,F)003L00		42,000				
FE4ANF005000	5, 8, 9, 10, 15, 18, 20, 24, 30	30,000	53-7/16-in 1357 mm	21-1/8-in 537 mm	22-1/16-in 560 mm	172 lb
FE4AN(B,F)005T00		to				78 kg
FE4AN(B,F)005L00		48,000				
FE4ANB006000	8, 9, 10, 15, 18, 20, 24, 30	36,000	59-3/16-in 1503 mm	24-11/16-in 627 mm	22-1/16-in 560 mm	207 lb
FE4ANB006T00		to				94 kg
FE4ANB006L00		60,000				
FE5ANB004T00	5, 8, 9, 10, 15, 18, 20	24,000	59-3/16-in 1503 mm	24-11/16-in 627 mm	22-1/16-in 560 mm	200 lb
FE5ANB004L00		to				91 kg
		42,000				

SPECIFICATIONS

MODEL	FE4A				FE5A
	002	003	005	006	004
SIZE					
COIL					
Refrigerant Metering Device	Puron® Refrigerant (R-410A) TXV				
TXV Size	2 Ton	3 Ton	4 Ton	5 Ton	3 Ton
Configuration	A	Slope	A	A	A
Rows—Fins/In.			3 / 14.5		
Face Area (Sq Ft)	3.46	3.46	5.93	7.42	7.42
MATCHES OUTDOOR UNIT SIZES					
Nominal Cooling Tons	1.5, 2, 2.5, 3	2, 2.5, 3, 3.5	2.5, 3, 3.5, 4	3, 3.5, 4, 5	2, 2.5, 3, 3.5
FAN					
Air Discharge	Upflow, Downflow, Horizontal			Upflow, Downflow	
CFM/Ton (Nominal Clg/Htg)	350+				
Motor HP (ECM)	1/2	1/2	1/2	3/4	3/4
Filter	16-3/8-in	19-7/8-in	19-7/8-in	23-5/16-in	23-5/16-in
21-1/2-in (546 mm) x	(417 mm)	(505 mm)	(505 mm)	(592 mm)	(592 mm)
CABINET CONFIGURATION OPTIONS					
	1-piece	1-piece / Modular	1-piece / Modular	Modular	Modular