

STRUCTURAL SUPPORT METHODS

CUSTOMER/CONTRACTOR SUPPLIED AND INSTALLED

ITEM DESCRIPTION (\* INDICATES EXISTING)

- SUPPORT BACKING, LOCATE AS SHOWN, REFER TO ELEVATION DETAIL S60, FOR MAIN DISCONNECT CONTROL.
- 3 SUPPORT BACKING, LOCATE AS SHOWN, REFER TO ELEVATION DETAIL S62, FOR DC LIGHTING CONTROL.
- SUPPORT BACKING, LOCATE AS SHOWN, REFER TO ELEVATION DETAIL S63, FOR MAGNET RUNDOWN UNIT.
- 6 SUPPORT BACKING, LOCATE AS SHOWN, REFER TO ELEVATION DETAIL S86, FOR MAGNET MONITOR.
- | 7 | LEVELING AREA FOR MAGNET AND TABLE
- 8 MINIMUM CEILING HEIGHT REQUIREMENT AREA REFER TO EQUIPMENT DETAILS

9 SUPPORT BACKING, LOCATE AS SHOWN, REFER TO ELEVATION DETAIL S110, FOR MAINTENACE BYPASS PANEL.

 $\triangleleft$ 

STRUCTURAL NOTES

- o ALL UNITS THAT ARE WALL MOUNTED OR WALL SUPPORTED ARE TO BE PROVIDED WITH SUPPORTS WHERE NECESSARY. WALL SUPPORTS ARE TO BE SUPPLIED AND INSTALLED BY THE CUSTOMER OR HIS CONTRACTORS. SEE PLAN AND DETAIL SHEETS FOR SUGGESTED LOCATIONS AND MOUNTING HOLE LOCATIONS.
- o DIMENSIONS ARE TO FINISHED SURFACES OF ROOM.
- CERTAIN MR PROCEDURES REQUIRE AN EXTREMELY STABLE ENVIRONMENT TO ACHIEVE HIGH RESOLUTION IMAGE QUALITY. VIBRATION IS KNOWN TO INTRODUCE FIELD INSTABILITIES oxdimesINTO THE IMAGING SYSTEM. THE VIBRATION EFFECTS ON IMAGE QUALITY CAN BE MINIMIZED DURING THE INITIAL SITE PLANNING OF THE MR SUITE BY MINIMIZING THE VIBRATION ENVIRONMENT. SEE MOUNTING DETAIL ON SHEET S2 FOR ADDITIONAL INFORMATION.
- o STANDARD STEEL STUDS, NAILS, SCREWS, CONDUIT, PIPING, DRAINS AND OTHER HARDWARE ARE ACCEPTABLE IF PROPERLY SECURED. ANY LODSE STEEL OBJECTS CAN BE VIOLENTLY ACCELERATED INTO THE BORE OF THE MAGNET. CAREFUL THOUGHT SHOULD BE GIVEN TO THE SELECTION OF LIGHT FIXTURES, CABINETS, WALL DECORATIONS, ETC. TO MINIMIZE THIS POTENTIAL HAZARD, FOR SAFETY, ALL REMOVABLE ITEMS WITHIN THE MAGNET ROOM SUCH AS FAUCET HANDLES, DRAIN COVERS, SWITCH BOX COVER PLATES, LIGHT FIXTURE COMPONENTS, MOUNTING SCREWS, ETC. MUST BE NON-MAGNETIC. IF YOU HAVE A SPECIFIC QUESTION ABOUT MATERIAL, BRING IT TO THE ATTENTION OF YOUR GE INSTALLATION SPECIALIST.
- FLOOR LEVELNESS IN THE MAGNET ROOM SHOULD NOT EXCEED 0.3125 in. (8 mm) WHEN MEASURING BETWEEN DEPRESSIONS AND HIGH SPOTS OVER ANY 120 in. (3048 mm) DISTANCE WITHIN THE 87.5 in. (2178 mm) BY 139.3 in. (3539 mm) ARÈA OF THE MAGNET ENCLOSURE AND THE AREA IN FRONT OF THE ENCLOSURE. THIS FLOOR LEVELNESS REQUIREMENT IS IMPORATANT FOR ACCURATE PATIENT TABLE DOCKING.
- NON-MOVABLE STEEL SUCH AS WALL STUDS OR HVAC COMPONENTS WILL PRODUCE NEGLIGIBLE EFFECT ON THE ACTIVE SHIELD MAGNET.
- $_{
  m o}$  customers contractor must provide all penetrations in post tension floors. CUSTOMERS CONTRACTOR MUST PROVIDE AND INSTALL ANY NON-STANDARD ANCHORING. DOCUMENTS FOR STANDARD ANCHORING METHODS ARE INCLUDED WITH GE EQUIPMENT
- o CUSTOMERS CONTRACTOR MUST PROVIDE AND INSTALL HARDWARE FOR "THROUGH THE FLOOR" ANCHORING AND/OR ANY BRACING UNDER ACCESS FLOORS. THIS CONTRACTOR MUST ALSO PROVIDE FLÓOR DRILLING THAT CANNOT BE COMPLETED BECAUSE OF AN OBSTRUCTION ENCOUNTERED WHILE DRILLING BY THE GE INSTALLER SUCH AS REBAR ETC

QT. DATE: 9/25/06

PROJECT

065904

DRAWN BY:

REVISION

10/4/06

00

**REVISION HISTORY:** 

CHECKED BY: PMM

QUOTE NO: KX1CB7