

**THIRD FLOOR FRAMING PLAN**

1/2" = 1'-0"

- NOTE: 1. FINISH FLOOR REFERENCE ELEVATION = 112'-10" TYP UNL.
- 2. EXTERIOR BEARING WALL FRAMING SECOND LEVEL TO THIRD LEVEL SHALL BE 2X8 STUDS @ 12" ON CENTER LING. ALIGN ONE STUD BELOW TRUSS BEARING POINTS TYP.
- 3. INTERIOR BEARING WALL FRAMING SHALL BE 11" 2x8 @ 24" O.C. ALIGN STUDS BELOW TRUSS BEARING POINTS TYP.

- 4. PROVIDE (2) 2X6 JACK STUDS BELOW ALL HEADERS UNL ON PLAN. ALL BUILT UP JACK STUDS SHALL BE CONTIGUOUS TO THE FOUNDATION.
- 5. V.L. - INDICATES VERSALLUM BEAM OR APPROVED ALTERNATE.
- 6. REFER TO HARDWARE LIST, SCHEDULE DRAWING S3.3 FOR ELEVATOR SHAFT LINEITS.

**CUS**

CUS Architects  
 454 Industrial Drive  
 Portland, ME 04108  
 Phone: (207) 771-4544  
 Fax: (207) 771-4511  
 www.cusarch.com


Client:  
**YORK-CUMBERLAND**  
 HOLDING DEVELOPMENT

**LOGAN PLACE**  
 PORTLAND, ME

Project No: 229

Working Title:  
**THIRD FLOOR FRAMING PLAN**

Scale: 1/2" = 1'-0"  
 Date: FEBRUARY 6, 2004



Sheet Number:  
**S1.4**