Reviewed for Code Compliance
Inspections Division
Approved with Conditions

Date: 08/02/16

CHILLER MODEL: GD - 10H-MS

230 Volt 1 Phase	
FLA	
MCA	
MOC	

208/240/ 3 Phase	
FLA	58
MCA	64
MOC	154

460 Volt 3 Phase	
FLA	28
MCA	38
MOC	76

Dimensions	108"L x 48"W x 73"H
Frame	Powder Coated Steel
Housing	Powder Coated Aluminum
Tank	212 Gallon/with aux ports
Compressor HP	10
Condenser	Air Cooled
#1 Glycol Pump HP	3/4
#2 Glycol Pump HP	5
Glycol GPM @ 25 PSI	150
Glycol Connection Size	2" FPT
HX	Brazed Plate
Controls	Two Stage Digital

Electrical Enclosure		NEMA 4
Shipping Weight		1700 Lbs.
DB @ 10'		68
Refrigerant		R404a
BTUH	@ 20 degree F	64,218
	@ 30 degree F	79,372
	@ 40 degree F	96,495

Chiller Package consists of the following:

Complete refrigeration circuits, Engineered high efficient heat exchanger for maximum energy efficiency,
Chiller pump, Process pump, Fluid bypass valve, Insulated oversized glycol reservoir with Aux ports for future chiller modual, All insula
control panel w/single point electrical connection, breakers, starters & safety switches, Digital temperature controller pre wired for fu
Brass ball valves for supply and return glycol connection, Powder coated steel frame, Powder coated aluminum housing,
Aluminum louvered access panels for easy service and maintenance, Factory-Run tested and fully charged w/ refrigerant

1 Year Parts and Labor Warranty

Reviewed for Code Compliance
Inspections Division
Approved with Conditions

Date: 08/02/16

GD10-13.5H-MS
MODULAR SERIES
STATIONARY CHILLER

G&D CHILLERS

COMMITTED TO COLD

○ EST 1993 ○

3498 WEST FIRST, SUITE 1 EUGENE, OR 97402 - TEL (541) 345-3903 (800) 555-0973