Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 10/15/14

Certified

- UL 1741 and 1699B compliant
- Integrated AFCI meets the requirements of NEC 2011 690.11

Innovative

- Secure Power Supply provides daytime power in case of grid outage

Powerful

- 97.2% maximum efficiency
- Wide input voltage range
- Shade management with OptiTrac Global Peak MPP tracking

Flexible

- Two MPP trackers provide numerous design options
- Extended operating temperature range

SUNNY BOY 3000TL-US / 4000TL-US / 5000TL-US

Setting new heights in residential inverter performance

The Sunny Boy 3000TL-US/4000TL-US/5000TL-US represents the next step in performance for UL certified inverters. Its transformerless design means high efficiency and reduced weight. Maximum power production is derived from wide input voltage and operating temperature ranges. Multiple MPP trackers and OptiTrac™ Global Peak mitigate the effect of shade and allow for installation at challenging sites. The unique Secure Power Supply feature provides daytime power in the event of a grid outage. High performance, flexible design and innovative features make the Sunny Boy TL-US series the first choice among solar professionals.

RESURGAM CITY OF PORTLAND, MAINE
Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 10/15/14

A NEW GENERATION OF INNOVATION

THE NEW SUNNY BOY TL-US RESIDENTIAL SERIES HAS YET AGAIN REDEFINED THE CATEGORY.

Transformerless design

The Sunny Boy 3000TL-US / 4000TL-US / 5000TL-US are transformerless inverters, which means owners and installers benefit from high efficiency and lower weight. A wide input voltage range also means the inverters will produce high amounts of power under a number of conditions.

Additionally, transformerless inverters have been shown to be among the safest string inverters on the market. An industry first, the TL-US series has been tested to UL 1741 and UL1699B and is in compliance with the arc fault requirements of NEC 2011.

Increased energy production

OptiTrac™ Global Peak, SMA's shade-tolerant MPP tracking algorithm, quickly adjusts to changes in solar irradiation, which mitigates the effects of shade and results in higher total power output. And, with two MPP trackers, the TL-US series can ably handle complex roofs with multiple orientations or string lengths.

An extended operating temperature range of -40 °F to +140 °F ensures power is produced in all types of climates and for longer periods of time than with most traditional string inverters.

Secure Power Supply

One of many unique features of the TL-US residential series is its innovative Secure Power Supply ability. With most grid-tied inverters, when the grid goes down, so does the solar-powered home. SMA's solution provides daytime energy to a dedicated power outlet during prolonged grid outages, providing homeowners with access to power as long as the sun shines.

Simple installation

As a transformerless inverter, the TL-US residential series is lighter in weight than it's transformer-based counterparts, which makes lifting and transporting the new inverter easier than before. A new wall mounting plate features anti-theft security and makes hanging the inverter quick and easy. A simplified DC wiring concept allows the DC Disconnect to be used as a wire raceway, saving labor and materials.

Leading monitc and control sol

The new TL-US more than high graphic display. options provide degree of flexi a wireless communications standard often used for home energy management, and numerous wired options allows for a highly controllable inverter and one that can be monitored on Sunny Portal from anywhere on the planet via an Internet connection. Whether communicating through Zigbee®, RS485, or SMA's new wired, plug-and-play WebConnect, installers can find an optimal solution to their monitoring needs.

RESURGAM CITY OF PORTLAND, MAINE
Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 10/15/14

More efficient

Shade management

Easier

Broad temperature range

Secure Power Supply

Flexible communications

Technical data	Sunny Boy 3000TL-US		Sunny Boy 4000TL-			
	208 V AC	240 V AC	208 V AC	240 V		
Input (DC)						
Max. DC power (@ cos φ = 1)	3200 W		4200 W			
Max. DC voltage	600 V		600 V			
MPP voltage range	175 – 480 V		175 – 480 V			
Min. DC voltage / start voltage	125 / 150 V		125 / 150 V			
Max. input current / per MPP tracker	18 A / 15 A		24 A / 15 A			
Number of MPP trackers / strings per MPP tracker	2 / 2					
Output (AC)						
AC nominal power	3000 W		4000 W			
Max. AC apparent power	3000 VA		4000 VA		4550 VA	5000 VA
Nominal AC voltage / adjustable	208 V / ●	240 V / ●	208 V / ●	240 V / ●	208 V / ●	240 V / ●
AC voltage range	183 – 229 V	211 – 264 V	183 – 229 V	211 – 264 V	183 – 229 V	211 – 264 V
AC grid frequency; range	60 Hz / 59.3 – 60.5 Hz		60 Hz / 59.3 – 60.5 Hz		60 Hz / 59.3 – 60.5 Hz	
Max. output current	15 A		20 A		22 A	
Power factor (cos φ)	1		1		1	
Output phases / line connections	1 / 2		1 / 2		1 / 2	
Harmonics	< 4%		< 4%		< 4%	
Efficiency						
Max. efficiency	96.8%	97.1%	96.8%	97.2%	96.8%	97.1%
CEC efficiency	96%	96.5%	96%	96.5%	96%	96.5%
Protection devices						
DC disconnection device	●					
DC reverse-polarity protection	●					
Ground fault monitoring / Grid monitoring	● / ●					
AC short circuit protection	●					
All-pole sensitive residual current monitoring unit	●					
Arc fault circuit interrupter (AFCI) compliant to UL 1699B	●					
Protection class / overvoltage category	I / IV					
General data						
Dimensions (W / H / D) in mm (in)	490 / 519 / 185 (19.3 / 20.5 / 7.3)					
DC Disconnect dimensions (W / H / D) in mm (in)	187 / 297 / 190 (7.4 / 11.7 / 7.5)					
Packing dimensions (W / H / D) in mm (in)	617 / 597 / 266 (24.3 / 23.5 / 10.5)					
DC Disconnect packing dimensions (W / H / D) in mm (in)	370 / 240 / 280 (14.6 / 9.4 / 11.0)					
Weight / DC Disconnect weight	24 kg (53 lb) / 3.5 kg (8 lb)					
Packing weight / DC Disconnect packing weight	27 kg (60 lb) / 3.5 kg (8 lb)					
Operating temperature range	–40 °C ... +60 °C (–40 °F ... +140 °F)					
Noise emission (typical)	≤ 25 dB(A)		< 25 dB(A)		< 29 dB(A)	
Internal consumption at night	< 1 W		< 1 W		< 1 W	
Topology	Transformerless		Transformerless		Transformerless	
Cooling concept	Convection		Convection		Convection	
Electronics protection rating	NEMA 3R		NEMA 3R		NEMA 3R	
Features						
Secure Power Supply	●		●		●	
Display: graphic	●		●		●	
Interfaces: RS485 / Webconnect	○/○		○/○		○/○	
Interface: ZigBee	○		○		○	
Warranty: 10 / 15 / 20 years	●/○/○		●/○/○		●/○/○	
Certificates and permits (more available on request)	UL 1741, UL 1998, UL 1699B, IEEE1547, FCC Part 15 (Class A & B), CAN/CSA C22.2 107.1-1					
NOTE: US inverters ship with gray lids						
Type designation	SB 3000TL-US-22		SB 4000TL-US-22		SB 5000TL-US-22	

Reviewed for Code Compliance
Inspections Division
Approved with Conditions

Date: 10/15/14

Accessories

Speedwire/Webconnect interface
SWDM-US-10

RS485 interface
DM-485CB-US-10

Fan kit
FANKIT02-10

● Standard feature ○ Optional feature – Not available
Data at nominal conditions

SB345TLUSEXDS-DUS131625 SMA and Sunny Boy are registered trademarks of SMA Solar Technology AG. Text and figures comply with the state of the art applicable when printing. Subject to technical changes. We accept no liability for typographical and other errors. Printed on chlorine-free pap