080-G-011 BUILDING PERMIT APPLICATION Fee\_

Zone	Map #	Lot#	

Permit # \_\_\_\_ City of \_\_\_\_ BUILDING PERMIT AF

Please fill out any part which applies to job. Proper plans must accompany form.

	DEDAMIT ISSUED
Owner:Phone #	For Official Use Only
Address:	Subdivision:
LOCATION OF CONSTRUCTION	Inside Fire Limits Name Lot
	Bldg Code Ownership: Public
Contractor: Sub.: Sub.: Phone #	Time Limit Private
Address:Phone #	Estimated Cost
Est. Construction Cost: 27,000,00 Proposed Use:	Zoning:
Past Use:	Street Frontage Provided: Back Side Side
# of Existing Res. Units # of New Res. Units	Review Required:
Building Dimensions LWTotal Sq. Ft	Zoning Board Approval: Yes No Date:
	Planning Board Approval: YesNo Date:  Conditional Use: Variance Site Plan Subdivision
# Stories: # Bedrooms Lot Size:	Shoreland Zoning Yes No Floodplain Yes No
Is Proposed Use: Seasonal Condominium Conversion	Special Exception
Explain Conversion	Other (Explain)
Expiant Conversion	ALSTORIC PRESERVATION
	Ceiling:
Foundation:	1. Ceiling Joists Size: Not in District nor Landmark.
1. Type of Soil: 2. Set Backs - Front Rear Side(s)	2. Ceiling Strapping Size Spacing Does not require review.
2. Set Backs - Front Rear Side(s)	3. Type Ceilings: 4. Insulation Type 5. Ceiling Height:
3. Footings Size:	5. Ceiling Height:
4. Foundation Size:	Roof: Action: Approved,
5. Other	1. Truss or Rafter Size SpanApproved with Condition
Floor:	2. Sheathing Type Size Dented
1. Sills Size: Sills must be anchored.	3. Roof Covering Type
2. Girder Size: 3. Lally Column Spacing: Size: 4. Joists Size: Spacing 16" O.C. 5. Bridging Type: Size: 6. Floor Sheathing Type: Size:	Chimneys:
3. Lally Column Spacing: Size:	Type: Number of Fire Places
4. Joists Size: Spacing 16" O.C.	Heating:
5. Bridging Type: Size:	Type of Heat:
	Electrical:  Service Entrance Size: Smoke Detector Required Yes No
7. Other Material:	Plumbing
Exterior Walls:	1. Approval of soil test if required YesNo
1. Studding Size Spacing	2. No. of Tubs or Showers
2. No. windows	3. No. of Flushes
3. No. Doors	4. No. of Layatories
4. Header Sizes Span(s) 5. Bracing: Yes No.	5. No. of Other Fixtures
5. Bracing: Yes No.	Swimming Pools:
6. Corner Posts Size	1. Type: 2. Pool Size: x Square ISSUED 3. Must conform to National Electrical Code and Manual ISSUED
7. Insulation Type Size	3 Must conform to National Electrical Code and State Law 1880 Electrical
7. Insulation Type Size 8. Sheathing Type Size 9. Siding Type Weather Exposure	2. Pool Size:  3. Must conform to National Electrical Code and AITH REQUIREMENTS  Permit Received By
	Permit Received By
11. Metal Materials	El Alle A Transfer
Interior Walls:	Signature of Applicant Date
1. Studding Size Spacing	Son Purhert 111
2. Header Sizes Span(s)	CEO's District
3. Wall Covering Type	PERMIT ISSUED
4. Fire Wall if required	CONTINUED TO REVERSE SIDE TO LUCEMENTS
5. Other Materials	CONTINUED TO REVERSE SIDE EQUIREMENTS
White - Tax Assessor	Ivory Tag - CĚO

## BUILDING PERMIT REPORT

Address 33 Kenwood ST	Date 12/MAY/94
Reason for Permit To ConsTryc +	a Dormon
	Bldg.Owner: Michael Danovan
Contractor: Munkay Congy,	
Permit Applicant:	<u> </u>
Approval: * 7 * 8 * 13	
CONDITION OF	APPROVAL:

- 1. Before concrete for foundation is placed, approvals from Public Works and
- Inspection Services must be obtained. (A 24 hour notice is required prior to inspection).
- 2. Precaution must be taken to protect concrete from freezing.
- 3. It is strongly recommended that a register land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- 4. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hr., including fire doors with selfclosers.
- 5. Each apartment shall have access to (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
- 6. The boiler shall be protected by enclosing with one (1) hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. Sprinkler piping serving not more than six sprinklers may be connected to a domestic water supply system having a capacity sufficient to provide 0.15 gallons per minute, per square foot of floor throughout the entire area. An INDICATING shut-off valve shall be installed in an accessible locations between the sprinkler and the connection to the domestic water supply. Minimum pipe size shall be 3/4 inch copper or 1 inch steel. Maximum coverage area of a residential sprinkler is 144 square feet per sprinkler.
- 7. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside opening without the use of special knowledge or separate tools. Where windows are provided as a means of egress or rescue, they shall have a sill height not more than 44 inches (1118 mm) above the floor. All egress or rescue windows from sleeping room must have minimum net clear opening height dimension shall be 24 inches (610 mm). The minimum net clear opening width dimension shall be 20 inches (508 mm), and a minimum net clear opening of 5.7 sg.ft.
- 8. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the building code 919.3.2 (BOCA National Building Code 1993), and NFPA 101 Chapter 18 & 19.