923376 Permit # City of	BUILDING PERMIT APPLIC	ATION FeeZone	Map #	080 - G-006 Lot#
Please fill out any part which applie	s to job. Proper plans must accompany form.			FRMIT ISSUED
Owner:	Phone #Phone #	E Off	100	LIMITS IGGGLD
Address:	St. 2014, ME 95102		cial Use Only Subdivision:	
	16 Sh4 Field St.	Date	Name	JAN 2 2 1992
		Inside Fire Limits	Lot	50.00
Contractor:	Sub.: Call made nously -	Bldg Code	Ownership:	OF DODLIAN
Address:	Phone #Phone #	Estimated Cost	UI	Y OF POrtivale A
Est. Construction Cost:	Proposed Use:	Zoning: A-3		
	Past Use:	Street Frontage Provided: Provided Setbacks: Front	n l	C: J. C: Jo
# of Existing Res. Units#		Review Required:	Back	SideSide
	Total Sq. Ft	Zoning Board Approval: Yes1	No Date:	
		Planning Board Approval: Yes	No Date:	
# Stories: # Bedrooms_	Lot Size:	Conditional Use: Varia Shoreland Zoning Yes No	nceSite Pla	No Subdivision
Is Proposed Use: SeasonalC	ondominium Conversion			
Explain Conversion	renovations; & dermer	Special Exception Other (Explain)	2/22	91
The state of the s		UNDA	1-00	MISTORIC PRESER
		1 (2 11) Table Olem		Was to District to the S
Foundation: 1. Type of Soil:		2. Ceiling Strapping Size	Spacing	NOU DI DISULCE NOI
2. Set Backs - Front	Rear Side(s)	3. Type Ceilings:		Dose not tedmie te
3. Footings Size:		4. Insulation Type	Size	Requires Review.
4. Foundation Size:		5. Ceiling Height:		
5. Other		Roof:  1. Truss or Rafter Size 2. Sheathing Type 3. Part Couring Type	Span	Action:Approved.
Floor:		2. Sheathing Type	Size	Approved was
	Sills must be anchored.	3. Roof Covering Type		Duto/ 149 197
2. Girder Size:	O. C.	Chimneys: Numl	her of Fire Places	Signature:
3. Lally Column Spacing:	Size:	Heating:	ber of Fire Fraces	1 20100
5. Bridging Type:	Spacing 16" O.C. Size:	Type of Heat:		
6. Floor Sheathing Type:	Size:	klectrical:		
7. Other Material:		Service Entrance Size:	Smoke Detector	Required YesNo_
Exterior Walls:		Plumbing: 1. Approval of soil test if required	Yes	No
	Spacing	2. No. of Tubs or Showers	Xeed .	
2. No. windows		3. No. of Flushes		
3. No. Doors		4. No. of Lavatories		
4. Header Sizes 5. Bracing: Yes	No. Span(s)	5. No. of Other Fixtures Swimming Pools:		
5. Bracing: Yes 6. Corner Posts Size	No. VVIII	1. Type:		
7. Insulation Type	Size	2. Pool Size : x	Square	Footage
8. Sheathing Type	Size	3. Must conform to National Elect	rical Code and State	Law.
9. Siding Type	Weather Exposure	Permit Received By	. Chase	
10. Masonry Materials 11. Metal Materials				1. 1
Interior Walls:		Signature of Applicant		Date //13 /7
1. Studding Size	Spacing	1 1 - 1 June 1 - 11	ker II	
2. Header Sizes	Span(s)	CEO's District		
3. Wall Covering Type 4. Fire Wall if required		41		
5. Other Materials		CONTINUED TO REVERSE SIDE		

		<b>A</b>
		- 1
	Inspection	Record
Base Fee \$ 75 — FEES (Breakdown From Front)	Туре	Date
Subdivision Fee \$Site Plan Review Fee \$		
Other Fees \$		
(Explain)		
Late Fee \$		
COMMENTS Trypectal alle + interior	o walls intalled a	t to close
ok b O wh		in
Of themes as con	e grung	
CER	RTIFICATION	
	proposed work is authorized by the owner of record an	nd that I have been authorized
ereby certify that I am the owner of record of the named property, or that the	proposed work is additionated by the owner or record di	
ner to make this application as has authorized agent and I agree to conformalication is issued, I certify that the code official or the code official's authority	n to all applicable laws of this jurisdiction. In addition, rized representative shall have the authority to enter a	if a permit for work described in
ner to make this application as has authorized agent and I agree to conformalication is issued, I certify that the code official or the code official's authority	n to all applicable laws of this jurisdiction. In addition, rized representative shall have the authority to enter a	if a permit for work described in
ner to make this application as has authorized agent and I agree to conformation is issued, I certify that the code official or the code official's authority	n to all applicable laws of this jurisdiction. In addition, rized representative shall have the authority to enter a mit.	if a permit for work described in
pereby certify that I am the owner of record of the named property, or that the pere to make this application as has authorized agent and I agree to conform plication is issued, I certify that the code official or the code official's authorisonable hour to enforce the provisions of the code(s) applicable to such per NATURE OF APPLICANT  ADDRESS	n to all applicable laws of this jurisdiction. In addition, rized representative shall have the authority to enter a rmit.  ### Power and the content of this jurisdiction. In addition, and in addition, and in addition, in addition, and in addition, and in addition addition and addition and addition addition.  ###################################	if a permit for work described if

## BUILDING PERMIT REPORT

ADDRESS: 16 Sheffield St. DATE: 1/22/92
REASON FOR PERMIT: ALTERATIONS AND NEW dormer AS per
Plans
BUILDING OWNER: John D. Walker II
contractor: Rich Aluminum Co.
PERMIT APPLICANT: OWNER
APPROVED: with conditions-starred tems (6,7,9)
•

## CONDITION OF APPROVAL:

- 1.) Before concrete for foundation is placed, approvals from Public Works and Inspection Services must be obtained.
- 2.) Precaution must be taken to protect concrete from freezing.
- 3.) All vertical openings shall be enclosed with construction having a fire rating of at least one(1) hour, including fire doors with selfclosers.
- 4.) Each apartment shall have access to two(2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
- 5.) The boiler shall be protected by enclosing with one(1) hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. Sprinkler piping serving not more than six sprinklers may be connected to a domestic water supply system having a capacity sufficient to provide 0.15 gallons per minute, per square foot of floor throughout the entire area. An INDICATING shut-off valve shall be installed in an accessable location between the sprinkler and the connection to the domestic water supply. Minimum pipe size shall be 3/4 inch copper or 1 inch steel. Maximum coverage area of a residential sprinkler is 144 square feet per sprinkler.
- 6.) Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside opening without the use of separate tools. Where windows are provided as a means of egress or rescue, they shall have a sill height not more than 44 inches (1118 mm) above the floor. All egress or rescue windows from sleeping rooms must have minimum net clear openings of 5.7 square feet (0.53m). The minimum net clear opening height dimension shall be 24 inches (610 mm). The minimum net clear opening width dimension shall be 20 inches (508 mm).
- 7.) All single and multiple-station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the building code (BOCA National Building Code 1990, and N.F.P.A. 74).

- 8.) Private garages located beneath rooms in buildings of Use Groups R-1, R-2, R-3 or I-1 shall have walls, partitions, floors and ceilings separating the garage space from the adjacent interior spaces constructed of not less than 1-hour fireresistance rating. Attached private garages shall be completely separated from the adjacent interior spaces and the attic area by means of 1/2-inch gypsum board or equivalent applied to the garage side. The sills of all door openings between the garage and adjacent interior spaces shall be raised not less than 4 inches (102 mm) above the garage floor. The door opening protectives shall be 1 3/4-inch solid core wood doors or approved equivalent.
- 9.) A guardrail system located near the open side of deck or elevated walking surfaces shall be constructed. Guards in buildings of Use Group R-3 shall be not less than 36 inches in height. Open guards shall have intermediate rails, balusters or other construction such that a sphere with a diameter of 4 inches cannot pass through any opening. Handrails on stairs shall be no less than 34 inches nor more than 38 inches. Handrails within individual dwelling units shall not be less than 30 inches nor more than 38 inches.
  - 10.) Section 25-135 of the Municipal Code for the City of Portland states: "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year.
  - 11.) The builder of a facility to which Section 4594-C of the Maine State Human Rights Act, Title 5 M.R.S.A. refers, shall obtain a certification from a design professional that the plans of the facility meet the standards of construction required by this section. Prior to commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.

Sincerely,

P. Samuel Hoffses

Chief of Inspection Services

/e1

11/16/88

11/27/90

8/14/91

the second of th

and the formation of the property with the

1 1/2 30