City of Portland, Maine - Buildin	ig or Use Permit Appli <mark>ca</mark>	tion 38	89 Congress	Street, (04101, Tel: (207) 87	4-8703, FAX: 874-8716
Location of Construction:	Owner:			Phone:		Permit No: 9 8 0 9 4 3
ARRENDAS 46 Devenshire St	Hartell,	Greg			797-7331	PERMIT ISSUED
Owner Address:	Lessee/Buyer's Name:		Phone:	Busines	sName: 870 24	PERIVIT ISSUED
Contractor Name:	Address:		Phone):):		Perinit Issued: 4 1998
Past Use:	Proposed Use:	IC	COST OF WORL	ĸ.	PERMIT FEE:	
Tast Osc.	Proposed Use.		\$ 60,000		\$ 320.00	CITY OF PORTLAND
2-1-1-1		F	IRE DEPT.		INSPECTION:	CITT OF TORTERINE
				Denied	Use Group: Type:	
					of The m	Zone: CBL: 08Z-C-001
Dunnand Duningt Description			ignature:		Signature:	Zoning Approval:
Proposed Project Description:		1000			ES DISTRICT (P.A.D.)	permitted for he
Rebuild 2-fem dwelling from fi	ire damage	A		Approved	uith Coudidana.	Special Zone or Reviews:
				Approved v Denied	with Conditions:	☐ Shoreland ☐ Wetland
				Demed		☐ Flood Zone
		S	ignature:		Date:	☐ Subdivision
Permit Taken By:	Date Applied For:	12 44	1000			☐ Site Plan maj ☐minor ☐mm ☐
EIG		1.3 AE	gust 1998			Zoning Appeal
1. This permit application does not preclude the	Applicant(s) from meeting applical	ole State ar	nd Federal rules.			□ Variance
2. Building permits do not include plumbing, so	1,1	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				☐ Miscellaneous
		C •	T 1 . 6			☐ Conditional Use ☐ Interpretation
3. Building permits are void if work is not started within six (6) months of the date of iss tion may invalidate a building permit and stop all work			suance. Faise informa-			□ Approved
non may invalidate a building permit and sit	op an work					□Denied
						I I I I I I I I I I I I I I I I I I I
Call Greg for Pau Pager: 8	70-2476				rn.	Historic Preservation ☐ Not in District or Landmark
			PER WITH F	MIT ISSU	JEU JEUTS	□ Does Not Require Review
			WITH F	REQUIRE	WENTS	☐ Requires Review
			Million			Action:
				-		Action:
	CERTIFICATION			-		□Appoved
I hereby certify that I am the owner of record of th						
authorized by the owner to make this application						
if a permit for work described in the application is					ive the authority to enter all	Date:
areas covered by such permit at any reasonable h	our to enforce the provisions of the	code(s) ap	pplicable to such	permit		-
		2.00	1000			
CICNATURE OF A DRUGANT	ADDRECC	13 Aug	ust 1998		DUONE	-
SIGNATURE OF APPLICANT	ADDRESS:		DATE:		PHONE:	
RESPONSIBLE PERSON IN CHARGE OF WOR	K, TITLE				PHONE:	CEO DISTRICT
White_Dr	ermit Desk Green-Assessor's	Canary_F	PW Pink_Pu	blic File	Ivory Card-Inspector	100

Inspection Record	
Туре	Date
Foundation:	
Framing:	110
Plumbing:	
Final:	
Other:	

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application

Attached Single Family Dwellings/Two-Family Dwelling

Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Addressof Construction (include Portion of Building)	46 Deienshaire	St. Park
Total Square Footage of Proposed Structure 2550	Square Footage of I	Lot 10 000 H
Tax Assessor's Chart, Block & Lot Number	Owner:	Telephone#:
Chart# (\\Z Block# C Lot# OO \	GREG MORTELL	1 797-7331
Owner's Address:	Lessee/Buyer's Name (If Applicable)	Cost Of Work: Fee
SAME	SANG	\$ 60000 \$ 320
Proposed Project Description:(Please be as specific as possible)		, , , , , , , , , , , , , , , , , , , ,
Rebeild two Franky F Contractor's Name, Address & Telephone S Amc	From Fire Pen	Rec'd By
Current Use:	Proposed Use:	tuo fanily
All construction must be conducted in compl All plumbing must be condu All Electrical Installation must comply of the HVAC (Heating, Ventililation and Air Conducted to the following with you applied to the following with your ap	cted in compliance with the St. with the 1996 National Electric litioning) installation must con n: Your Deed or Purchase and Sa of your Construction Contract, 3) A Plot Plan/Site Plan r the above proposed projects. The	AC and Electrical installation. Building Code as amended by Section 6-Art II. tate of Maine Plumbing Code. cal Code as amended by Section 6-Art III. omply with the 1993 BOCA Mechanical Code. ale Agreement t, if available

4) Building Plans

Unless exempted by State Law, construction documents must be designed by a registered design professional A complete set of construction drawings showing all of the following elements of construction:

- Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)
- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas
 equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.

Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.

Signature of applicant:	my	mutter	Date: 8/	13/98
Building Per	rmit Fee: \$25.00 for the	1st \$1000.cost plus \$5.00 per	\$1,000,00 construct	tion cost thereafter.

Additional Site review and related fees are attached on a separate addendum

Call Grag Pg 870-2476 for 1/4

9.

BUILDING PERMIT REPORT	
DATE: 0/21/98 ADDRESS: 46 Devon Shire St	
$C \setminus A \setminus A \setminus A \setminus C \setminus A \setminus A \setminus A \setminus A \setminus A \setminus $	7
REASON FOR PERMIT: Ebulg After the (Significantly in FER)	\neq
BUILDING OWNER: 9 MArtell	_
CONTRACTOR:	
PERMIT APPLICANT: 0 WNLT	
USE GROUP R-3 BOCA 1996 CONSTRUCTION TYPE 5B	_
CONDITION(S) OF APPROVAL	
This Permit is being issued with the understanding that the following conditions are met:	
	2
Approved with the following conditions: #6, #7, #8 #9, #6 #11, #12, #13, #14 #15, #16, #2 #25 #26, #27, #28, #29 #30, #31, 1 This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.	<u>_</u> ,
1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.	
2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)	
Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing	
not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches	
beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the	
bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The	
top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be	*
protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or	
crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2	
2.6 Foundations anchors shall be a minimum of 1 1/2" in diameter, 7" into the foundation wall, minimum of 12" form corners	of
From corners of foundation and a maximum 6'o.c. between bolts. (Section 2305.17)	
Precaution must be taken to protect concrete from freezing. Section 1908.0	
It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.	
5. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from	
adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire	
resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated fro	
the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½	ļ
inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA	
National Mechanical Code/1993). Chapter 12 & NFPA 211	
Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's building code. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated	ŝ
building code.	
Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated	
walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-	
1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material suc	
that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that	
would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be	
less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at	
least 1 1/4" and not greater than 2". (Sections 1021 & 1022.0) Headroom in habitable space is a minimum of 7'6". (Section 1204.0)	
0.) Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7.3/4" maximum rise. All other Use group	
least 1 1/4" and not greater than 2". (Sections 1021 & 1022.0) Headroom in habitable space is a minimum of 7'6". (Section 1204.0) Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread. 7" maximum rise. (Section 101±.0) The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6' 8") 1014.4 Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window of the stairway s	
The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4	
y a compared to the second of the compared to	r
exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill heigh	t

over

13.	not more than 44 inches (1118min) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6) Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. Section
15)	All vertical openings shall be enclosed with construction having a fire rating of at lest one (I)hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) Section 710.0 The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment. Table 302.1.1
(16./	All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations): In the immediate vicinity of bedrooms
	In all bedrooms To make the possibility and walking waits including becomes to
	• In each story within a dwelling unit, including basements In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2
17.	A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. Section 921.0
18.	The Fire Alarm System shall be maintained to NFPA #72 Standard.
19.	The Sprinkler System shall maintained to NFPA #13 Standard.
20.	All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
21.	Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to
22.	excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year". The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the
	certification to the Division of Inspection Services.
23)	Ventilation shall meet the requirements of Chapter 12 Sections 1210. Of the City's Building Code. (crawl spaces & attics) All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade.
25	All requirements must be met before a final Certificate of Occupancy is issued.
26/ 27.)	All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National Building Code/1996).
27.	Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)
28 29)	Mechanical Code/1993). (Chapter M-16) Please read and implement the attached Land Use-Zoning report requirements. I Shall remain Z families—Not Adesian Standard Shall be Submitted) to This office for Approval Leutchen ego
	for the floor & roof trusses before work is started
(30.)	Seefed 2305, 8.1 2305, 8. 2305, 4.4
31.	GLASS is glazny as per chapter 24 of the Boca Bldg Code Shall be met
32.	
P. Samu	nel Hoffses. Building Inspector
	McDougall, PFD ge Schmuckal, Zoning Administrator