# City of Portland, Maine – Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

and the second se

Location of Construction:	Owner:	Carol Kinney	Phone:	6-5950	Permit No:
ner Address: Lessee/Buyer's Name:		Phone:	Phone: BusinessName:		991124
Contractor Name:	Name: Address:		Phone:		Permit Issued: DOULD
Past Use:	Proposed Use:	COST OF WOR \$ 850.00		PERMIT FEE: \$ 30.00	OCT   4 1999
1-Family	Same	FIRE DEPT.	Denied	INSPECTION: Use Group: U'Type: 53	Zone: CBL:
		Signature:		BOCA 96 Signature: Hollen	1R-4 084-2-002 []
Proposed Project Description: Storage Shad & x 12*	96#	Action:	Approved	DISTRICT (0, 4, D.)	Zoning Approval: Special Zone or Reviews: Shoreland Wetland Flood Zone Subdivision
Permit Taken By:	Date Applied For:	10-4-99	1.00	and the second	□Site Plan maj □minor □mm □
<ol> <li>This permit application does not preclude the Building permits do not include plumbing, st</li> <li>Building permits are void if work is not starte tion may invalidate a building permit and store</li> </ol>	eptic or electrical work. d within six (6) months of the date o op all work	f issuance. False informa- end To: Richard 4 26 Whitel	Carol Ei bead Stree Land, ME PERM	04108 TISSUED	Zoning Appeal
			WITH REC	QUIREMENTS	Action:
I hereby certify that I am the owner of record of th authorized by the owner to make this application if a permit for work described in the application is areas covered by such permit at any reasonable he	as his authorized agent and I agree to issued, I certify that the code offici	to conform to all applicab al's authorized representa	le laws of this tive shall have	jurisdiction. In addition,	□ Appoved □ Approved with Conditions □ Denied Date:
		10-4-99			
SIGNATURE OF APPLICANT	ADDRESS:	DATE:	J	PHONE:	
RESPONSIBLE PERSON IN CHARGE OF WOR	K, TITLE			PHONE:	
White-Pe	ermit Desk Green-Assessor's	Canary-D.P.W. Pink-P	ublic File Iv	ory Card-Inspector	ub

measured		Inspection Record	
June June			
the rup		Type	ng: ng:
Libuchia			Founda Framin Plumbi Final
Cose at			
Cherken Not hun Comple.			
66			

COMMENTS

	BUILDING PERMIT REPORT				
I	ATE: 50CT.99 ADDRESS: 26 WhiTehead Street P.T. CBL: 084-N-002				
F	REASON FOR PERMIT: 8x12 STorage Shed				
E	Building owner: Kinney				
р	ERMIT APPLICANT:				
τ	se group $\underline{U}$ . Construction type $\underline{5B}$				
	he City's Adopted Building Code (The BOCA National Building Code/1996 with City Amendments) he City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993) # 30, 0 d				
	CONDITION(S) OF APPROVAL				
Т	his permit is being issued with the understanding that the following conditions are met: $\frac{1}{2}$				
Ā	pproved with the following conditions:				
×1.	This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained.				
¥	(A 24 hour notice is required prior to inspection)" <u>ALL</u> LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING."				
3.					
	10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the				
	footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter				
	membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor				
	elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be				
4.	placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2 Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and				
4.	a maximum 6' o.c. between bolts. (Section 2305.17)				
5.	Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.				
6. 7.	Precaution must be taken to protect concrete from freezing. Section 1908.0 It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify				
7.	that the proper setbacks are maintained.				
8.	Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent				
	interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private				
garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage means of 1/2 inch gypsum board or the equivalent applied to the					
	garage side. (Chapter 4, Section 407.0 of the BOCA/1996)				
9.	All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National				
	Mechanical Code/1993). Chapter 12 & NFPA 211				
10.	Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.				
11.					
	for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use				
	Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2, M and R and public garages and open				
	parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through				
	any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 3e4" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section				
	with an outside diameter of at least 1 ¼" and not greater than 2". (Sections 1021 & 1022.0) - Handrails shall be on both sides of				
	stairway. (Section 1014.7)				
12.	Headroom in habitable space is a minimum of 7'6". (Section 1204.0)				
13.	Stair construction in Use Group R-3 & R-4is a minimum of 10" tread and 7 3/" maximum rise. All other Use Group minimum 11"				
14	tread, 7" maximum rise. (Section 1014.0) The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4				
14. 15.	Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door				
	approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate				
	tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above				
	the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches				
	(610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.				

.

## (Section 1018.4)

- Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits 16. directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)
- All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self 17. closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0)
- The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic 18. extinguishment. (Table 302.1.1)
- All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of 19. the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
  - In the immediate vicinity of bedrooms
  - In all bedrooms
  - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2.

- A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved 20. type. (Section 921.0)
- 21. The Fire Alarm System shall maintained to NFPA #72 Standard.
- 22. The Sprinkler System shall maintained to NFPA #13 Standard.
- All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 23. of the City's Building Code. (The BOCA National Building Code/1996)
- Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open 24. any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification 25. from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
- 26. Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).
- ₹ 27. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all electrical (min.72 hours notice) and plumbing inspections have been done. . .
  - All requirements must be met before a final Certificate of Occupancy is issued.
- 28. ¥ 29. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building Code/1996). 30.
  - Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)
  - Code/1993). (Chapter M-16) Please read and implement the attached Land Use Zoning report requirements. Without Altaning the SetDate Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code. 32. 33. Glass and glazing shall meet the requirements of Chapter 24 of the building code.
- All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code 34. 1996). . .

35. 36. 37. 38. Building Inspector Lt. McDougall PFD cc: Marge Schmuckal, Zoning Administrator

PSH 7/24/99

\*\*On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.

#### THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

#### PERMIT IS ISSUED

Building or Use Permit Pre-Application

## Additions/Alterations/Accessory Structures

**To Detached Single Family Dwelling** 

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE\*\*If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Address of Construction	26 WF	iTE he	ad St	P.I	04108

Tax Assessor's Chart, Block & Lot Number Chart# 084 Block# N Lot# 002	* RICHARD +CAROC KINNE	Telephone#: 207 766-5950					
Owner's Address: 26 WHITEHEND ST. 04108	Lessee/Buyer's Name (If Applicable)	Cost Of Work: Fee \$ 850 ° \$ 30 -					
Proposed Project Description: (Please be as specific as possible) STORNGE SHED 8 X/2							
	W/4 TETTONP ST PENIS ISLAN	By: UB D. M. E. 64108					

Separate permits are required for Internal & External Plumbing, HVAC and Electrical installation. •All construction must be conducted in compliance with the 1996 B.O.C.A. Building Code as amended by Section 6-Art II. •All plumbing must be conducted in compliance with the State of Maine Plumbing Code.

•All Electrical Installation must comply with the 1996 National Electrical Code as amended by Section 6-Art III. •HVAC(Heating, Ventilation and Air Conditioning) installation must comply with the 1993 BOCA Mechanical Code. You must Include the following with you application:

## 1) A Copy of Your Deed or Purchase and Sale Agreement

2) A Copy of your Construction Contract, if available

## 3) A Plot Plan (Sample Attached)

If there is expansion to the structure, a complete plot plan (Site Plan) must include:

- The shape and dimension of the lot, all existing buildings (if any), the proposed structure and the distance from the actual property lines. Structures include decks porches, a bow windows cantilever sections and roof overhangs, as well as sheds pection pools, garages and any other accessory structures.
- Scale and required zoning district setbacks

## 4) Building Plans (Sample Attached)

A complete set of construction drawings showing all of the following elements of construction

- Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)
- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas
  equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.

#### Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued. I certify that the Code Official's authorized representative shall have the authority to enter all areas govered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.

Signature of applicant: Date:

Building Permit Fee: \$30.00 for the 1st \$1000.cost plus \$6.00 per \$1,000.00 construction cost thereafter. ONINSP/CORRESP/MNUGENT/APADSFD/WPD





Department of Urban Development Joseph E. Gray, Jr. Director

# **CITY OF PORTLAND**




# Building or Use Permit Application Additions/Alterations/Accessory Structures To Detached Single Family Dwelling

As an applicant for a building permit, you are about to enter into a relationship with our Office. We welcome any questions, comments or suggestions that will make the process more efficient. Attached you will find an application and some samples of the submissions you will provide at application time. Please read <u>ALL</u> of the information and if you need any further assistance please call 874-8703 or 874-8693.



Inspection Services Michael J. Nugent Manager

The the shed Perry And -> [0-10 G/-1 BX |''=10'10 54' 18' > 511 D# 8 SideyAnd >15'-15'sh  $\gg N$ 1. <u>H</u> EXISTING GARDEN 15. 80 HOUSE Porch -----444 (front) STREET 26 WHITE HOND



$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	LOURING 3/1 NOS LOUR JOISTS ELUNC JOISTS RAFIERS		North AUVOLO PLATE · SOLE PLATE · RIDGE BOARD · RIDGE BOARD · NTILC STUDS Inse FACIA	10 2 × 4 × 4 × 5 2×4×8 1 2×6×12 4 2×4×12 4 2×4×12 4 2×4×12 4 2×4×12 4 2×4×12	KINNG	y 26 a
ro Nargen						6x0
2×4×10 64 3.2× 207,94 2×6×12 1 6.12 6.12					en e	
146 x 1 10 3,71 37.10						
448×12 12 10,75° 129,00						
44847/16 6 10,75 64,50						
44194744 3 28,15 84,47 Cb	X					
24848 2 5,86 11,72 248×12 2 7,76 17,52 Nollwood Minglen 168 ft 47,70 6 builder 7,95 Color brieg Tap						
strews 25,00						
mæile mæile 11.00 546.07 38.7624 .644.07 38.7624 .644.90 278.040 463.21 Door wirdow concrete blafan heingen		8VI2 = 96 ft				
				Bandari setan arawi 199 72 magala ganga panapara sa		an a
						6.76
				on and on hear of the second	ann an the second and the second s	

Ultitations ST. PENIS ISLAND CONCRETTE PADS ET CORNER 676 ON 6x6 beams on concrete Plack Π

