

City of Portland, Maine - Building or Use Permit Application 589 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

Location of Construction: 41-A New Island Ave, Peaks Isl		Owner: Remington O. Schmidt		Phone: w) 773-1430 h) 766-5550		Permit No: 981107							
Owner Address: SAA 04108		Lessee/Buyer's Name:		Phone:		BusinessName:							
Contractor Name: SAA		Address:		Phone:		<div style="border: 2px solid black; padding: 5px; text-align: center;"> PERMIT ISSUED Permit Issued: SEP 29 1998 CITY OF PORTLAND </div>							
Past Use: 1-fam		Proposed Use:		COST OF WORK: \$ 1,000.00 PERMIT FEE: \$ 25.00		INSPECTION: Use Group: Type: B BOX A 76 Signature: 7/1/98							
Proposed Project Description: New Porch w/doors & windows		PEDESTRIAN ACTIVITIES DISTRICT (P.A.D.) Action: <table style="display: inline-table; vertical-align: top;"> <tr><td>Approved</td><td><input type="checkbox"/></td></tr> <tr><td>Approved with Conditions</td><td><input type="checkbox"/></td></tr> <tr><td>Denied</td><td><input type="checkbox"/></td></tr> </table>		Approved	<input type="checkbox"/>	Approved with Conditions	<input type="checkbox"/>	Denied	<input type="checkbox"/>	Signature: _____ Date: _____		Zone: CBL: 084-N-026+ Zoning Approval: 8/11/98 Special Zone or Reviews: <input type="checkbox"/> Shoreland <input type="checkbox"/> Wetland <input type="checkbox"/> Flood Zone <input type="checkbox"/> Subdivision <input type="checkbox"/> Site Plan maj <input type="checkbox"/> minor <input type="checkbox"/> mm <input type="checkbox"/>	
Approved	<input type="checkbox"/>												
Approved with Conditions	<input type="checkbox"/>												
Denied	<input type="checkbox"/>												
Permit Taken By: SP		Date Applied For: 18 September 1998											

- This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules.
- Building permits do not include plumbing, septic or electrical work.
- Building permits are void if work is not started within six (6) months of the date of issuance. False information may invalidate a building permit and stop all work..

PERMIT ISSUED
WITH REQUIREMENTS

CERTIFICATION

I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit

21 September 1998

SIGNATURE OF APPLICANT _____ ADDRESS: _____ DATE: _____ PHONE: _____

RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE _____ PHONE: _____

White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

CEO DISTRICT

2

COMMENTS

10/2/98 - Customer Called - did pie - Can - foundation forms are ready for prep. - discussed "footprint", changing 2x6 to 2x8's, needs/riens & guardrail space. Request prep for foundation next week

10-5-98 We talked on the phone and He is Ready For Inspection of

Foundation (TR)

10-7-98 Footers OK for Pour (TR)

Inspection Record

Date

Foundation: _____

Framing: _____

Plumbing: _____

Final: _____

Other: _____

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

**Building or Use Permit Pre-Application
Additions/Alterations/Accessory Structures
To Detached Single Family Dwelling**

In the interest of processing your application in the quickest possible manner, please complete the information below for a Building or Use Permit.

NOTEIf you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted. 04108-1338**

Location/Address of Construction: <u>41-A NEW ISLAND AVENUE, PEAKS ISLAND, ME</u>			
Tax Assessor's Chart, Block & Lot Number Chart# <u>84</u> Block# <u>N</u> Lot# <u>27</u>	Owner <u>Remington O. Schmidt</u>	Telephone#: <u>773-1430</u> <u>766-5356</u>	<u>OF</u> <u>140</u>
Owner's Address:	Lessee/Buyer's Name (If Applicable):	Cost Of Work: <u>\$1,000.00</u>	Fee: <u>\$25</u>
Proposed Project Description: (Please be as specific as possible) <u>New Porch - OLD ONE ROTTED AWAY w/ WOODS.</u>			
Contractor's Name, Address & Telephone <u>NONE / OWNER</u>		Rec'd By:	

Separate permits are required for Internal & External Plumbing, HVAC and Electrical installation.

- All construction must be conducted in compliance with the 1996 B.O.C.A. Building Code as amended by Section 6-Art II
- All plumbing must be conducted in compliance with the State of Maine Plumbing Code.
- All Electrical Installation must comply with the 1996 National Electrical Code as amended by Section 6-Art III.
- HVAC (Heating, Ventilation and Air Conditioning) installation must comply with the 1993 BOCA Mechanical Code.

You must include the following with you application:

- 1) A Copy of Your Deed or Purchase and Sale Agreement
- 2) A Copy of your Construction Contract, if available
- 3) A Plot Plan (Sample Attached)


If there is expansion to the structure, a complete plot plan (Site Plan) must include:

- The shape and dimension of the lot, all existing buildings (if any), the proposed structure and the distance from the actual property lines. Structures include decks porches, a bow windows cantilever sections and roof overhangs, as well as, sheds, pools, garages and any other accessory structures.
- Scale and required zoning district setbacks

4) Building Plans (Sample Attached)

A complete set of construction drawings showing all of the following elements of construction:

- Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)
- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.



Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.

Signature of applicant: <u>[Signature]</u>	Date: <u>9-18-98</u>
--	----------------------

Building Permit Fee: \$25.00 for the 1st \$1000 cost plus \$5.00 per \$1,000.00 construction cost thereafter.

BUILDING PERMIT REPORT

DATE: 27 Sept. 98 ADDRESS: 41-A New Island AVE. Pt. 084-N-026+
 REASON FOR PERMIT: New Porch w/doors & windows.
 BUILDING OWNER: R. O. Schmidt.
 CONTRACTOR: SAA
 PERMIT APPLICANT: SAA
 USE GROUP R-3 BOCA 1996 CONSTRUCTION TYPE 5B

CONDITION(S) OF APPROVAL

This Permit is being issued with the understanding that the following conditions are met:

Approved with the following conditions: *1, *2, *2.5, *2.6, *8, *9, *10, *24, *26, *23, *29.

- *1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
- *2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)
- *2.5. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.3.2
- *2.8. Foundations anchors shall be a minimum of $\frac{1}{2}$ " in diameter, 7" into the foundation wall, maximum of 12" from corners of foundation and a maximum 6' o.c. between bolts. (Section 2305.17)
- 3. Precaution must be taken to protect concrete from freezing. Section 1908.0
- 4. It is strongly recommended that a registered land surveyor check all foundation lines before concrete is placed. This is done to verify that the proper setbacks are maintained.
- 5. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of $\frac{1}{2}$ inch gypsum board or the equivalent applied to the garage means of $\frac{1}{2}$ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
- 6. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211
- 7. Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's building code.
- *8. **Guardrails & Handrails:** A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". (Sections 1021 & 1022.0)
- *9. Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
- *10. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread, 7" maximum rise. (Section 1014.0)
- 11. The minimum headroom in all parts of a stairway shall not be less than 30 inches. (6' 8") 1014.4
- 12. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height

not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)

- 13. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. Section 1010.1
- 14. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self-closers. (Over 3 stories in height requirements for fire rating is two (2) hours.) Section 710.0
- 15. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment. Table 302.1.1
- 16. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and F-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2

- 17. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. Section 921.0
- 18. The Fire Alarm System shall be maintained to NFPA #72 Standard.
- 19. The Sprinkler System shall maintained to NFPA #13 Standard.
- 20. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
- 21. Section 15-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 22. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.

- *23. Ventilation shall meet the requirements of Chapter 12 Sections 1210. Of the City's Building Code. (crawl spaces & attics)
- *24. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade.
- 25. All requirements must be met before a final Certificate of Occupancy is issued.
- *26. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National Building Code/1996).


27. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)

- *28. Please read and implement the attached Land Use-Zoning report requirements. → porch not to exceed existing footprint
- *29. The proposed 2x6" rafters @ 16" OC. 10' - 1" span does NOT meet The City's building code - A minimum of 2x8" @ 16" IS required.

30. _____

31. _____


32. _____



P. Samuel Hobbes Building Inspector

cc: Lt. McDougall, PFD
Marge Schumacher, Zoning Administrator

New Island Avenue
Peck Island, Me



My 2 LOTS are 84-N-27 +
84-N-26

R.O. "Ted" Schmidt
9-18-98

September 18, 1998

Peaks Island Porch Specifications
Lots 84-N-27 & 84-N-26
R.O. "Ted" Schmidt

Foundation of main part of porch, will pored concrete directly onto bedrock. I have some steel pins into the bedrock.

There may be masonry above and around the pored foundation. I have some rock pieces to use, also some brick.. My excavation is down to bedrock. I already have the form in place to pore concrete. This was under my last permit, now expired.

The uprights may be masonry or 6X6 timbers, depending on how far the masonry goes. The porch floor will be of 2X6 construction. The uprights by the cellar door may be masonry, or wood timber posts upon suitable pored footings, depending on how far we go with masonry.

The cellar door is already in under my last permit. The other doors and windows are not selected yet, but will be suitable units with at least double 2X6 headers. These are needed to replace the old ones where the porch is going. The roof will be of 2X6 construction, or heavier.

The masonry will be left exposed, if it is above ground. The rest of the structure will be covered with suitable siding. Maybe wood shingles, or other materials.

The space under the porch could be left open, but will probably be enclosed and have a door to the basement like space to keep cats out.

The size of the porch and steps will be 10' wide, and as long as the house, namely 26.6'. However, there may be some overhang for the roof, the porch floor, etc.

The footing wall is 16" thick, and it is already built under my last permit. It needs to be inspected before the pore.

Porch Post Rafters
2x8 or more
Double 2x10 or
more.

6x6 Post
To Post Timber

Joists
2x6 Floor under
16

2x10 Double WINDY.
6x6 Post TO MASONRY
Whole Post may be
masonry if
I have enough
masonry.

Door
have w/ 1/2
2x6
Timber
or Masonry
or 2x8's

Cellar
Door
6x6
Post
TO MASONRY
Whole Post
may be
masonry

2x6 Double or more
New
Window
have
Floor
of
Porch

← 24" →

SPACE UNDER
PORCH.

6x6 Post
To Post
Timber

Board Timber
2x6
2x8
2x10

6x6
Post
TO MASONRY

Board
Post

Post
w/ 2x8's
or 2x10's

26' 6"

Double 2x10

TOP VIEW
PORCH FLOOR



10'

Double 2x10

Double 2x10

↳ 2x6

16" on Center

2x10
Doubled

26.6 Feet

TOP VIEW OF
PORCH ROOF

2x10
Doubled

→ Rafter
2x8

16" on center.

10'