Location of Construction:			Phone	Dermit No
15 Merriam St, Peaks Isl	Owner: Weymouth, La	wrence & Anne	Phone:	Permit No:970949
Owner Address:	Lessee/Buyer's Name:	Phone:	BusinessName:	DEDMIT ICCHED
15 Merriam St Peaks Isl	04108	774-1067		PERMIT ISSUED
Contractor Name:	Address:	Phone:		Permit Issued:
Rob deSousa	766-2920		SEP - 5 1997	
Past Use:	Proposed Use:			
	Same	\$ 7,400.00	\$ 55.00	- OITY OF DODTLAND
1-fam		FIRE DEPT. A		CITY OF PORTLAND
	bame		enied Use Group R 3 Type: 5	Zone: CBL:
		Signature:	BOC + 96 Signature: Hollow	Zone: CBL: 085-J-017
Proposed Project Description:	poposed Project Description: Signature: Sign		Zoning Approval:	
			pproved	0 O Enocial Zono of Povious:
			approved with Conditions:	□ Special Zone or Reviews: /
Construct Dormer, Heighted	l alter existing roof	1	Denied	U U Wetland
				Flood Zone
		Signature:	Date:	
Permit Taken By: Mary Gresik	Date Applied For:	28 August 1997		Site Plan maj 🗆 minor 🗆 mm 🗆
				Zoning Appeal
1. This permit application does not preclude the A	Applicant(s) from meeting applicable	State and Federal rules.		□ Variance
2. Building permits do not include plumbing, se	ntic or electrical work			
		suuanca Ealsa informa		□ Conditional Use □ Interpretation
3. Building permits are void if work is not started within six (6) months of the date of issuance. False informa- tion may invalidate a building permit and stop all work				
tion may invalidate a building permit and stop	o un work.			Denied
				Historic Preservation
		, ⁵ 4		Does Not Require Review
				□ Requires Review
		2 **		
				Action:
	CERTIFICATION			
I hereby certify that I am the owner of record of the	en Approved with Conditions			
authorized by the owner to make this application a	on, Denied			
if a permit for work described in the application is	issued, I certify that the code official'	s authorized representativ	ve shall have the authority to enter	
areas covered by such permit at any reasonable ho	ur to enforce the provisions of the co-	de(s) applicable to such I	permit	
(-th)(-		28 August 19	97	DA4
SIGNATURE OF APPLICANT Lawrence Wey	mouth ADDRESS:	DATE:	PHONE:	
RESPONSIBLE PERSON IN CHARGE OF WORK			PHONE:	
	x,			
White-Pe	rmit Desk Green–Assessor's Ca	nary-D.P.W. Pink-Put	olic File Ivory Card-Inspector	
				M. LEAFY

City of Portland, Maine – Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

	store of			Date
COMMENTS	Tuchad in pornet & 20 4	alkel to on First Home (1) alkel to me home (TR) No me home (TR)	Inspection Becord	Type Foundation: Framing: Framing: Plumbing: Final: Other:
	A C	7.23.98 7		

Applicant: LAWrence Weymouth Date: 9/4/97 Address: 15 Merrian St. PT. C-B-L: 85-J-17 HECK-LIST AGAINST ZONING ORDINANCE Date - EXISTY 1900'S Zone Location - IL-2 Interior or corner lot -Proposed Use/Work - Construct . Dormen / raise rouf Sewage Disposal -Lot Street Frontage using The old Section of 14-436 which Allows This Front Yard -Rear Yard -Side Yard -Projections -Width of Lot -Height - only 30' toridge (which is Not The true measuring Spot Lot Area -Lot Coverage/ Impervious Surface -Area per Family -**Off-street** Parking -Loading Bays -Site Plan -Not within Shoreland Zoning/ Stream Protection -Flood Plains - NOT within

BUILDING PERMIT REPORT

DATE	<u>SepT.97</u> ADDRESS: 15 Merriam 97, P.I.
REAS	ONFORPERMIT: Jo Construct dormen (10'x12')
BUILI	DING OWNER: Neymouth, L. C.A.
CONT	RACTOR: Rob De Sousa
PERM	IIT APPLICANT: OWNER APPROVAL: */*8 ×9 ×10,×11 ×12 ×16 DENIED
	×21×27×28
	CONDITION(S) OF APPROVAL
XL	This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
2.	Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services
_	must be obtained. (A 24 hour notice is required prior to inspection)
3. 4.	Precaution must be taken to protect concrete from freezing. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is
4.	done to verify that the proper setbacks are maintained.
5.	Private garages located <u>beneath habitable rooms</u> in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from
	adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire
	resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from
	the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage means of 1/2
	inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
б.	All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA
7.	National Mechanical Code/1993) U.L. 103. Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's
1.	building code.
¥ ^{8.} ∙	Guardrail & Handrails A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that
	would provide a ladder effect.
¥ 9.	Headroom in habitable space is a minimum of 7'6".
$\mathfrak{L}^{10.}$	Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group
₹n.	minimum 11" tread. 7" maximum rise.
د ۱۱. ۲۱2.	The minimum headroom in all parts of a stairway shall not be less than 80 inches. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or
	exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as <u>means of egress or rescue</u> they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.
13.	Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable
14.	when it exits directly from the apartment to the building exterior with no communications to other apartment units. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with
14.	self closer's.
15.	The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.
× 16.	All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the
<u> </u>	 provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations): In the immediate vicinity of bedrooms
	In all bedrooms
	• In each story within a dwelling unit, including basements In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and

1-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

- 17. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
- 18. The Fire Alarm System shall be maintained to NFPA #72 Standard.
- 19. The Sprinkler System shall maintained to NFPA #13 Standard.
- 20. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
- 21. No construction or demolition work shall begin until you have obtained permits for dumpsters or containers. A work Stop Order shall be issued if this requirement is not met.
 - 22. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
 - 23. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
 - 24. This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's office.
 - 25. Ventilation shall meet the requirements of Chapter 12 Sections 1210. of the City's Building Code.
 - 26. All electrical and plumbing permits must be obtained by a Master Licensed holders of their trade.
 - All requirements must be met before a finial Certificate of Occupancy is issued.

\$ 28. 5 1STen mus 29. 90124 95 9 æe a

C: LI. McDougall, PFD Marge Schmuckal

!

Robert deSousa

11 Merriam St Peaks Island, ME 04108

QUOTE

Date: 8 - 10 - 97 JOB LOCATION BILL TO 13 Merkiam St ANNe 3 Loric Waymath Peak Island Me 04108 attic addition estimate for 13 Merrian St PeakeTsland 10' X 12 ad in to 3RD Estinate loft - Space Hemoral COURKS histing KM-en on Rean ot Root onmer 10 RAPE with 2x 2X4 2×6 Framing below sil Exhisting Zox sill 4 × 4 to at 6ASE thru Ack asphalt shuiles, sidius to <u>shi</u> price is For framing, Rooting, would floors - Insulation in walls ? ceiling , Roof satt vents included - Interior Pinish If be done by home ownen Later

15 Merrian St P.I