LG
Life's Good

With LG
it's all p

Reviewed for Code Compliance
Inspections Division
Approved with Conditions

Date: 01/02/15

inter solar award 2013 WINNER

PLUS X AWARD achieved for High Quality Ecology

Mono X® NeON

LG300N1C-B3

60 cell

Introducing Mono X® NeON module series, which uses highly efficient n-type materials, an elaborate process control adopting a semiconductor processing solution and a double-sided structure. Our R&D concentrates on developing a product that is not only efficient, but strives to increase practical value for customers.

APPROVED PRODUCT
MCS
KM 564573 BS EN 61215
Photovoltaic Modules

N-Type Material

Mono X® NeON uses n-type cells, boasting higher mobility of electric charge, resulting in higher generation efficiency.

Near Zero LID (Light Induced Degradation)

The n-type cells used in Mono X® NeON have almost no boron, which may cause the initial efficiency to drop, leading to less LID.

Nano Level Control

Mono X® NeON uses the Nano-level process control predominant in semiconductor processing process, which ensures less electric loss from internal defects.

Double-Sided Cell Structure

The rear of the cell used in Mono X® NeON is designed to contribute to generation; the light beam reflected from the rear of the module is reabsorbed to generate a great amount of additional power.

16.8kg Light Weight | Convenient Installation | EL Test | 2% Current Sorting | 25yrs Linear Warranty | +3% Positive Power Tolerance

About LG Electronics

LG Electronics is a multinational corporation committed to expanding its capacity with solar energy business as its future growth engine. Our a solar energy source research program was launched in 1985, backed by LG Group's rich experience in semi-conductors, LCD, chemistry and electronic materials industry. We successfully released the first Mono X® series to the market in 2010 which exported to 32 countries in 2 years. In 2013, Mono X® NeON won "Intersolar Award", which proved its leading innovation in the industry.

MonoX® NeON

LG300N1C-B3

Reviewed for Code Compliance
Inspections Division
Approved with Conditions

Date: 01/02/15

Mechanical Properties

Cells	6 x 10
Cell vendor	LG
Cell type	Monocrystalline
Cell dimensions	156.5 x 156.5 mm / 6 x 6 in
# of busbar	3
Dimensions (L x W x H)	1640 x 1000 x 35 mm 64.57 x 39.37 x 1.38 in
Static snow load	5400 Pa / 113 psf
Static wind load	2400 Pa / 50 psf
Weight	16.8 ± 0.5 kg / 36.96 ± 1.1 lb
Connector type	MC4 connector IP 67
Junction box	IP 67 with 3 bypass diodes
Length of cables	2 x 1000 mm / 2 x 39.37 in
Glass	High transmission tempered glass
Frame	Anodized aluminum

Certifications and Warranty

Certifications (In Progress)	IEC 61215, IEC 61730-1/-2, UL 1703, ISO 9001, IEC 61701, IEC 62716
Product warranty	10 years
Output warranty of Pmax (measurement Tolerance ± 3%)	Linear warranty* NEW

* 1) 1st year: 98%, 2) After 2nd year: 0.7%p annual degradation, 3) 81.2% for 25 years

Temperature Coefficients

NOCT	45 ± 2 °C
Pmpp	-0.41 %/°C
Voc	-0.29 %/°C
Isc	0.04 %/°C

Characteristic Curves

Electrical Properties (STC *)

MPP voltage (Vmpp)	[illegible]
MPP current (Impp)	9.40
Open circuit voltage (Voc)	39.8
Short circuit current (Isc)	9.98
Module efficiency (%)	18.3
Operating temperature (°C)	-40 ~ +90
Maximum system voltage (V)	1000 (IEC), 600 (UL)
Maximum series fuse rating	20
Power tolerance (%)	0 ~ +3

* STC (Standard Test Condition): Irradiance 1000 W/m2, module temperature 25 °C, AM 1.5
* The nameplate power output is measured and determined by LG Electronics at its sole and absolute discretion.

Electrical Properties (NOCT*)

	300 W
Maximum power (Pmpp)	220
MPP voltage (Vmpp)	29.3
MPP current (Impp)	7.50
Open circuit voltage (Voc)	36.9
Short circuit current (Isc)	8.05
Efficiency reduction (from 1000 W/m2 to 200 W/m2)	< 2%

* NOCT (Nominal Operating Cell Temperature): Irradiance 800 W/m2, ambient temperature 20 °C, wind speed 1 m/s

Dimensions (mm/in)

* The distance between the center of the mounting/grounding holes.

LG Life's Good

North America Solar Business Team
LG Electronics U.S.A. Inc
1000 Sylvan Ave, Englewood Cliffs, NJ 07632

Contact: lg.solar@lge.com
www.lgsolarusa.com

Product specifications are subject to change without notice.
"LG Life's Good" is a registrated trademark of LG Corp.
All other trademarks are the property of their respective owners.
DS-N-60-C-US-F-EN-31002

Copyright © 2014 LG Electronics. All rights reserved.
06/17/2014

With LG, it's all possible.