City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Location of Construction: Phone: Permit No: *** 500 Seashore Ave Peaks Island Will Winkelman **** 774-0111 Lessee/Buyer's Name: Owner Address: Phone: BusinessName: Permit Issued: Contractor Name: Address: Phone: UEU 2 0 1999 COST OF WORK: PERMIT FEE: Past Use: Proposed Use: \$6,000 60.00 Single family INSPECTION: FIRE DEPT. Approved C100203-49 Use Group 13-3 Type: 5/ ☐ Denied Zone: CBL: BOCAGE Signature: Zoning Approval: Proposed Project Description: PEDESTRIAN ACTIVITIES DISTRICT Action: Approved Special Zone or Reviews Approved with Conditions: ☐ Shoreland 14x23 Addition to an existing shed 12x14 Denied ☐ Wetland ☐ Flood Zone 7 □ Subdivision Date: Signature: ☐ Site Plan maj ☐minor ☐mm ☐ Permit Taken By: Date Applied For: K Dec 17 1999 K Zoning Appeal □ Variance This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. 1. ☐ Miscellaneous 2. Building permits do not include plumbing, septic or electrical work. ☐ Conditional Use 3. Building permits are void if work is not started within six (6) months of the date of issuance. False informa-□ Interpretation ☐ Approved tion may invalidate a building permit and stop all work... ☐ Denied Historic Preservation ■ Not in District or Landmark ☐ Does Not Require Review PERMIT ISSUED WITH REQUIREMENTS ☐ Requires Review Action: CERTIFICATION □ Appoved ☐ Approved with Conditions I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been □ Denied authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all Date: areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit Dec 20 1999 SIGNATURE OF APPLICANT ADDRESS: DATE: PHONE:

White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

PHONE:

CEO DISTRICT

RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE

COMMENTS

				1	
8/30/01	Set bruchs 01	4. Project	not finde	Jeg. an	
/ /		0			
					TO THE TOTAL
1/1 / Jan					
		111111111111111111111111111111111111111			
				Inquestion Decord	
			Туре	Inspection Record	Date
			Framing:		
			Final:		
			Other:		

BUILDING PERMIT REPORT Seushore Ave. P.I. CBL: 086-A-013 PERMIT APPLICANT: -3 CONSTRUCTION TYPE: 5 3 CONSTRUCTION COST: 6,000,000 PERMIT FEES: 60,000 The City's Adopted Building Code (The BOCA National Building code/1996 with City Amendments) The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993) This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) "ALL LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING." Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2 Foundations anchors shall be a minimum of 12" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' O.C. between bolts. Section 2305.17 Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code. Precaution must be taken to protect concrete from freezing. Section 1908.0 It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage means of 1.2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCN 1996) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211 10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code. X11. Guardrails & Handrails: A guardrail system is a system of building components located near the oopen sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A,B.H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38"). Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". (Sections 1021 & 1022.0). Handrails shall be on both sides of stairway. (Section 1014.7) X 12. Headroom in habitable space is a minimum of 7'6". (Section 1204.0) 13. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 1/2" maximum rise. All other Use Group minimum 11" tread, 7" maximum rise. (Section 1014.0) 14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4 (11) 3 3 (11) 1 (11) 1 (11) 15. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508)mm, and a minimum net clear opening of 5.7 sq. ft. (Section 1010.4) 16. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)

(Over 3 stories in height requirements for fire rating is two (2) hours. (Section 730.0)

18. The boiler shall be protected by enclosing with (1) hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)

17. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's.

-X 1 9.	
•	Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be
	installed and maintained at the following locations):
	In the immediate vicinity of bedrooms
	In all bedrooms
	In each story within a dwelling unit, including basements
20.	A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
	(Section 921.0)
21.	The Fire Alarm System shall maintained to NFPA #72 Standard.
22.	The Sprinkler System shall maintained to NFPA #13 Standard.
	All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the
	City's Building Code. (The BOCA National Building Code/1996)
24.	Section 25 - 135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any
	street or sidewalk from the time of November 15 of each year to April 15 of the following year".
25.	The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a
	design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection
	Services.
26.	Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).
A ²⁷ .	All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all
	electrical (min. 72 hours notice) and plumbing inspections have been done.
28.	All requirements must be met before a final Certificate of Octo party is issued.
× 29.	All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (The BOCA National Building
20	Code/1996).
30.	Ventilation of spaces within a building shall be done in accordance with the City's Mechanical code (The BOCA National Mechanical
60	Code/1993). (Chapter M-16) Please read and implement the attached Land Use Zoning report requirements.—This Shall Not turn who A 2nd dwell well as
131	Please read and implement the attached Land use Zoning report requirements. (PASS START) ON TWO
32.	Boring, cutting and notching shall be done in accordance with Sections 2305.3, 2305.3.1, 2305.4.4 and 2305.5.1 of the City's Building Code.
X 33.	Bridging shall comply with Section 2305.16. Glass and glazing shall meet the requirements of Chapter 24 of the building code. (Safety Glazing Section 2405.0)
X 34.	All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code/1996).
33.	All signage, shari be done in accordance with section 5102.0 signs of the City's Building Code, (The BOCA Manorial Building Code 1970).
-	

Co. McDougall, PFD
Marge Schmuckal, Zoning Administrator

PSH 11/25/99

**On the basis of plaus submitted and conditions placed on these plaus any deviations shall require a separate approval.

...THIS PERMIT HAS BEEN ISSUED WITH THE UNDERSTANDING THAT ALL THE CONDITIONS OF THE APPROVAL SHALL BE COMPLETED. THEREFORE, BEFORE THE WORK IS COMPLETED A REVISED PLAN OR STATEMENT FROM THE PERMIT HOLDER SHALL BE SUBMITTED TO THIS OFFICE SHOWING OR EXPLAINING THAT THE CONDITIONS HAVE BEEN MET. IF THIS REQUIREMENT IS NOT RECEIVED YOUR CERTIFICATE OF OCCUPANCY SHALL BE WITHHELD.

****CERTIFICATE OF OCCUPANCY FEE \$50.00

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application Additions/Alterations/Accessory Structures

To Detached Single Family Dwelling

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Address of Construction 500 56	EASHORE AVE - +	EAKS KLAND
		DA./,
Tax Assessor's Chart, Block & Lot Number	Overer.	Telephone#: @ WIPF
Charl# 86 Block# A Lot# /3	WILL WWEELMAN	774 0111
Owner's Address	Lessee/Buyer's Name (If Applicable)	Cost Of Work: Fee
SAME		\$ 6,000 - \$ 60 -
Proposed Project Description:(Please be as specific as possil	ole)	,
14 x 23 SINGLE LEVGL A	DOITION TO AN EXISTING	12×14 SHED.
Contractor's Name, Address & Telephone		Rec'd By:
ME		
Separate permits are required for	Internal & External Plumbing, HV	C and Electrical installation
•All construction must be conducted in con		
	iducted in compliance with the State of M	
,	ly with the 1996 National Electrical Code	
-HVAC(Heating, Ventilation and Air Co		h the 1993 BOCA Mechanical CodeCTIO
You must Include the following with yo	CITY OF PORTLAND, ME	
	Your Deed or Purchase and Sale A	oreement
,	f your Construction Contract, if a	9 11 11 1000 1 3 1000
		tvaliable
	A Plot Plan (Sample Attached)	
If there is expansion to the structure, a		
	l existing buildings (if any), the proposed st	
	is porches, a bow windows cantilever section	os and roof overhangs, as well as, sheds.
pools, garages and any other accessor		
 Scale and required zoning district seth 	acks	
	NOTE OF A STATE OF	

4) Building Plans (Sample Attached)

A complete set of construction drawings showing all of the following elements of construction:

- Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)
- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas
 equipment. HVAC equipment (air handling) or other types of work that may require special review must be included.

Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.

Signature of applicant:	V	M		A	PA -		Date:	1.2	/ /	7/	90	7	
Building Permit Fee: \$3	0.0	0	fdY	Üς.	e 1 31 8 1000 cost	plus \$6.00 per \$1.	.000.00 cons	strucil	on co	ost	therea	fter.	

ONINSPICORRESPIMNUGENTIAPADSFD WPD

Inspection Services Michael J. Nugent Manager



Department of Urban Development Joseph E. Gray, Jr. Director

CITY OF PORTLAND



Building or Use Permit Application Additions/Alterations/Accessory Structures To Detached Single Family Dwelling

As an applicant for a building permit, you are about to enter into a relationship with our Office. We welcome any questions, comments or suggestions that will make the process more efficient. Attached you will find an application and some samples of the submissions you will provide at application time. Please read <u>ALL</u> of the information and if you need any further assistance please call 874-8703 or 874-8693.