City of Portland, Maine – Buildi		1 389 Congress 3					
Location of Construction:	Owner:		Phone:	Permit No:			
Owner Address:	Lessee/Buyer's Name:	Phone:	BusinessName:	000614			
-SAA*				PERMIT ISSUED			
Contractor Name:	Address:	Phone:		Permit Issued:			
Past Use:	Proposed Use:	COST OF WORK:	PERMIT FEE:	JUN 8 2000			
		\$ 750.00	\$ 30,00				
single famiy	same	FIRE DEPT. Ap	ired INSPECTION: Use Group: U Type:	CITY OF PORTLAND			
Dropogad Project Description:		Signature:	Signature: Aff	Zoning Approval:			
Proposed Project Description: 9x12 shed	F2 2	Action: Ap	proved with Conditions: nied Date:	Special Zone or Reviews: Shoreland Wetland Flood Zone Subdivision			
Permit Taken By:	Date Applied For:			☐ Site Plan maj ☐minor ☐mm ☐			
Territor Taken By.		ne 6 2000 K		Zoning Appeal			
 Building permits do not include plumbing, Building permits are void if work is not startion may invalidate a building permit and 	ted within six (6) months of the date of iss	uance. False informa-		☐ Miscellaneous ☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied			
			PERMIT ISSUED WITH REQUIREME	Historic Preservation Not in District or Landmark Does Not Require Review Requires Review Action:			
	CERTIFICATION		*	DAnnoved			
I hereby certify that I am the owner of record of authorized by the owner to make this application if a permit for work described in the application areas covered by such permit at any reasonable	the named property, or that the proposed we n as his authorized agent and I agree to co is issued, I certify that the code official's	onform to all applicable la authorized representative e(s) applicable to such pe	ws of this jurisdiction. In additi- shall have the authority to enter	on, Denied			
SIGNATURE OF APPLICANT	ADDRESS:	June 7 2000 DATE:	PHONE:	DEPMIT ISSUED			
				WITH REQUIREMENT			
RESPONSIBLE PERSON IN CHARGE OF WO	RK, TITLE		PHONE;	CEO DISTRICT			
	Permit Desk Green-Assessor's Can		AC PROPERTY AND A PROPERTY AND	V			

-

gi-

SHED AT 53 LMTHER ST. IR-2 Ene

Résidence: of wendy Ashley Rearry - N/A

Sideyd-25'reg-25'show

Style: Greek Revival Farmhouse. 5/fed

will closely match details of house

Such as clapboard siding, pitch of

Roof, soffits and returns, and Rake

monldings.

9112 = 108th

shed - Ates hote shed sits

back 25' from

luther st, 25'

from House and

30' from mediest

neighbors property.

Cost: Materials 90% Recycled Immser

obtained for free.

material cost #750

1260r (donated)

#750

BUILDING PERMIT REPORT

DATE: 7 June 766 of ADDRESS: 5 3 Luther 57. CBL: \$87-E-615" REASON FOR PERMIT: 9'X 12' 5he of BUILDING OWNER: W. 135/21
REASON FOR PERMIT: 9 x 12 Shoof
BUILDING OWNER: W. Ashled
PERMIT APPLICANT: CONTRACTOR Paul Brahams
USE GROUP: U _CONSTRUCTION TYPE: 5 B _CONSTRUCTION COST: 750.02 PERMIT FEES: 340
The City's Adopted Building Code (The BOCA National Building code/1999 with City Amendments) The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)
CONDITION(S) OF APPROVAL
This permit is being issued with the understanding that the following conditions are met: * 36
This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. 2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) "ALL LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING."

- 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
- Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a
 maximum 6' O.C. between bolts. Section 2305.17
- 5. Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.

6. Precaution must be taken to protect concrete from freezing. Section 1908.0

- It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the
 proper setbacks are maintained.
- 8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1999)
- All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211
- 10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.
- 11. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42". In occupancies in Use Group A,B.H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such thet a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Exception: Handrails that form part of a guard shall have a height not less than than 36" and not more than 42". Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". (Sections 1021 & 1022.0). Handrails shall be on both sides of stairway. (Section 1014.7)
- 12. Headroom in habitable space is a minimum of 7'6'. (Section 1204.0)
- 13. Stair construction in <u>Use Group R-3 & R-4 is a minimum of 10" tread and 7 %" maximum rise.</u> All other Use Group minimum 11" tread, 7" maximum rise. (Section 1014.0)
- 14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4
- 15. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508)mm, and a minimum net clear opening of 5.7 sq. ft. (Section 1010.4)
- 16. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)
- 17. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours. (Section 710.0)
- 18. The boiler shall be protected by enclosing with (1) hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)

- 19. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1999), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements
- 20. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)
- 21. The Fire Alarm System shall be installed and maintained to NFPA #72 Standard.
- 22. The Sprinkler System shall be installed and maintained to NFPA #13 Standard.
- 23. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1999)
- 24. Section 25 135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 25. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
- Ventilation and access shall meet the requirements of Chapter 12 Sections 1210.0 and 1211.0 of the City's Building Code. (Crawl spaces & attics).
- 27. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all electrical (min. 72 hours notice) and plumbing inspections have been done.
- 28. All requirements must be met before a final Certificate of Occupancy is issued.
- All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (The BOCA National Building Code/1996).
- 30. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical code (The BOCA National Mechanical Code/1993). (Chapter M-16)
- 31. Please read and implement the attached Land Use Zoning report requirements.
- 32. Boring, cutting and notching shall be done in accordance with Sections 2305.3, 2305.3.1, 2305.4.4 and 2305.5.1 of the City's Building Code.
- 33. Bridging shall comply with Section 2305.16,
- 34. Glass and glazing shall meet the requirements of Chapter 24 of the building code. (Safety Glazing Section 2406.0)
- 35. All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code/1999).

36	Re} SeT	-0 ~C	Dha	112	r 5,	ulde	199	Cal	aZ,	2520	C 720-	7 Se	4/5	25	For	
	<u> 5</u> eT	back	7/5	9/11/6	0110	27	•//									

Hoffses, Bullding Inspector

Marge Schmuckal, Zoning Administrator

PSH 1/26/00

**On the basis of plans andmitted and conditions placed on these plans any deviations shall require a separate approval.

... THIS PERMIT HAS BEEN ISSUED WITH THE UNDERSTANDING THAT ALL THE CONDITIONS OF THE APPROVAL SHALL BE COMPLETED. THEREFORE, BEFORE THE WORK IS COMPLETED A REVISED PLAN OR STATEMENT FROM THE PERMIT HOLDER SHALL BE SUBMITTED TO THIS OFFICE SHOWING OR EXPLAINING THAT THE CONDITIONS HAVE BEEN MET. IF THIS REQUIREMENT IS NOT RECEIVED YOUR CERTIFICATE OF OCCUPANCY SHALL BE WITHHELD.

****CERTIFICATE OF OCCUPANCY FEE \$50.00

**** All PLANS THAT REQUIRE A PROFESSIONAL DESIGNER'S SEAL,(AS PER SECTION114.0 OF THE BUILDINGCODE) SHALL ALSO BE PRESENTED TO THIS DIVISION ON AUTO CAD LT.2000, OR EQUIVALENT.

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application Additions/Alterations/Accessory Structures

To Detached Single Family Dwelling

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

GEAK2

53 LUTHER

<u> </u>	7 7 7 7 7 7
Lessee/Buyer's Name (If Applicable)	Cost Of Work: Fee 30 0
ible) \$ 3×6 FRAMing nense.	15 16" O.C. Solding
	Rec'd By:
oly with the 1996 National Electrical Code conditioning) installation must comply with our application: Your Deed or Purchase and Sale A of your Construction Contract, if a of A Plot Plan (Sample Attached) complete plot plan (Site Plan) must it all existing buildings (if any), the proposed striks porches, a bow windows cantilever section by structures.	as amended by Section 6-Art III. h the 1993 BOCA Mechanical Code. Agreement vailable include: vecture and the distance from the actual
Building Plans (Sample Attached) gs showing all of the following eleme	
	ible) # 3×6 FRAMMy Menbe To 75-6694 External Plumbing, HVA mpliance with the 1996 B.O.C.A. Building moducted in compliance with the State of M ply with the 1996 National Electrical Code conditioning) installation must comply with ou application: Your Deed or Purchase and Sale A of your Construction Contract, if a) A Plot Plan (Sample Attached) complete plot plan (Site Plan) must in all existing buildings (if any), the proposed str siks porches, a bow windows cantilever section ry structures. backs Building Plans (Sample Attached)

Date: Building Permit Fee: \$30.00 for the 1st \$1000.cost plus \$6.00 per \$1,000.00 construction cost thereafter.

Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment, HVAC equipment (air handling) or other types of work that may require special review must be included. Certification I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued. I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the

codes applicable to this permit.

Floor Plans & Elevations Window and door schedules

Foundation plans with required drainage and dampproofing

Location/Address of Construction:

Tax Assessor's Chart, Block & Lot Number

FRAMONOT: Floor Joist well studs & plètes, Rafters are all 3x6". Joists & Rafters are 16" on center_ DOUT = 30" × 6'8" windows: 20 36" x 20"(4). 10 16 x 24" 5 H E D A T 53 LUTHER ST = 9' × 12' × 14' sand tuise/concrete footings (if allowed)
otherwise on Blocking or stone.

.